WHAT'S NEW IN Global Mapper v13.1

- **Significant New Features**
  - Added support for PDF import/export to 64-bit builds.
  - Significantly sped up depression filling step when generating watersheds/drainage areas.
  - Added new built-in Topo Maps category to File->Download Online Imagery/Data menu command and added new Brazilian Topo Map source to the list.
  - Added built-in access land cover datasets, like NLCD for the US and CORINE for Europe, using the File->Download Online Imagery/Data menu command.
  - Added support for generating roughness grids by right-clicking on a land cover raster or grid layer in the Control Center and selecting the option to generating roughness. Currently the CORINE land cover and MODIS VCF are supported as input data types.
  - Added option to allow cropping any loaded features to one or more selected area features to the right-click menu of the Digitizer/Edit.
  - Added support for exporting area and line features to CSV files using WKT coordinate formatting.
  - Added option to Digitizer Tool to copy selected attributes from selected areas to any areas contained (partially or fully) within selected areas. Useful for applying things like land-use attributes to smaller areas.
  - Added support for adding new OSM, TMS, and Google Maps tiled sources using a custom URL naming scheme. You can now provide URLs with %x, %y, and %z variables in them to have the tile URL setup however the source requires.
- **New Supported Formats**
  - Added support for loading LASzip (compressed Lidar) files.
  - Added support for loading .las.gz (gzipped-Lidar LAS) files.
  - Added support for loading IHS 297/298 Well Data point files.
  - Added support for loading GeoJSON files.
  - Added support for loading TRMM Precipitation Grid files from NASA.
  - Added support for loading WAsP Resource Grid (.wrg/.rsf) files.
  - Added support for loading IGF DIS terrain grids.
  - Added support for loading INM 3TX terrain grids.
  - Added support for loading Micropath 3CD terrain grids.
  - Added support for exporting area features to SMT Kingdom Polygon files.
  - Added support for loading GML files directly from .gz archives.
  - Added support for loading QGIS and CLR palettes.
  - Added support for exporting data to multi-band and high bit-depth NITF files.
  - Added support for exporting terrain data to NITF format files.
- **Projection/Datum Changes**
  - Added built-in Minnesota County datum with pre-built zones for each special Minnesota projection.
  - Added built-in 3TM (Alberta), Trinidad Grid, and Universal Polar Stereographic North and South Zone projections.

- Added Krasovsky 1940 Ellipsoid, NAD27 (Michigan) [for Lambert Michigan State Plane zones only], Potsdam 1983, Tete (Mozambique) and VN-2000 (Vietnam) datums.
- Added Clarke 1866 (Michigan) as built-in ellipsoid.
- Added kilometers as a built-in unit.
- Improved storage and retrieval of datums with non-Greenwich meridians from WKT-format PRJ files.
- Made false easting/northing work for Bonne projection.
- Made 'South American 1969' datum automatically use SAD 1969 (Brazil) specialization if the location being converted is in Brazil.
- Updated American Samoa 1962 datum conversion to use NADCON conversion tables for the best possible accuracy.
- Fixed problems parsing degree projection attributes from GeoPDF files that aren't just straight decimal numbers (i.e. '69 W' rather than '-69').
- Allowed Equidistant Conic B projections to be saved to WKT PRJ files.
- Fixed problems in v13.00 release with Old Israeli Datum, MGI Croatia-Serbia, MGI Slovenia, Kertau 1948 (Malaysia), and S-42 (Azerbijan/Georgia) datums.
- Corrected Bursa-Wolfe transformation parameters provided as part of a TOWGS84 part of a PRJ file. The rotation angles had been reversed for small rotation angles.
- Fixed extraction of projection information from ESRI .aux.xml files.
- Fixed issue with very large (i.e. over 20,000,000 meters magnitude or so) false easting or northing values in MapInfo files.
- Made the elevation units for vector files default to the units of provided projection if the elevation units are not explicitly specified.

- **Scripting Changes**
  - Allowed for interactive user provision of variable values using the PROMPT and PROMPT_TEXT parameters for the DEFINE_VAR script command. This allows you to run scripts that take user input!
  - Parameters that expect a value of YES or NO to enable or disable functionality can be enabled with just the parameter name. So rather than saying FLAG_PARAM_NAME=YES you can just say FLAG_PARAM_NAME to get the same behavior.
  - Updated COMBINE_LINES script command to allow CREATE_AREAS_FROM_LINES=YES to be specified for combining lines to areas from a script.
  - Added support for specifying bounds for many commands with an ADDRESS and RADIUS field.
  - Added support for BSB export with EXPORT_RASTER script command.
  - Updated EDIT_VECTOR command to allow special names like <Feature Name> or <Index in Layer> on right-side of ATTR_VAL parameter.
  - Added support for wildcards in FILENAME parameter to IMPORT_ARCHIVE command.
  - Fixed bug from v13.00 that caused POLYGON_CROP_BBOX_ONLY parameter for EXPORT_RASTER command not work.

    - Added support for exporting XY_COLOR format files using the EXPORT_RASTER script command.
    - Made variable replacement work inside DEFINE_MAP_LAYOUT sections.
    - Added support for PTS_AT_INTERSECTIONS parameter for EDIT_VECTOR script command to allow creating points at line intersections.
- Fixed checkered export from some online sources, like 1 arc second NED and SRTM.
- Added new right-click option to Swipe Tool to maintain the swipe after releasing the left mouse button. Then the swipe will be maintained for any exports.
- Added support for using Epanechnikov kernel when calculating density grids.
- Updated density grid generation to be volume-preserving.
- Added options to density grid generation to specify how many sample cells will be in each radius and what area units to report using.
- Added 'Automatic' option for DPI on PDF export. This will automatically use a DPI that causes the full resolution of the most detailed raster layer involved in the export to be maintained if possible.
- Updated 3D viewer so that arrow keys and page up/down will pan and zoom the map in non-walk mode.
- Added option to select area features that contain the selected point feature(s) to the Advanced Selection submenu of the Digitizer Tool when points are selected.
- Added option when right-clicking on a map from a map catalog with the Digitizer/Edit Tool active to remove that map from the map catalog.
- Improved automatic placement of point labels when they cannot be placed to the top right of points without colliding with another label. Now more locations than just the bottom left will be checked to see if they fit there.
- Allow much larger view shed calculations as the tables for calculation can spill to disk rather than having to be in memory.
- Added progress reporting to view shed calculation when applying vector obstructions.
- Allowed for the same text label for point and area features to be displayed multiple times in the same area of the screen so long as they don't overlap.
- Sped up calculation of contrast adjustment statistics for some very large images.
- Prevent display of 'Map Data Not Available' tiles when working with online data sources like 'World Imagery' that don't contain data at all zoom levels at all locations.
- Added option when batch converting to MapInfo formats to control whether or not NAME attributes are added.
- Added support for automatically using a .gcp control point file accompanying an image file to rectify the image when loading it.
- Added option to control whether or not sub-folders are searched when loading all files from a directory tree.
- Made the load of some palette-based raster formats (like TIFF files) look for more descriptive palette files in the same folder as the TIFF file to improve the text display on the status bar.
- Updated projection of point along a distance and bearing to use more accurate Vincenty formula so that distances should match exactly.
- Dramatically sped up the creation of buffers around very complex shapes in some cases.
- Added support for some curved arc segments from ESRI File Geodatabase (GDB) data.

- Improved support for TextString rectangles from ESRI File Geodatabase (GDB) files. Now they just come in as text.
- Updated DXF and DWG exports to have new labeling option to include labels in same layer as area and line features that they come from rather than generic FEATURE_LABELS layer.
- Updated export of area and line features with a single elevation value to still create 3D features in exported DXF files.
- Made road icons scale based on the symbol scaling factor specified when exporting PDF files.
- Added new command to external control API command (GM_Ctrl_DeletePoint) to allow deleting existing point features that were added with GM_Ctrl_AddPoint.
- Added option to automatically split Garmin Raster Map exports into separate KMZ files if the result won't fit in a single KMZ that Garmin units can make full use of.
- Updated Measure Tool to add new options on right-click menu to always use the larger unit (like km for metric or miles for statute) and also to round the measured value to the nearest whole number.
- Updated creation of regular grid cropped to area to include cells where the center isn't inside the crop area if the option on the Advanced section of the General tab of the Configuration dialog is checked to keep pixels if any part is in the crop area.
- Added option when exporting vector data to KML files to control whether or not lines with per-vertex times are exported as 'Replay Tracks'.
- Updated elevation grid generation to allow a grid tightness threshold down to 0.5 grid spacings to allow getting a grid that exactly covers a regularly gridded set of input data.
- Added option to control whether or not tile organization is used for exported JPEG2000 files.
- Improved support for NLCD (National Land Cover Database) files by automatically detecting the palette for those files and making the land cover type name be added to the palette for display in the status bar as you move the cursor around the map.
- Made calculated density grids be saved to workspaces.
- Fixed issue creating buffer areas when the current view datum is different than the native datum for the feature being buffered.
- Added button to map catalog dialog allowing the removal of files that can't be found.
- Added option to Lidar LAS export to specify the File Source ID and Global Encoding values in the header.
- Added option to Lidar LAS export to specify which vertical CS/datum to store in the header.
- Made the bounds specified on an Export Bounds or other bounding box tab be displayed on the map as it is updated if possible.
- Fixed crash calculating cut-and-fill volumes with the Measure Tool over a range of heights.
- Added option to 'Prepend as Text' when calculating new attribute values.
- When prepending or appending text to attributes from the calculate attribute option of the Control Center, don't automatically provide an extra space character.
- Fixed problem with coloring of point clouds from Lidar files from v13.00 release.
- Updated the web format exports to treat an export PNG or JPG file where all pixels end

up as background pixels as "empty" so they should not be exported if the ‘Skip Empty Tiles’ option is checked.
- Fixed issue with ‘Show Labels for Lines of This Type’ setting not always working on the Line Styles tab of the Configuration dialog.
- Made Cancel button actually work when cancelling the creation of multiple buffer areas around selected area and line features with the Digitizer Tool.
- Fixed issue with sample spacing being incorrect for raster and elevation exports when gridding an export to selected areas and multiple areas resulting in the same output filename.
- Fixed loading of some online sources, like World Imagery and World Topo Maps, from workspace files.
- Made the last filename setting (i.e. use source filename or use quad filename/description) used be remembered when batch converting.
- Fixed inconsistency with ‘User Created Features’ layer still being displayed as ‘User Created and Modified Features’ in some locations.
- Fixed rare issue with some parts of double-precision Surfer Grid files not displaying.
- Updated reporting of Metadata for vector layers to separately report how many deleted and non-deleted area, line, and point features there are.
- Updated Control Center display to include the feature count next to each vector layer.
- Fixed font assignment when splitting up features based on an attribute from the Control Center.
- Updated creation of gridded surfaces by flattening areas to always use the flat area with the largest elevation at a given location if multiple areas are present at that location.
- Added new built-in ‘Course Line’ line type to control how GPS course lines are displayed if that option is enabled.
- Added support for exporting BSB maps natively with the Transverse Mercator projection.
- Added option to allow long labels when batch converting to DXF files.
- Fixed crash showing path profile/line of sight details when a Fresnel zone frequency is applied.
- Made Lidar LAS files correctly write v1.2 in the header if color values are present rather than v1.1.
- Updated the calculation of area and line elevation statistics to include the position of the minimum and maximum elevation found within the area as separate X and Y attributes rather than a combined coordinate pair for each to make it easier to load back in as points.
- Allowed calculation of elevation statistics for 3D lines even if no terrain data is loaded.
- Added option to create points at the intersection of line features when finding/splitting lines at intersections using the Digitizer Tool.
- Fixed problems finding geospatial information from some Erdas .img files.
- Updated LAS export with color values stored for each point to store colors in upper 8 bits of color values rather than lower 8 bits as some applications expect them that way.
- Updated LAS export with color values from LAS point clouds that had the color data to allow transferring that color data over to the new file.
- Added option when creating equal-value areas from palette-based raster layers to specify whether to always save the palette index/name or the full RGB value.
- Fixed problems doing hyper-spectral multi-band exports with more than 16 bands or so.

- Made option to snap to nearest input layer pixel on export work for gridded elevation exports in addition to raster exports.
- Added keyboard shortcut so holding down ‘J’ when selecting multiple vertices with the Digitizer Tool automatically puts you in ‘join’ mode.
- Made very small (i.e. less than 1.0E-6) elevation scale factors store properly in workspace files.
- Fixed problems loading some slightly corrupt .zip files.
- Don’t add extra space above or below path profile to buffer when explicitly setting a minimum or maximum height to display.
- Made option in Digitizer Tool to find points within some distance of another point save the results to a CSV file.
- Made path profile be available for 3D lines from the Digitizer Tool even if no terrain data is loaded.
- Drastically reduced memory requirements for online data sources when a very large bounds (like all data) is used and you reproject and zoom way in.
- Made the default File->Open Data File folder be shared with the File->Load Workspace menu command.
- Drastically sped up display of Map Layout dialog and Styles tabs of vector options dialogs when very large numbers of features are loaded from Lidar layers.
- Dramatically sped up the load of some GML format files.
- Added progress reporting to MapInfo MIF/MID and TAB/MAP exports.
- Don't prompt for fake position or rectification for image files (like JPG) loaded from an archive file (like a .zip) if other files are present in the archive file.
- Removed the ‘Close’ button from the Overlay Control Center as it was unnecessary and the dialog Red X suffices.
- Updated web exports with the ‘Fill to Tile Bounds’ option checked to export all layers to the full bounds of the tiles from the lowest zoom level so that you don’t get different coverages at different zoom levels.
- Fixed problems rendering overlapping point symbols in 3D view.
- Updated SegY importer to use the same settings for each SegY file involved in a multi-load.
- Fixed some rendering issues with some DGN files, like those with 2D curves.
- Drastically sped up sub-sampled exports from Erdas Imagine .img files with overview layers.
- Added option to map catalog options dialog to always show the maps in the map catalog. This also fixes an error message if you right-clicked on a map catalog in the Control Center and set the zoom scales to show at to always, then tried to open the Options dialog for the map catalog.
- Made automatic positioning work for new USGS GeoPDF topo maps.
- Fixed per-vertex elevation lists being all 0 when loading SEGP1 and UKOOA files.
- Made embedded picture images exported to KML/KMZ files be referenced as lower-case to make them work with Google Earth 6.1 which has a bug dealing with upper-case file extensions.

WHAT'S NEW IN Global Mapper v13.00

- **Significant New Features**
  - Added support for loading ESRI File Geodatabase (GDB) data sets from ArcGIS v10 and later.
  - Added support for generating density grids from point features in a loaded layer. This density grid can be based on either just a count of the point features or any numeric attribute value associated with the points.
  - Added support for joining a file with attributes to the attribute table of an existing loaded spatial layer against a common attribute. To do this, right-click on the layer in the Control Center and select the new JOIN TABLE option.
  - Added support for calculating/copying new attribute values made by copying an existing attribute or performing mathematical operations either between two attribute values or an attribute value and some number. To do this, right-click on the layer in the Control Center and select the new CALC ATTR option.
  - Added built-in access to premium streaming high-resolution terrain and imagery from Intermap using the File->Download Online Imagery/Data menu command.
  - Added option under View menu to zoom to the same location in Google Earth.
  - Added option to transform layer coordinates either by a manually specified coordinate transformation or with a control point file when shifting coordinates for selected layers from the Control Center in addition to just shifting a fixed distance.
  - Added option to crop area features to line features using the Digitizer Tool.
  - Added option to easily draw rotated area and line rectangles using the Digitizer Tool through the 3-point draw method.
  - Added new Image Swipe Tool to allow easily swiping away a raster layer to see other layers in an interactive manner.
  - Added option to create line features rather than areas when creating a regular grid of features using the Digitizer Tool.
  - Added option to create point features at the cell edges when creating a regular grid of features using the Digitizer Tool. This can be handy for creating a custom grid labeled with the coordinate values at the edges.
  - Added option to create a line feature from selected point features.
  - Added a new option to the Advanced Feature Creation submenu of the Digitizer Tool to create lines connecting selected points to selected line features along the shortest path between the point and any of the selected lines.
  - Added option to Digitizer Tool to automatically move selected point features to the nearest point on selected line features.
  - Updated drawing of area and line features to allow easily drawing new segments at right angles to previous segments by holding down the ‘R’ key.
  - Added option to only search on-screen features in the search dialog.
- **New Supported Formats**
  - Added support for loading ESRI File Geodatabase (GDB) data sets.
  - Added support for exporting loaded terrain data to SRTM HGT format files.
  - Added support for loading SegY format files.
  - Added support for loading NMGF (Noise Model Grid Format) files.

- Added support for loading ATLAS BNA (boundary) format files.
- Added support for exporting loaded data to XY Color text files.
- Added support for exporting 3D triangle areas to Vulcan 3D TIN (.00t) files.
- Added support for additional ways of encoding ASTER DEM data in HDF files.
- Added support for loading NOAA/NGA Geoid binary grid shift files.
- Added support for additional types of Japanese DEM files in LEM format.
- Added support for Geosoft Grid files with 8-byte double-precision samples.
- Added support for batch converting to Garmin-compatible KMZ files.

- **Projection/Datum Changes**
  - Corrected NAD83 HPGN/HARN transformations that were messed up in v12.02.
  - Made Washington/Oregon HPGN/HARN transformation actually work.
  - Added support for automatically transforming vector file coordinates using a .gm_xform file accompanying the data file describing the transformation. This is useful for modeling things like local mine grids.
  - Updated rotation for projections to be applied relative to the false easting/northing location rather than the (0,0) point.
  - Added built-in support for Dealul Piscului 1933 (Romania), Le Pouce 1934 (Mauritius), NAD83 HARN North Carolina, WI County (Chippewa), WI County (Taylor), and Xian 1980 datums.
  - Added support for Cape Feet, Centimeters, and Millimeters as linear units.
  - Made British Grid coordinates be displayed in the status bar with the 2 letter grid cell designation followed by easting and northing rather than just as decimal coordinates.
  - Make NAD83 datums write out as "NAD83" rather than "D_North_American_1983" to old format PRJ files to maintain compatibility with old ESRI products.
  - Corrected EPSG code for NY West Sate Plane zone to 2262 from 2261.
  - Improved conversion parameters for ED50 (Turkey) datum.
  - Fixed cropping to polygon during EXPORT_RASTER command.
  - Improved accuracy of some State Plane projection conversions that used non-unity scale factors (increased from 6 to 9 digits of precision used for State Plane projection definitions).
  - Made Provisional South American Datum 1956 (PSAD56) export correctly to MapInfo files.
  - Fixed New Zealand EPSG codes 27291 and 27292 (the false easting and northing values were wrong).
  - Corrected import of scale factor from custom datum transformations specified with TOWGS84 in PRJ files.
  - Improved accuracy of Bursa Wolfe datum transformations with large rotation angles (i.e. more than a few arc seconds of rotation).
  - Corrected use of wrong datum transformation in some cases when using the non-specific NAD83 CSRS datum.
- **Scripting Changes**
  - Added support for simplifying (reducing) line features with the EDIT_VECTOR

command using the SIMPLIFICATION parameter.
    - Added support for converting area features to line features with the EDIT_VECTOR command using the CONVERT_AREAS_TO_LINES parameter.
    - Added support for inserting vertices at line intersections and splitting those lines at those intersections with the EDIT_VECTOR command.
    - Added support for assigning unique ID attribute values to matching features for an EDIT_VECTOR script command using the UNIQUE_ID_BASE parameter.
    - Made SAVE_SCALE_AND_LEGEND work for EXPORT_PDF command.
    - Added FORCE_RGB parameter to GENERATE_EQUAL_VAL_AREAS script command to allow forcing the color attribute to use the full RGB color and not a palette index.
    - Added support for EXPORT_HEADER parameter for EXPORT_VECTOR command to control whether or not header row is written out for CSV export.
    - Added support for exporting to the InRoads ASCII format using the EXPORT_VECTOR command.
    - Added FORCE_EXIT command to allow forcibly closing a running instance of Global Mapper from a script.
    - Updated EDIT_VECTOR command to not work on hidden/disabled layers.
    - Added support for limiting the range of contour generation using MIN_ELEV and MAX_ELEV parameters for the GENERATE_CONTOURS script command.
    - Allow splitting DTED exports into folders by longitude using the EXPORT_ELEVATION command by adding a SPLIT_INTO_FOLDERS=YES parameter.
- Added support for calculating free space path loss during view shed calculation and making those areas with less power more translucent. You can also see the remaining power at any location on the status bar as you move your cursor over the view shed.
- Added display of the free space path loss in the path details for a line of sight calculation when Fresnel zones are calculated.
- Updated the KML export to include a <gx:Track> section for lines that have per-vertex time stamps associated with them so you can play them back in Google Earth.
- Added support for supplying radius for range ring generation from selected points through a RING_RAD_M attribute which supplies the radius in meters.
- Updated the Simple ASCII Text export to use DMS or DM format for lat/lon values exported to text files if the Position Display Format is configured that way on the General tab of the Configuration dialog.
- Added option to SEGP1 export allowing elevation values to be stored with an implied decimal.
- Updated similar color transparency specification on the Display tab of the Options dialog for raster layers to provide a slider to control how similar a color can be to the transparent color and still be treated as transparent. This replaces the checkbox option to enable similar color transparency so that more control is possible.
- Updated option to insert vertices at line intersections to allow only splitting where there are existing intersections and not inserting new vertices.
- Added option to Alter Elevations tab of Options dialog for elevation grid layers to allow

providing a power to apply when adjusting elevation values.

- Added new option to the Options menu on the Path Profile/Line of Sight dialog to allow creating point features at the minimum and maximum elevation locations along the path.
- Added new 'Dot – Orange' built-in symbol.
- Changed the border color for red and green dots to black from white.
- Improved grouping of Control Center right-click menu options to make them easier to find and also added upper-case one word descriptions to the start of some commonly used options to make them easier to spot.
- Added option to Control Center right-click menu to allow hiding all layers that don't intersect a selected area.
- Added option to split Shapefile exports based on the description of the layer that each feature is in.
- Added upper-case short descriptions of some commonly used items on the right-click menu for the Digitizer Tool.
- Updated creation of equal value areas to allow color fuzziness up to 256 to allow easily getting a polygon for the valid area of the layer.
- Added Ctrl+Alt+M as shortcut for Measure Volume functionality in Measure Tool and Digitizer Tool.
- Added new Advanced Selection option to the right-click menu in the Digitizer Tool to allow easily selecting any area features that are connected to the selected areas.
- Added new Advanced Selection option to the right-click menu in the Digitizer Tool to allow easily selecting any line features that are connected to the selected areas.
- Fixed problem loading *.NTF files in v12.02.
- Added support for adding a suffix to the row and column names when creating a regular grid of area or line features with the Digitizer Tool.
- Updated KML/KMZ raster exports to allow specification of JPG quality value.
- Added 2 new filtering modes for the Combine Terrain operation. You can now choose to keep the value from the first elevation layer if the second layer value is greater than or less than some other user-specified value.
- Allow specifying a suffix for the label for points generated from selected area or line features (in addition to a prefix which you could already specify).
- Added option to generate AutoKA PC World Files when batch converting to image formats.
- Added option to use the layer name for a feature as the label for the feature in an automatically generated map legend.
- Added support for coordinates in DDMMSS.S and DDMM.M formats when loading from generic ASCII text files.
- Added real-time display of 16-bit values from high-bit depth TIFF imagery files as you move the cursor over the file.
- Updated adding of measure attributes to 3D line features to include a LENGTH_3D attribute with the 3D length of the line if it is different than the 2D length.
- Fixed export of overview layers to Erdas Imagine .img files from map catalogs.
- Added display of maximum slope along path to 3D path profile details.
- Added support for fractional coordinates of form degrees.numerator/denominator. For example, to enter W94.125, you could now enter W94.1/8.

- Fixed fill coloring from some DGN files.
- Added support for NetCDF files larger than 2GB in size.
- Fixed problem from v12.00 with drawing elevation Erdas Imagine .img files when zoomed out if the files have overview layers.
- Added option when creating point features spaced at some interval along selected area/line features to control whether or not a point is always added at the feature end point even if not at an exact multiple of the sampling distance.
- Added option to not interpolate (resample) when batch converting to a gridded elevation format.
- Fixed problems loading data from WMS servers that list both GET and POST methods for accessing the servers (like GeoPortal Poland).
- Lightened up the outside color of displayed vertices to make them easier to see on dark backgrounds.
- Fixed problem with crashes exporting from online elevation sources.
- Made the simplification (reduction) of area features not create self-intersecting areas.
- Made some PDS imagery files that use floating point samples for single band imagery (like from NASA's LRO mission) display properly.
- Sped up exports to Arc ASCII Grid files from large numbers of input files.
- Fixed error saving workspaces and Global Mapper Package files when new areas with islands have been created in a layer.
- Made the feature info dialog display the description for a layer from the Control Center as the Map Name rather than the original description.
- Fixed RasterOverlay.cpp error loading some JP2 and ECW files with 16-bits per color channel.
- Improved display of arrows to the ends of lines for thick lines and fixed width lines.
- Fixed download of WCS data in projections other than lat/lon/WGS84.
- Added support for NITF imagery using tiled JPEG compression (code M3).
- Swap the drawing for area and line rectangles to by anchored at the top left by default, and switched to center-anchored if the 'T' key is pressed.
- Made most view shed parameters be remembered between runs.
- Fixed cropping to lat/lon boundary for polar stereographic projections.
- Fixed bug updating the elevations for selected vertices on the Vertices dialog for a feature (previously it was just setting the elevation to the index of the vertex and not the actual elevation).
- Fixed problem with some OSM XML files taking extreme amounts of memory to load.
- Default to always show digitizer toolbar to prevent redraws when switching to Digitizer Tool. You can always turn this off if you want, it just defaults to on now.
- Reduced memory required to load large Lidar LAS files as point clouds.
- Updated the calculation of area elevation statistics to include the position of the minimum and maximum elevation found within the area.
- Added support for providing extra parameters in OSM, TMS, and Google Maps tiled URLs when adding new sources.
- Added support for Arc ASCII Grid files with extra line breaks after the header lines.
- Fixed drawing of striped lines with black edges when printing.
- Corrected Y flip of SurvCAD grid files.

- Made 3D lines show through 3D translucent areas in the 3D view.
- Fixed render issues with some GeoPDF files.
- Corrected loading of MTEXT entities from DXF files with rotation elements provided.
- Added support for reading and writing receiver group records in UKOOA P-190 files.
- Corrected generation of area features for some VPF data sets (i.e. VMAP-1).
- Added support for loading uncompressed 32-bit tiles from Arc Binary Grid files.
- Made using Java filenames the default when exporting WorldWind tiles.
- Added Ctrl+E shortcut to Overlay Control Center providing quick access to edit the description of selected layers.
- Added new option to disable the automatic bilinear interpolation of terrain layers on load to the Advanced section of the General tab of the Configuration dialog.
- Corrected creation of equal-value elevation areas around zero.
- Fixed issue with duplicate area entries in the map legend sometimes.
- Fixed bug with some exported SVG files having an extra group close.
- Fixed export of text labels from points with no symbol to SVG files.
- Made ‘fill to tile bounds’ option work for OSM and TMS exports.
- Added progress reporting and cancel support for selecting areas that are included within or intersect other areas with the Digitizer Tool.
- Added support for loading GIF images from KMZ files.
- Fixed loading of curves from DGN files.
- Made layer names for inserted BLOCK entities in DXF files be assigned properly.
- Added new Advanced option to tiled web format exports (i.e. Google Maps, Bing Maps, OSM, and TMS) to use PNG files rather than JPG files whenever background pixels are encountered during the JPG export.
- Added new options to Google Maps tiled export to make the custom map be a basemap layer rather than an overlay layer and to control whether the zoom, pan, and street view controls are added.
- Fixed use of feet as receiver or transmitter height units for view shed calculation.
- Added option to save the results of a ‘Find Non-Connected Line Endpoints’ operation to a file.
- Added support for NMEA GPS devices that use $DPGGA position sentences.
- Added options to DWG and DXF exports to allow exporting labels longer than 31 characters.
- Added option to Polish MP export to save out all feature attributes and not just those defined by the MP format.
- Made OSM export use lower-case text for all attribute names.
- Fixed crash when inserting vertex along closing leg of area feature.
- Fixed grid line placement when margins are present on Map Layout dialog.
- Do a little bit smarter address search when no 'ADDRESS' field is found in file to geo-code but other fields are.
- Allow specification of new elevation values on feature vertex dialog with comma for decimal place rather than period.
- Added CLOSED_CONTOUR attribute to automatically generated contour lines that are closed.

- Added ELEVATION attribute to automatically generated contours so the elevation is available as an attribute as well as the display label.
- Added support for using LZW or Deflate compression on elevation GeoTIFF files.
- Added new option to the Advanced section of the General tab of the Configuration dialog to disable the prompt to skip loading files that are already loaded.
- Added new option to the slope direction shader to allow providing an offset angle to allow for checking alignment against angles other than cardinal directions.
- Fixed problems with attribute names with accent characters not working to add display labels from in some cases.
- Fixed error loading NITF files with JPEG2000 encoding over 2GB in size.
- Improved reading of SHP files with no SHX file.
- Fixed issue with red box around point location for 'No Symbol' points with text exported to KML/KMZ files.
- Added JPG quality setting to Google Maps/Bing Maps/OSM/TMS export dialog.
- Updated option for selecting lines within area to allow selecting those lines that are just partially in the area in addition to those completely within the area.
- Allow export of grid lines to Shapefiles even if no other line features are loaded.
- Added support for extracting feature attribute information from <ExtendedData> section of <Placemark> entities in KML/KMZ files.
- Added option to the Advanced section of the General tab of the Configuration dialog to minimize the main window during exports.
- Made simplification and smoothing operations work on un-selected island areas.
- Made the aspect ratio always be maintained when saving the 3D view to an image file.
- Made SVG exports include an “id” values with a unique number for each exported feature.
- Updated GPS menu item for sending custom raster maps to a connected Garmin device to have an option to specify the maximum map count. This default to 100, but you can increase it for newer units that support more than 100 map tiles.
- Fixed problem exporting Ozi .ozf images to palette-based formats.
- Updated JPG2000 export to internally tile the created image to 1024x1024 tiles.
- Made Lidar points marked as “withheld” be automatically marked as deleted on import.
- Improved vector search dialog so that moving features to a new layer doesn’t reset the sort and column sizes.
- Added option to default GeoTIFF export to use no compression to the Advanced section of the General tab of the Configuration dialog.
- Added option to the GeoTIFF export dialog to disable the writing of GeoTIFF header information to the generated file. This is useful for using things like datum specializations that can’t be exactly stored in GeoTIFF files, so you’d rather just use a PRJ file and not have anything in the GeoTIFF file.
- Updated SEGP1 import to default to feet for the elevation units if statute is selected for the elevation display/export units on the Vertical Options tab of the Configuration dialog.
- Added option to the Vector Display tab of the Configuration dialog to set the default character set for fonts to allow easily switching default fonts to a non-Western European character set.
- Made export of distance/Z file from path profile dialog work properly when a non-zero

base distance is specified.

WHAT'S NEW IN Global Mapper v12.02

- **Significant New Features**
  - Added built-in access to additional online Worldwide Imagery, Street Maps, MapQuest OSM Street Maps, and Topo Maps using the File->Download Online Imagery/Data menu command.
  - Added new MapMart On Demand premium data source to the File->Download Online Imagery/Data menu command. This source provides easy access to the large library of data sets that MapMart.com provides.
  - Added support for adding online sources that use the Google Maps tiling scheme, like a lot of ArcGIS tile sources and Nearmap imagery from Australia.
  - Added support for loading data from WCS (Web Coverage Service) data sources using the File->Download Online Imagery/Data menu command.
  - Updated creation of equal-value areas to allow selected just a single color value to create areas for rather than creating equal-value areas for all selected colors.
  - Added new right-click option to Control Center to allow splitting a loaded vector layers into new layers based on the feature description, type, name, or any attribute value. The new layers will automatically be grouped under the original layer name.
  - Added additional built-in line styles, including several new Dash styles with different dash sizes and spacing.
  - Updated creation of strike-and-dip points to allow dragging along the strike/dip direction when placing the points to automate selection of value.
- **New Supported Formats**
  - Added support for loading ioGAS .gas point files.
  - Added support for loading Lowrance USR v4 format files.
  - Added support for exporting point features to Lowrance USR v4 format files.
- **Projection/Datum Changes**
  - Added built-in support for NAD83 (CSRS) [Canadian Spatial Reference System] datum transformations, with grid shifts initially supported for Alberta, British Columbia, New Brunswick, Quebec, and Saskatchewan.
  - Added built-in support for Combani 1950 (Mayotte), CSJ67 (Guyane), ED50 (TURKEY), Fort Marigot (St. Maarten), Guadeloupe 1948, Martinique 1938, RGFG96, RGM04, RGR92, and RGSPM06 datums.
  - Added built-in 10TM (Alberta) and Natural Earth projections.
  - Made Irish Grid coordinates display using grid tile letters and coordinates on the status bar rather than just the base eastings and northings.
  - Added support for decoding Transverse Mercator projections from Touratech .cal files.
  - Restored Bogota Observatory transformation from before v10 as it is more appropriate for all of Colombia.
  - Improved storage of New Zealand Map Grid and New Zealand Transverse Mercator parameters in GeoTIFF and MapInfo files.

    - Corrected ellipsoid used for Kertau 1948 datums from Everest 1830 to Modified Everest 1848.
    - Recognize "standard_parallel_1" for true scale latitude parameter for Mercator projections from WKT PRJ files.
    - Added support for Links and Clarke Links as a linear unit for projections.
    - Updated the projection selection dialog to display the base projection parameter values for State Plane projections.
    - Corrected EPSG codes used for SIRGAS 2000 UTM zones.
- **Scripting Changes**
    - Added support for defining variables and associated values using the new DEFINE_VAR script command.
    - Added EXPORT_PDF script command to allow exporting PDF files from a script.
    - Added GENERATE_EQUAL_VAL_AREAS script command to allow creating equal value areas from a script.
    - Added support for copying attribute values in loaded vector data using the ATTR_TO_COPY parameter for EDIT_VECTOR script commands.
    - Made the EDIT_VECTOR command work for User Created Feature layers.
    - Added support for exporting ESRI-format .hdr files for BIL export by adding a USE_ESRI_HDR=YES parameter to the EXPORT_ELEVATION script command.
    - Added support for POLYGON_CROP_FOLDER_ATTR parameter to add an attribute name as a folder name when cropping to a list of area from a file.
    - Added support for adding lat/lon columns to CSV exports with an ADD_LAT_LON=YES parameter.
    - Added support for adding fading to raster KML/KMZ exports using KML_FADE_EXTENT_MIN and KML_FADE_EXTENT_MAX parameters for EXPORT_RASTER script command.
    - Added support for specifying quality for JPEG-in-TIFF exports using QUALITY parameter.
    - Added support for exporting DTED files with the EXPORT_ELEVATION script command.
    - Added support for only exporting vector layers to package files using the VECTOR_ONLY parameter for EXPORT_PACKAGE commands.
- Updated Lidar import to support filtering out any types of returns rather than just keeping them all or just ground shot points.
- Updated PDF export to include clickable hot-spot links for any point features with a LINK attribute pointing to a web page or local file.
- Updated Shapefile export to add option to split the exports based on the feature display label or any attribute value (previously you could only split on feature type or description).
- Updated Style tabs of Options dialog for vector layers to allow initializing the attribute-based styling list with the list of attribute values found in the selected layer(s).
- Updated cut-and-fill volume analysis for area features to allow specifying a range of elevation values to calculate the volumes relative to. When this is done the results for

each cut level will be displayed in a table.
- Added option to the Vector Display tab of the Configuration dialog allowing changing the default font face name.
- Reduced memory required for loading PDF files so that more PDF files can be loaded at once at higher resolutions.
- Made cropping of multi-band exports to areas features work properly.
- Added option to control fading and maximum display level for raster KML/KMZ exports.
- Added advanced option to raster KML/KMZ export to allow separating each layer exported into its own ground overlay in the exported file.
- Added support for <PhotoOverlay> elements from KML files. They will come in as Picture point features that show the image when clicked on.
- Added support for using KML/KMZ files reference via external <NetworkLink> elements when loading KML/KMZ files.
- Added support for using styles referenced via external URLs when loading KML files.
- Made duplicate vertices be removed from area features when exporting to Shapefiles.
- Updated equal-value area creation to support cropping to bounds or selected area features.
- Added support for only selecting point features with the Feature Info/Digitizer Tool by holding down the ‘P’ key when left clicking, lines by holding down the ‘L’ key when left clicking, and areas by holding down the ‘A’ key when left clicking (previously area-only selection used the ‘P’ key).
- Updated option to create a new point feature at a specified location to also allow providing an elevation value.
- Made automatic iconization of road names work for European-style highway names (like A, B,and M roads) and also when you change the attribute to use for labeling rather than just at load time.
- Added support for WMS servers that use CRS rather than SRS to specify projections in their GetCapabilities document.
- Fixed poor performance with some TIFF files in the 64-bit version.
- Updated gridding to area features to allow combining the export results of multiple areas that have the same attribute/label being used for naming.
- Updated WaSP .map import to find areas that are holes/islands in other areas.
- Fixed 1-pixel shift of data under a translucent layer half of the time due to rounding.
- Updated to support VPF files with no 'lat' file when loading directly from a 'lht' file, such as is common with UVMAP data sets.
- Fixed issue with built-in Landsat imagery data sources only getting up to 30m resolution data rather than better than 15m resolution. This bug has existing since v11.00.
- Updated map catalog dialog to have a button allowing the modification of style settings for vector layers in the map catalog.
- Fixed crash sometimes trying to find areas enclosed in other areas when partial overlaps are being checked for.
- Fixed issue with X and Y coordinates being swapped when importing GML files with lat/lon coordinates.
- Updated Bing Maps, Google Maps, OSM, and TMS tile exports to have option to force

PNG files to export as palette-based PNG files rather than automatically switching to 24-bit RGB PNG files if each tile has more than 256 colors.

- Made the style 'Solid with Black Edges' render correctly with fixed width in meters styles.
- Include quotes around CSV column headers to prevent warnings in Excel for CSV files saved from the path profile dialog.
- Updated import of VPF format data sets (like VMAP, UVMAP, DNC, etc.) to include both the decoded attribute descriptions and value descriptions as well as the raw attribute names and values.
- Corrected issues importing and export Z/elevation values with DGN v8 files.
- Updated equal-value area creation to save the palette index for the color value for palette-based files rather than the full RGB color.
- Fixed problems with elevation legend display for very large values (i.e. over 1 million).
- Prompt user for whether to recurse directories or not when adding a directory of files to a map catalog.
- Remove error about file being open in another application when skipping existing tiles and exporting to new TIFF files.
- Added support for providing view shed transmitter and receiver height values relative to sea level rather than ground via selected point attributes named OFFSETA_MSL and OFFSETB_MSL. You can also add 'ft' to the end of the height values to specify the heights in feet rather than meters.
- Updated Gridding tab for exporting to allow specifying overlap as a number of pixels/samples in addition to percent of cell size.
- Fixed crash when interrupting the draw of some TIFF files (i.e. zooming and/or panning fast around the data).
- Fixed bug with modifications to vector features not being read from workspaces if the layer also used custom area, line, or point style setups for the layer.
- Made areas exported to WaSP .map files always be clockwise in orientation.
- Added option to CSV export to control whether or not lat/lon coordinate values are formatted according to the Position Display Format settings or just use raw numbers.
- Updated option to create points at elevation grid cell centers in the Control Center to allow generating points only for a portion of the selected layer(s).
- When creating new unclassified features or moving unclassified features to a new layer with a default type set, automatically change the type to the default type (area, line, or point) for the layer of the feature.
- Updated Google Maps HTML export to use v3 of the Google Maps API.
- Updated the area elevation statistics calculation to include the aspect (what direction the area faces) if it faces most one cardinal direction.
- Made Lowrance symbol be remembered when importing a Lowrance USR file and exporting to a new USR file.
- Significantly reduced or removed visual seams between elevation layer tiles in map catalogs and from online sources.
- Fixed issues with area features from some DGN files coming in as lines.
- Added some support for parsing tables of attributes in KML feature descriptions into separate attribute values in Global Mapper.

- Fixed loading of SEG-P1 files that uses decimal lat/lon coordinates rather than DMS coordinates.
- Fixed loading of some line styles from DGN files.
- Split raster maps that cross the anti-meridian into 2 separate pieces when batch converting to a lat/lon projection, like for KMZ export.
- Corrected view shed calculation when a range of transmission angles are provided.
- Fixed problems with some attributes from some DGN files not being properly assigned.
- Fixed export of HF2/HFZ files with fractional units (like centimeters).
- Updated feature vertex display dialog to show lat/lon coordinates using the current Position Display Format setting rather than always showing decimal degrees.
- Added right-click menu option to feature vertex dialog allowing you to easily spread the elevation values along the vertices of a feature to achieve a constant slope between the first and last point.
- Added right-click menu options to feature vertex dialog allowing you to add per-vertex times and editing existing time/speed values for each segment of a line feature.
- Added support for ENVI DEM files with 32-bit integer samples.
- Added new right-click option to Download Online Imagery/Data dialog allowing you to set the maximum resolution at which to try and download data from a user-added WMS source.
- Added new box minimum resampling methods.
- Added new 9x9 box average and box max resampling methods.
- Automatically shrink the font for the sub-path text display on the path profile dialog to make sure it fits if it is too large to fit in the default font.
- Added option to specify stream area threshold for watershed delineation as a ground area or a fixed cell count.
- Added option to save the flow accumulation values for each cell to a grid layer when calculating a watershed.
- Updated watershed generation to add NEXT_STREAM_ID attribute to generated watershed areas where the ID of the stream that the stream for the watershed flows into is stored to facilitate determining connectivity.
- Updated watershed generation to add DRAIN_AREA attribute to generated streams to show the total area that drains into the stream.
- Update the label display for built-in dot symbols to be closer to the actual dot.
- Made numeric values be sorted numerically in vector map legend.
- Improved text placement for some TEXT entities from DXF files.
- Added support for SOSI files with multiple unit multiplier specifications.
- Added support for Architectural paper sizes for PDF export.
- Corrected rendering of fixed height symbols to PDF files.
- Fixed elevation values for points created from an elevation grid layer when offset and/or scale values are applied to the elevation grid layer.
- Fixed loading of WKT formatted data from some text files.

WHAT'S NEW IN Global Mapper v12.01

- **Significant New Features**

- Added built-in access to 1/3rd arc second (~10m resolution) US NED terrain data using the File->Download Online Imagery/Data menu command.
- Added option to export tiles conforming to the OSM (OpenStreetMaps) and TMS (Tile Map Service) standards for tile naming and zoom levels. This is under the File->Export Web Formats menu command and very similar to the Google Maps or Bing Maps exports.
- Added support for adding new custom OSM/TMS online tile sources on the File->Download Online Imagery/Data dialog.
- Added support for exporting loaded data to BSB Marine Chart format files.
- Added ability to improve display of 3D view by selecting the size of the terrain and texture layers to use when displaying the 3D view and also interpolating view of data draped from main map view. You can increase the terrain and texture sizes to get a more detailed (but slower) display.
- Added option to create area features from equal colors/elevations in any loaded raster/elevation layer by right-clicking on it in the Control Center and selecting the new option to do so. This is useful for things like extracting vector coverages from something like a land use/cover raster image, like NLCD data.
- Updated watershed analysis to allow finding the drainage areas that drain to a selected point as well as to trace the flow leaving selected points.
- Made custom symbols be embedded within Global Mapper Package (GMP) files so those symbols can automatically be used on other installations without having to first install those symbols. This makes GMP files even more self-contained for transporting data.
- Added support for automatically adding custom symbols referenced in KML/KMZ files.
- Added support for using overview layers from Erdas Imagine .img files when rendering, greatly speeding rendering of very large .img files with overview layers.
- Updated creation of area features from lines with the Digitizer Tool to provide options for the combination, including requiring closed areas to be created and also only connecting lines that match attribute-wise against the other lines. Also added progress reporting for the operation.
- Added new line drawing styles for a dashed line with arrows pointing to either or both ends.
- Added support for batch converting to mulit-band BIL, BIP, BSQ, and JPEG2000 formats.
- Added option to locate the minimum and maximum elevation values in selected layers via a new right-click option in the Control Center.
- Added new option to Measure Tool to display measurement paths and measure distances/bearings using rhumb lines in addition to great circle or grid lines.
- Updated JPEG-in-TIFF export to use YCbCr color encoding to generate 2-3 times better compression at the same quality than the previous settings.

- **New Supported Formats**
  - Added support for new MrSID MG4 raster files, including support for multi-spectral MrSID images and MrSID images with an alpha channel for

transparency.
    - Added support for exporting loaded data to BSB Marine Chart format files.
    - Added support for loading HRE (High Resolution Elevation) data files.
    - Added support for loading ACE2 global elevation data set.
    - Added support for loading WindSim .gws files with terrain and roughness data.
    - Added support for Lowrance SL2 CSV files.
    - Added support for exporting loaded terrain and roughness grid files to WindSim .gws format files.
    - Added support for exporting loaded line and point features to Orca XML obstacle files.
    - Added support for additional PDS format imagery files, including automatic support for positioning polar data from the moon.
- **Projection/Datum Changes**
    - Added support for supplying a rotation angle about the origin for some projections, like Transverse Mercator and Orthographic, to facilitate setting up rotated local grid projections.
    - Added new Swedish Grid (SWEREF99) built-in projection with all SWEREF99 projections used in Sweden available as zones.
    - Added new built-in Mercator (Navionics Special) and Mercator (Lowrance Special) projections to represent the custom Mercator projections used by Lowrance and Navionics.
    - Added American Samoa 1962, GDM2000 (Malaysia), Lowrance, and Potsdam/DHDN (Ferro Meridian) datums.
    - Corrected storage of central meridian for Polyconic projections in GeoTIFF files.
    - Modified saving of NAD83 and NAD27 datums to WKT PRJ files so that ESRI products that are inflexible can recognize them.
    - Made the corrected “standard parallel 1” field be used for the true scale latitude for the Equirectangular projection in GeoTIFF files.
    - Added support for decoding LOCAL projections from WKT PRJ files.
    - Added support for loading Laborde projections from WKT PRJ files.
    - Fixed problems with wrong EPSG code being written to GeoTIFF files for State Plane projections that use units other than meters.
    - Fixed problems with loading non-standard State Plane projections from PRJ files.
    - Made RSO projections with 0 rotation angles work correctly.
- **Scripting Changes**
    - Added new EXPORT_SCALE parameter to EXPORT_RASTER command to allow exporting to a particular scale.
    - Added new ATTR_TO_RENAME parameter to EDIT_VECTOR script command to allow renaming attributes from a script.
    - Fixed problems with EDIT_VECTOR command not finding any matching results if a comparison string is provided without any type assignments.
    - Added EXPORT_SLOPE_PERCENT parameter to EXPORT_ELEVATION script command to allow exporting slope values as percent slope rather than degrees when exporting Float/Grid files.
    - Added support for exporting BMP files with the EXPORT_RASTER script

command using a format of BMP.
    - Updated GENERATE_ELEV_GRID command to support additional display options like those also supported by the IMPORT command.
    - Added new LABEL_FIELD_FORCE_OVERWRITE parameter for IMPORT command to specify that any LABEL_FIELD value should be applied to all features even if they already have a display label.
    - Added support for KML_MAX_LOD_PIXELS parameter for EXPORT_RASTER command to specify the value to use for the <maxLodPixels> tag in generated KML files.
- Added new box maximum resampling methods for terrain layers to allow resampling elevation layers by finding the maximum rather than average value within a box of samples. Automatic sub-sampling of elevation layers during export will automatically use these rather than box average resamplers.
- Updated SVG export to include display labels.
- Drastically sped up calculation of raster statistics for contrast adjustment for JPEG2000 and ECW format files.
- Added elevation under cursor (if available) to the current projection coordinate display on the status bar.
- Added option when combining area features with the Digitizer Tool to only combine those with compatible attribute values.
- Updated elevation legend display to only display the range of layers that are on-screen and not all loaded layers.
- Made the last selected projected system for files with an unknown projection be remembered between runs.
- Added new option to default auto-contrast adjustment to a linear min/max stretch rather than a standard deviation stretch. The option is in the Advanced Section of the General tab of the Configuration dialog.
- Added new option to disable auto-contrast adjustment on load for high bit depth imagery. The option is in the Advanced Section of the General tab of the Configuration dialog.
- Added new option to create a map catalog from selected layers on the right-click menu of the Control Center.
- Added new option to combine terrain layers using a divide operation.
- Added support for loading Global Mapper Grid (GMG) files larger than 4GB in size.
- Added support for rotated ENVI files and raster imagery with ENVI headers, including massively multi-spectral ENVI files.
- Added START_TIME and END_TIME attributes to tracklogs with timestamps imported from GPX files.
- Added option to include MAP_NAME attribute when exporting Shapefiles. The attribute will contain the description of the map that the feature originally came from.
- Added support for loading very large .zip files (Zip64 format) over 2GB in size.
- Added option when loading very large OpenStreetMap (OSM) XML files to only load those features that intersect the current screen view.
- Added support for generating MCF (uBlox position) files when exporting to most raster imagery formats (i.e. PNG, JPG, etc.).
- Updated GeoTIFF export to allow using Deflate (ZIP) compression as well as specifying

the quality to use for JPEG-in-TIFF compressed files.

- Added new option when capturing the screen contents to an image to crop the results to the bounds of the loaded map data.
- Added a new option during watershed generation to save the depression-filled DEM to a GMG file so you can use that later for repeat operations and have the depression filling already done
- If water display is enabled on the Vertical Options tab of the Configuration dialog, show it on the 3D path profile dialog.
- Allowed working with the underlying map while the 3D path profile dialog is open.
- Added support for exporting palette-based BMP files.
- Updated folder selection dialog to include edit box for manually typing a path.
- Fixed problems loading ECWP (ECW file from the web) from workspace/script files.
- Fixed problem with last point going out to full spacing in 3D path profile rather than to end of provided path when using a fixed spacing for the elevation samples.
- Fixed issue with generated watershed stream network not saving to workspace files.
- Fixed problems loading files larger than 4GB from map catalogs.
- Fixed problems loading some BigTIFF files larger than 4GB in size.
- Fixed issue from early v12.00 builds that caused box average resampling to automatically be used for some exports where reprojecting and changing units.
- When creating tight buffers around line and area features with per-vertex elevations, copy the elevation from the nearest point on the source feature to the vertex in the buffer area so that the buffer area will be a 3D feature as well.
- Made spacebar work to hide/show selected layers in the Control Center.
- Fixed placement problems with some DGN files (i.e. those with a non-zero origin) in v12.00.
- Enabled option to crop to the right-and-bottom bounds of grid cells when gridding to a fixed ground size.
- Made area obstructions in view sheds work better when the area feature is small compared to the view shed sample spacing.
- Updated the behavior of the arrow buttons in the Control Center for re-ordering layers to skip over entire groups of layers at a time.
- Added support for serial GPS devices that use 7-bit mode (7N1) rather than the normal 8-bit (8N1) connection mode. This is for advanced users only. See the User's Manual section on the GPS Setup dialog for details.
- Updated the "same as source units" elevation unit option when batch converting to the GMG format to automatically switch meters to centimeters and feet to centifeet so that the full resolution of the vast majority of data sets can be maintained by default while still getting excellent compression.
- Updated batch conversion to use lower-case file extensions for all conversions.
- When loading geo-positioned PDF files with multiple positioned map frames, make the map frame that is the largest portion of the PDF file be treated as the main map frame if the users chooses to just load the main one.
- Added support for loading DTED files that incorrectly store the row for each data record.
- Made Control Center remember which groups of layers are expanded when new layers are added and the list is rebuilt.

- Made workspaces remember their bounds properly when loading them by double-clicking in Windows Explorer.
- Fixed problems from v12.00 exporting 3D area and line features or area features with labels to DGN files.
- Fixed problem with the 'default to use screen bounds for export' option not working right if you didn't actually click to the bounds tab of an export or other bounded operation option dialog before pressing ok.
- Sort sources on Download Online Imagery/Data dialog alphabetically within each group.
- Fixed problems exporting new OpenStreetMap (OSM) XML files with non-HTML characters in the name or attributes.
- Corrected assignment of vertex elevations to selected area and line features when the layer didn't use meters for units.
- Added Help menu link to Shortcut Key List.
- Fixed incorrect calculation of slope values from some lat/lon elevation grids.
- Updated new areas created by cutting out another area with the Digitizer Tool be created in the same layer as the area being cut rather than the 'User Created Features' layer if the area layer isn't being reprojected.
- Corrected placement of point symbols for 3D points in 3D view. They were shifted one symbol height down.
- Updated watershed calculation for selected points to add the enclosed area of the watershed areas for each point to be added as a SHED_AREA attribute to the selected point features.
- Fixed conversion of elevation units to feet when exporting to a new vector format with S-57/ENC data as the input.
- Corrected application of contrast adjustment to NITF imagery layers that use embedded JPEG2000 files.
- Made the feature measurement dialog resizable.
- Fixed problems with some DGN areas being filled that shouldn't be.
- Made changing the projection for multiple layers at a time using the Projection tab of the Options dialog for the layers work for more than the first selected layer.
- Added advanced option to create world files for each exported tile when doing a WorldWind export.
- Fixed bug in Digitizer/Edit Tool with splitting lines into separate features for each line segment that caused not all of the lines to be split.
- Added support for loading Geosoft LUT and TBL palette files.
- Fixed issue with main map not redrawing when double-clicking on a file in the file open dialog to open it.
- Apply scale factor to values extracted from NetCDF files that include that, like some gravity grid files.
- Made any vertices selected on the map also be selected initially when opening a vertex dialog on that feature from the Feature Info or Digitizer Tools.
- Fixed problems loading some GRIB format files.
- Made most GRIB data sets come in as elevation grids rather than rasterized and scaled grayscale data.
- Made "version" attribute be maintained when importing OSM XML data.

- Made area translucency, fixed width lines, and fixed height symbols be saved properly to SVG files.
- Fixed issue rotating and scaling islands in areas if both the island and the parent area are selected.
- Fixed flicker of map layout elements (like scale bar and elevation legend) when moving cursor around path profile.
- Fixed export of borders for translucent areas to PDF files.
- Made the margin color selection in the Map Layout dialog be remembered.
- Updated the rotate/scale dialog to remember the last manually entered position selected to rotate about during a single session.
- Made holes/islands in areas export properly to Lowrance LMC format files.
- Fixed issue with 2nd rectification dialog appearing when rectifying an image with a map catalog of images loaded in the main map view.
- Added support for decoding gml:Curve elements from GML files.
- Fixed export of elevation data sets with valid values below -9999.0 to Arc ASCII Grid files.
- Updated the palette dialog to allow editing the color or description for multiple entries at a time.
- Added support for pulling in files via FTP using the IMPORT command in scripts.
- Allow cancel when loading large PNG files.
- Added option to Google Maps and Bing Maps (VirtualEarth) exports to fill each exported tile to the full bounds rather than cropping to the specified export bounds.
- Fixed issue with changes to vertices made through the Vertices dialog off of the Feature Information dialog being lost if you switch tools or click to select a new feature in the Feature Info tool.
- Fixed Bing Maps (VirtualEarth) export to use proper zoom scale names.
- Fixed error exporting DGN files with a projected system not using meters as the ground units.
- Fixed rare problem encoding negative elevation values to Global Mapper Grid files.
- Made water drawn in the 3D view use the water color configured on the Vertical Options tab of the Configuration dialog rather than always being blue.
- Fixed problems with path profiles generated over online elevation sources when the path spans more than one screen's worth of data.
- Added option to fill small gaps in data when batch converting to raster/image formats (it was already there when converting to elevation formats).
- Added support for providing symbol rotation angles in attribute fields named ANGLE or SYM_ANGLE.
- Fixed problems with missing per-vertex elevation values for some area features from DGN files.
- Fixed bug in v12.00 release that caused contour areas to only cover part of the data set in many cases.
- Updated XYZ Grid export of elevation layers to reduce number of decimal digits saved in some cases (such as for integer values).
- When splitting line features with an "id" attribute at a vertex, clear the "id" attribute on all but the first new segment so there won't be duplicate "id" values.

- Greatly sped up the load and display of RPF (Raster Product Format) data sets like CADRG and CIB.

WHAT'S NEW IN Global Mapper v12.00

- **Significant New Features**
  - Added built-in access to the NAIP color high-resolution imagery for the entire United States via the File->Download Online Imagery/Data menu command.
  - Added built-in access to the ASTER GDEM terrain data at 1.5 arc second (~45m) resolution for the entire world via the File->Download Online Imagery/Data menu command.
  - Added built-in access to premium Parcel data for the entire US via the File->Download Online Imagery/Data menu command.
  - Added support for automatically delineating stream networks and watershed areas using loaded terrain/DEM data using the File->Generate Watershed menu command.
  - Added 'Point Styles' tab to Options dialog for vector layers with point features allowing users to setup the styling of points in a layer. Now users can use the default type-based styling, apply a single style to all point features in a layer, setup an attribute-based styling system that styles the points based on the value of an attribute value or the display label, or randomly assign colors to the dot or custom symbols for points in a layer.
  - Updated the Download Online Imagery/Data interface to group data sources to allow easily finding data sources of a particular type or covering a particular area.
  - Updated the Control Center to support assigning groups to selected layers via the right-click menu. Those groups can then be collapsed in the Control Center to allow easily selecting, closing, or hiding/showing that group.
  - Added new right-click option to the Digitizer Tool for creating a regular grid of areas anchored at some point and of user-specified size, rotation angle, and naming.
  - Added ability to export BIL/BIP/BSQ and JPEG2000 raster files with multiple bands of data at 8, 16, or 32-bit depth (similar to what was possible before for GeoTIFF exports).
  - Added option to use “halo” fonts for text display. Halo fonts display a thin border around text of a slightly different color, making the text visible on any background. The new Halo style is available on the font selection dialog when editing the label font for feature types or individual feature styles.
  - Updated the export interface to replace the long sub-menus with dialogs allowing format selection to prevent overflowing the export format lists off of the screen.
  - Updated the map legend display based on vector types to allow labeling each style in the legend by the feature type, name, or any attribute value, in addition to the feature description which is what was always used before.
  - Added new EDIT_VECTOR script command (replacing the ASSIGN_TYPES command) to allow adding/updating feature attributes values and display labels, reclassifying features, rotating/scaling/offsetting feature coordinates, connecting

islands of areas to the main parent, deleting duplicate features, or marking features as deleted by searching loaded features for matches against their attributes/label values and/or types.
    - Updated PDF export to allow using a separate layer for each raster/elevation file exported to a PDF file rather than always combining them into a single layer.
    - Made grid line setup be saved in workspace files and map layout files, so your grid spacing setup will be saved separately in each workspace.
    - Allowed adding/updating per-vertex elevations for selected line and area features from loaded terrain layers using the Digitizer Tool.
    - Added elevation units selection for loaded vector layers to the main Feature Types option tab for the layer (moved from Projection tab), making it much easier to find and work with.
    - Added option to area volume measurement to find the cut height at which the cut and fill volumes would be approximately equal.
    - Added option to save color values from loaded raster files and select the elevation units when exporting new Lidar LAS files from loaded vector data.
    - Added option to log all incoming GPS fixes and NMEA strings to a file on the GPS Setup dialog.
    - Added support for initializing view shed calculation parameters for calculations from selected points based on attribute values of those points. This allows for calculating a bunch of view sheds at once with different parameters.
    - Added support for automatically rotating geology symbols based on an attribute value providing the rotation angle. Currently the attributes DIP_AZI, DIP_DIR, STRIKE_AZI or STRIKE_DIR are supported to provide the angle in degrees.
- **New Supported Formats**
    - Added support for loading HCRF (Hydrographic Chart Raster Format) files, including ARCS (Admiralty Raster Chart Services) charts.
    - Added support for exporting gridded elevation data to JPEG2000 elevation grid files.
    - Added support for exporting new DTED3/HRTE3 format files from loaded elevation data. DTED level 3 files have a resolution of 0.4 arc seconds, or about 12 meters per sample.
    - Added support for exporting loaded line data to LMN (Spectra Land Management Node) format files.
    - Added support for loading Tobin WCS (Well Coordinate System) files.
    - Added support for loading Carlson SurvCAD Grid files.
    - Added support for exporting loaded line data to Hypack Planned Line (LNW) format files.
- **Projection/Datum Changes**
    - Added support for automatically adding custom datums from TOWGS84 parameters in WKT PRJ files.
    - Added option to the Advanced section of the General tab of the Configuration dialog to control whether or not generated WKT PRJ files include the datum transformation as a TOWGS84 field.
    - Added Hotine Oblique Mercator Azimuth Natural Origin projection to allow

specifying Hotine projections where the false easting and northing are at the natural origin of the system.
    - Added new Hong Kong 1980, MGI (Croatio/Serbia), MGI (Slovenia), and NAD83 (ITRF96) datums.
    - Fixed loading of Minnesota State Plane South Feet projection from ECW files.
    - Updated Clarke 1866 Authalic Sphere to behave as the USGS intended (i.e. no conversion to WGS84, similar to how Google Maps datum works).
    - Added support for saving almost every datum from Global Mapper into exported Erdas Imagine files.
    - Added EPSG codes 2991 and 2992 for Oregon Lambert projection.
    - Updated Winkel Tripel projection to allow modifying the True Scale Latitude.
    - Updated the Interrupted Goode Homolsine projection to support a Central Longitude parameter.
    - Added support for zone 10 to Gauss Krueger Germany 3-degree zone projection.
    - Corrected Kansas State Plane North and South NAD83 zone definitions for ECW files.
    - Fixed problems parsing some MGRS coordinates with shortened coordinates.
    - Added support for getting Gauss Krueger Germany 3-degree zone projections from Touratech TTQV .cal files.
    - Added support for saving projections using arc second and grade units to WKT PRJ files.
    - Added support for decoding of Geographic projections using units other than arc degrees from WKT PRJ files.
    - Updated scale value for Arizona West State Plane projection to have enough digits of precision.
- **Scripting Changes**
    - Added new EDIT_VECTOR script command (replacing the ASSIGN_TYPES command) to allow adding/updating feature attributes values and display labels, reclassifying features, rotating/scaling/offsetting feature coordinates, connecting islands of areas to the main parent, deleting duplicate features, or marking features as deleted by searching loaded features for matches against their attributes/label values and/or types.
    - Added GENERATE_WATERSHED script command to allow performing watershed analysis from a script.
    - Added new RUN_COMMAND script command to allow running any application from within a Global Mapper script.
    - Added new COMPRESSION parameter to EXPORT_RASTER command to allow specifying the compression to use when exporting GeoTIFF files. This deprecates the USE_LZW parameter**.**
    - Added support for new %PARENT_DIR% wildcard in DIR_LOOP_START...DIR_LOOP_END loop in script to allow using the name of the parent folder for the current file.
    - Fixed EXPORT_VECTOR script command when splitting against anything other than an actual attribute.
    - Added option to KML export using EXPORT_VECTOR command to specify

which feature attribute to use for the folder name in the generated KML file. The new KML_FOLDER_ATTR support specifying what attribute to use for the folder name.
    - Updated FILENAME_ATTR_LIST parameter for EXPORT_VECTOR command to allow specifying particular attribute values to filter against in addition to just splitting by attribute.
    - Updated GENERATE_CONTOURS command to support cropping contours to a polygon using the POLYGON_CROP_FILE or POLYGON_CROP_NAME parameters.
    - Added support for exporting slope or slope direction values to new Float/Grid format files using the EXPORT_ELEVATION command. The new parameters are EXPORT_SLOPE and EXPORT_SLOPE_DIR.
    - Made running scripts via the command line return a code of 1 rather than 0 if an error occurs while processing the script.
    - Added SKIP_UNLOAD_ALL parameter to EMBED_SCRIPT command to make embedding workspace files without unloading everything else possible.
    - Added support for specifying the spatial resolution for operations that take a resolution in meters using a new SPATIAL_RES_METERS parameter.
- Updated digitizing of new line and area features when a point location is snapped to a point feature or vertex with an elevation, a 3D line or area is created (assuming every vertex location had an elevation) with the elevation values of the clicked points/vertices.
- Updated path details reported for line-of-sight analysis to include information about the location of the minimum LOS clearance, like the location, clearance for Fresnel zone and baseline, and elevation of baseline**.**
- Added new line style ‘Solid with Arrow Pointing to Both Ends’ to allow easily drawing a line feature with arrows pointing at both ends.
- Added option to restrict the range of considered elevation values when generating contour lines from loaded terrain data.
- Made Download Online Imagery/Data dialog resizable.
- Allow measuring the combined cut-and-fill volumes of multiple selected areas.
- Updated the GPS Information display dialog to display the altitude above ground level (AGL) if terrain data is loaded at the current GPS location.
- Added right-click option to the Control Center to allow selecting all onscreen layers.
- Added right-click option to the Control Center to allow selecting all of the features in selected layers with the Digitizer Tool.
- Added support for configuring the band layout of files within a map catalog.
- Allow cropping to selected areas when printing.
- Added option to search by a feature's index in a layer when doing a search.
- Updated the attribute-based styling for layers to allow wildcards (* and ?) in the attribute value strings.
- Added 'Edit' button to Help->About dialog allowing you to easily change where settings files for things like custom datums, ellipsoids, and types/styles are stored.
- Added new option on the 'Specify Sample Spacing in Other Units' dialog for raster and elevation exports to use the sample spacing used for the last export.
- Added new option to view shed calculation to allow specifying a range of Fresnel zone

percentage clearances to match against rather than just a minimum percent clear.
- Made map catalogs remember the selected elevation units for vector files included in the map catalog.
- Updated batch conversion 'Use Quad Names' option to work for any type and to use the layer description if a quad name is not available.
- Added option to export slope values as percent rather than degrees when exporting Float Grid files.
- Added access to an additional zoom layer of OpenStreetMap.org tiles so you can zoom in far enough to see things like house numbers now.
- Added option to combine terrain layers using a multiplication operation.
- Added new option to convert area features with separate islands into a single parent area with all of the islands connected through a single vertex list with "stock arcs". This is useful for software that cannot handle areas with islands. The option is in the Advanced Feature Creation submenu of the right-click menu of the Digitizer Tool when at least one area with islands is selected.
- Added option to split DTED exports into folders by the western longitude of the exported tiles. For example, a tile having a southwest corner of W90 and N35 would be stored in your selected path plus \W090\N35.dt0.
- Added new blend mode, ‘Color to Grayscale’, that allows viewing any color raster /imagery layer in grayscale.
- Added support for displaying information about clicked features from loaded WMS servers using the Feature Info tool.
- Increased the number of remembered recently used files from 6 to 9.
- Added option to select areas that are only partially contained within an area when using the Advanced Feature Selection submenu option to Select Areas that are Contained Within Other Areas using the Digitizer Tool.
- Updated CSV export to maintain the original attribute order if all features being exported have the same set of attributes in the same order.
- Updated CSV export to include options controlling whether or not the LAYER and SYMBOL fields are exported for each point.
- Added new right-click menu option to the Digitizer Tool to allow counting the line and point features contained with selected area features and adding those counts as attributes (LINE_COUNT and POINT_COUNT) to the selected area features.
- Updated creation of range rings from selected point features to copy the attribute list of the points that the range rings is centered on to the created range ring feature.
- Made the 'I' column from .xyzi files automatically come in as an INTENSITY attribute when loading them with the File->Open Generic ASCII Data File menu command.
- Make splitting lines with per-vertex timestamps keep the timestamps.
- Added option to generate world files for tiles exported during Google Maps or Bing Maps exports. This can be useful when debugging the exports as you can then easily pull the exported image tiles back into Global Mapper (or other software).
- Allowed sorting of the columns in the control points list for the rectification dialog. This is handy for sorting by the error column.
- Added option to the Advanced section of the General tab of the Configuration dialog to allow reversing the direction of zooming down for the Page Up/Down keys and zooming

with the mouse wheel.
- Added option when exporting new GPX files to encode text using UTF-8 rather than ISO-8859-1. This allows non Western-European text to be encoded properly.
- Added option to only re-order the selected layers in the Control Center when selecting the option to re-order layers (by name, position, etc.) in the Control Center.
- Made the toolbar hide/show state be remembered for all toolbars.
- Fixed some errors creating buffers areas area/line features.
- Made batch conversion to DWG files use the DWG version last selected on the DWG export dialog.
- Made the last selected elevation units on the custom shader dialog be remembered.
- Made cropping to a selected area work for CSV exports.
- Updated the CSV export to use the selected Position Display Format settings for lat/lon values exported to CSV files rather than always using decimal degrees.
- Updated the GeoPDF import to recognize multiple map areas and bring them in as separate layers at the correct location and already cropped
- Updated the PNG export to remember the state of the "Save Vector Data if Displayed" option.
- Fixed problems loading encrypted PDF files.
- Corrected loading of BIL files with unsigned 16-bit elevation values.
- Don't add CLOSED attribute from loaded ASCII files if it was just used to mark a feature as an area or line.
- Fixed issue from v11.02 with the alpha channel from ECW files not being used.
- Updated creating lines from areas to not copy over any default attribute values from the area to the line.
- When copying features to the clipboard from the search results dialog, maintain the order of the sort when pasting those features.
- Fixed loss of measurement attributes when changing the classification of newly created features with the Digitizer Tool.
- Added new "Range Ring Center" point type.
- Added option to reorder maps in the Control Center by their type (i.e. elevation layers first, then raster layers, and finally vector layers).
- Updated Anuga Mesh import to use geo-referencing from file to properly position coordinates.
- Improved results of auto-interpolation during raster exports, particularly way undersampled or web-based exports.
- Updated creation of range rings and arc areas of a fixed radius to start the feature relative to magnetic north rather than true north if that option is selected in the Measure Tool.
- Added option to rotate feature dialog to allow rotating around the center of each individual feature center rather than around the center of the total bounding box of all features.
- Fixed issues with files rotated 90, 180, and 270 degrees with a world file.
- Made 'Restore Default Settings' button on General tab of the Configuration dialog also restore all elevation shader options.
- When editing the symbol multiple points with rotation or scaling applied, maintain the original rotation and scaling for each point unless those values are explicitly changed.

- When editing strike-and-dip points, don't change the default strike-and-dip symbol for when new strike-and-dip points are being created.
- Added button to feature vertices dialog to allow updating the existing per-vertex elevation values based on loaded terrain data.
- Fixed bug exporting Lowrance LCM maps that caused many point types to come out as cities rather than the proper type (like a navaid).
- Updated GPX to look for a URL attribute from a feature and include it as a <url> value for points exported to the new GPX file.
- Added option to the Advanced section of the General tab of the Configuration dialog to specify that exported PRJ files should append the .prj to the entire filename (like test.ecw.prj for test.ecw) rather than replacing the existing file extension with .prj).
- Added new 'Box Average 7x7' resampling method.
- Added new empty square custom point symbol.
- Allowed setting the 'Center Label on Line' setting when editing individual line feature styles.
- Improved support for SEGP1 files with only easting and northing coordinates.
- Updated MrSID Lidar Decode SDK to v1.1 for faster MrSID MG4 Lidar decoding.
- Added option to load EMF files as vector or raster (the current default).
- Fixed problems with missing data from some Tobin .bas format files.
- Added option when applying elevation from loaded terrain data to selected point features to control whether or not the unit label (like 'ft' or 'm') is appended to the elevation.
- Made layer metadata dialog close when the Escape key is pressed.
- When the advanced option to always display lat/lon values as WGS84 is checked, display the lat/lon values as WGS84 in the Feature Information dialog for point features in addition to on the status bar.
- Fixed error exporting named points with no symbol to DWG files.
- Fixed problems getting data from some secure (HTTPS) WMS servers.
- Added 'Automatic' setting for orientation of PDF exports to allow automatically selecting landscape or portrait orientation based on the aspect ratio of the exported data.
- Fixed bug with left margin setting in map layout being set to right margin when saving a re-opening a workspace or Global Mapper.
- Updated creation of a new feature classification/type from the feature edit dialog to use the currently selected style as the default style.
- Made the shift/offset feature dialog display the bounds of the selected feature.
- Fixed issues loading some PDS format files.
- Fixed problem with duplicate attributes when splitting line and area features on a change in a particular column when importing ASCII data.
- Made the automatic delimiter check during generic ASCII imports check for the pipe (|) symbol.
- Made multi-page TIFF files load as separate layers in the Control Center.
- Made last used contour simplification threshold be remembered.
- When moving items in the Control Center, ensure that the item being moved remains visible if possible.
- Fixed bug where rotating or scaling 3D area or line features would cause any per-vertex elevations to be lost.

- Updated map catalog files to save any calculated raster statistics for a layer so they don't have to be recalculated multiple times as a map is loaded and unloaded.
- Updated the sub-path text display on the profile dialog to include the slope as % grade (in addition to degrees slope).
- Updated the area and line elevation statistics calculation to include the slope as percent grade in addition to degrees.
- Updated the line elevation statistics calculation to include the maximum slope both up and down and well as the total elevation gain and loss along the line. These things are useful for evaluating hiking and biking trails.
- Added item to right-click menu for scale bar to zoom to a user-specified scale.
- Made more print settings, like header, scale, etc., be remembered between runs.
- When batch converting files that are loaded in the current workspace, copy any color grade or resampling settings from the loaded layers.
- Made the contour generation checkbox options be remembered between runs.
- Fixed import of per-vertex elevations when breaking on the change in a particular field during generic ASCII text file import.
- Added support for some additional non-comforming SEGP1 formats with only easting and northing values.
- Fixed positioning of PDF files with rotated orientations and embedded world file coordinates.
- Fixed issue with Bing Maps exports with just a single level of data not displaying in the web browser.
- Made vector search dialog not automatically redo search when an item label or attribute is changed. This allows faster editing in-place, you just have to trigger the re-search yourself.
- Added support for adding a point feature's latitude and longitude to the description string for the point in a KML file by using the %<Longitude>% and %<Latitude>% entries in the custom HTML text for the point description.
- Updated search-and-replace of road name text to automatically detect iconized road names.
- Added support for decoding Transverse Mercator projections from BSB files.
- Improved type mapping when exporting MP files (or any features with a MP_TYPE attribute) to the OSM XML format.
- When splitting area features at selected vertices, create the new areas in the same layer as the original.
- Corrected point record size written out to exported Lidar LAS files (this was incorrect in v11.02).
- Improved display of some TEXT entities loaded from DXF files to have the correct orientation and color.
- Fixed incorrect export of 3D area features to DXF files.
- Added option to control whether or not LAYER attribute is added to exported MapInfo files when doing a batch conversion.
- Added support for grades as a bearing measurement unit in the Measure Tool.
- Added 'Yes to All' and 'No to All' option for loading files where a projection is guessed based on the filename and the user is asked to confirm.

- Fixed export of non-closed 3D areas to vector KML/KMZ files.
- Added shortcut key (Shift+C) for File->Capture Screen Contents to Image menu item.
- Append the classification name of a feature to the text displayed in the status bar when the cursor is over the feature if it is different than the description.
- Updated Full View (Home) to use the cropped rather than full bounds of loaded layers.
- Fixed custom band setup for Erdas Imagine and NITF image formats.
- Fixed problems loading area features from some SOSI format files.
- When creating point features from selected line and area features with the Digitizer Tool, copy the attribute values from the selected features to the new points.
- Fixed dark display of some GIF files.
- Fixed problems saving named views from v11.02.
- Fixed export of header and footer text to PDF files when no top or bottom margins are used.
- Updated the hill shading when a non-zero maximum shadow darkness is used to scale the shadows between the maximum brightness and darkness rather than clamping any shadows to the max darkness value. This allows for more contrast in the darkly shadowed areas.
- Added support for loading SWIR and TIR data sets from ASTER L1B HDF files.
- Added new right-click option to the Measure Tool to enable display of extra digits of precision for measurement values.
- Updated SEGP1 exports to have an option (enabled by default) to write out easting and northing columns with an implied digit of decimal precision if possible.
- Fixed view shed calculation for checking beam visibility for negative transmission angles.
- When saving a line of sight to a KML file from the Path Profile dialog, save extra points along the line of sight rather than just the endpoints so that it displays properly in Google Earth.
- Added time of fix to GPS Information dialog.
- Updated WMS import to not default to EPSG:4326 (Lat/Lon WGS84) if the WMS server does not explicitly specify that EPSG:4326 is supported and there is another recognized projection available.
- Fixed issues loading some DGN files, particularly in the 64-bit version.
- Make sure that point features created from area centroids are always inside the area feature that they are created from.
- Updated package export to store elevation values with centimeter rather than decimeter precision. This results in slightly larger GMP files but higher precision.
- Updated Shapefile export to not mark fields with all empty values as numeric by default, but instead as character fields (unless the field came from a loaded layer that explicitly marked the field as numeric).
- Updated vector KML/KMZ export to allow loading an HTML description from a file.
- Fixed problems with holes in areas not always coming in properly from MapInfo MIF/MID files.
- Fixed issues loading directories of files from non-Windows servers, like SUSE.
- Fixed export of elevation values to DXF files for 3D TIN face area features.
- Corrected PDF export to scale when using margin units of centimeters.

- Fixed issue with labels not exporting to MapInfo MIF/MID or TAB/MAP files.
- Fixed issues with PDF files losing or having incorrect rectification when reloaded from a workspace.
- Made gridding vector exports to selected areas support cropping the export to the actual boundary of each selected area rather than just to the bounding box of the area.
- Made creation of distance/bearing/COGO lines create segments that much more exactly match the requested bearing (previously there could be errors of a few tenths of a degree).
- Added option to specify the export bounds for terrain/gridded elevation exports as “pixel is area” rather than “pixel is point”. This option is available under the Advanced section of the General tab of the Configuration dialog.
- Updated Google Maps export HTML file to prevent zooming in beyond where the data would be displayed.
- Fixed rare crash loading some improperly formatted Shapefiles.
- Made attributes for S-57/S-63 files include both the raw value and the associated text for that value (if known), rather than just the associated text if known.
- Fixed extremely slow loading and searching of some Tiger Shapefiles.
- Fixed usage of grid tightness and ‘fill to bounds’ settings when loading and gridding multiple Lidar LAS files at a time. Previously those settings would only be used on the first file, then the default settings would be used for the rest.
- Added support for getting per-vertex elevations from <gpxx:Depth> fields for tracks in GPX files even if no <ele> tags are available.
- Made adjusting the elevation units for map catalog layers work.
- Added support for getting roughness values for areas on export to Wasp .map files from attributes named ‘ROUGHNESS’ or ‘ROUGH’.
- When combining range rings, create an area feature rather than a line if the boundary if a valid area in the current projection.
- Added support for world files using comma rather than decimal points as decimal delimiters.
- Added support for exporting elevation GeoTIFF files at a particular scale and with a DPI stored in them.
- Fixed loading of multi-patch Shapefiles with multi-part triangle fan features.
- Added support for directly loading .bag.gz files.
- Fixed problem with shifted layers not showing up if shifted outside of the previous loaded data bounds until something else is loaded or unloaded.
- Don't prompt users to rectify images from KMZ files that aren't positioned as ground overlays in the KML files in the KMZ.
- Added support for loading style information from KML/KMZ files where the style definitions are at the end of the file rather than the beginning.
- Fixed slow response to clicks in some tools (like Digitizer) when ECW or MrSID files were loaded.
- Added support for loading Float/Grid files larger than 4GB in size.
- Added ability to change the color used for a view shed layer by right-clicking on it in the Control Center and selecting the option to change the color.

WHAT'S NEW IN Global Mapper v11.02

- **Significant New Features**
  - Added support to the Map Layout tool for automatically generating a map legend, either from the collection of loaded map features display styles or from a user-specified color palette.
  - Added 'Area Styles' tab to Options dialog for vector layers with area features allowing users to setup the styling of areas in a layer. Now users can use the default type-based styling, apply a single style to all area features in a layer, setup an attribute-based styling system that styles the areas based on the value of an attribute value or the display label, or randomly assign colors to the areas in a layer.
  - Added 'Line Styles' tab to Options dialog for vector layers with line features allowing users to setup the styling of lines in a layer. Now users can use the default type-based styling, apply a single style to all line features in a layer, setup an attribute-based styling system that styles the lines based on the value of an attribute value or the display label, or randomly assign colors to the lines in a layer.
  - Added support for resampling raster and elevation layers using bicubic interpolation or a box average of size 3x3, 4x4, or 5x5, in addition to the previously available options of nearest neighbor and bilinear interpolation. The "anti-alias" option on the Raster Options dialog has been replaced with one for selecting the sampling method to use.
  - Updated the option to crop lines to areas in the Digitizer Tool to allow splitting lines (i.e. keeping parts both inside and outside the crop areas).
  - Updated the option to add areas as islands in another area in the Digitizer Tool to allow removing overlapping but not enclosed areas from another area. The option was renamed to 'Cut Selected Area(s) from Another Area (Add Islands)' to reflect the new functionality.
  - Updated creation of buffer areas to allow combining overlapping buffer areas into a single combined buffer area.
  - Added option to create buffers some distance inside an area feature by specifying a negative buffer distance.
  - Updated area combine functionality in the Digitizer Tool to allow combining multiple groups of non-intersecting areas into as many combinations as are possible.
  - Added option to export GeoTIFF files to a particular scale.
  - Added new option when creating/flattening terrain from areas to taper the edges. This provides for easy simulation of non-flat areas like a sand bunker or hill while just providing a single elevation value for the area.
  - Added support for batch-converting to multi-band GeoTIFF imagery files.
- **New Supported Formats**
  - Added support for loading S-63 (encrypted S-57 charts) format files. Use File->Create S-63 User Permit menu command to generate a user permit file to provide to S-63 data provider to obtain S-63 files encrypted for use with your Global Mapper installation.

    - Added support for loading NV Verlag encrypted marine charts (EAB/BSB format).
    - Added support for loading TOBIN .bas (TDRBM II) files.
    - Added support for loading OziExplorer OZFx2 and OZFx3 files.
    - Added support for importing GRIB I and II format data, a format commonly used for meteorological data.
    - Added support for loading COLLADA 3D models (like model.dae files referenced from KML/KMZ files).
    - Added support for loading ATS (Alberta Township System) v4.1 files.
    - Added support for GeoDXF and GeoDWG files (DXF/DWG positioned with WLD file).
    - Added support for using Adobe Color Table (.act) files for palettes.
    - Added support for TIFF files with 12-bit per sample JPEG-in-TIFF encoding.
    - Added support for 16-bit TIFF files with palettes.
    - Added support for MrSID files encoded using CMYK colors.
    - Added support for LIDAR LAS files using point format 2 or 3. This allows for coloring Lidar data sets using the RGB color specified in the LAS file rather than the elevation-based color.
    - Added support for loading Anuga Triangulated Mesh format files.
    - Renamed Platte River export to reflect that it is the same as the Whitestar/Geographix Township/Range format export.
- **Projection/Datum Changes**
    - Added support for providing custom datums with the conversion to WGS84 based on a set of control points from a text file. This allows you to easily create your own datum conversions when you just know a collection of lat/lon values in the source projection and the corresponding WGS84 lat/lon location.
    - Added support for getting projection information from ESRI .aux.xml files.
    - Added the La Canoa (Venezuela), PSD93 (Oman), and North Sahara 1959 (Hassi Messaoud) datums as a built-in datums.
    - Updated PRJ files saved in WKT format to use names expected by ESRI products that in general don't conform to OGC standards.
    - Made Wisconsin County Projections write out correctly to GeoTIFF files.
    - Added support for decoding Irish Grid projections from Ozi .map files.
    - Added support for Dutch Grid projections in ECW files.
    - Fixed bug selecting UTM zones in the Southern Hemisphere in the 64-bit version.
    - Added EPSG codes for Corregre Alegre and Nord Sahara 1959 UTM projections.
    - Corrected latitude for Japanese Grid Zone IV projection.
    - Added support for EPSG code 2056 (Swiss Grid CH1903/LV95).
    - Fixed bug in v11.01 that caused custom datum transformation parameters to be lost in some cases.
    - Fixed positioning of GeoPDF files using Southern UTM zones.
- Updated ECW and JPEG2000 access to be much faster when sub-sampling for export or rectifying either of those types.
- Updated option that calculates and adds elevation attributes for selected areas to also

calculate and add MAX_SLOPE, AVG_SLOPE, and MODE_ELEV attributes for selected line features.
- Made selecting a feature with a GM_LINK attribute with the Feature Info tool open the file referenced by the attribute value in the current Global Mapper instance.
- Added option for users to choose which DWG version to create when exporting a new DWG format file.
- Allow specifying a prefix and suffix for labels when setting up labeling using multiple attributes for a layer.
- Added support for modifying the folder that user data is stored in by adding a registry key value with the desired path at 'HKEY_CURRENT_USER\Software\Global Mapper\SettingsFilePath'.
- Added option to generate 8-bit GeoTIFF files with no compression via a new compression selection list on the GeoTIFF export dialog.
- Removed separate JPG-in-TIFF GeoTIFF export option as you can now achieve the same results with a 24-bit RGB export and the JPEG compression option selected.
- Added option to online data source dialog to load WMS data sources from an external text file. This provides an easy way to share your list of WMS sources with other users.
- Updated 3D view to rotate around the center of the current view rather than the center of the entire data set currently in the 3D view.
- Updated LIDAR point clouds to display in color in the 3D view.
- Made most point symbols display in the 3D view rather than just a dot for each point.
- Added option to KML/KMZ export to highlight areas in Google Earth when you mouse-over them.
- Updated automatic loading of image links from attributes to support image filename values relative to the path of the data file containing the feature with the attributes.
- When exporting Shapefiles, provide more options for splitting the data into separate files so that you can now choose to split based on the type/classification of each feature (same as the current option) or based on the feature description/layer.
- Added support for cropping to selected area features when creating an elevation grid from loaded vector layers.
- Updated the rectification dialog so that if you press 'Enter' with the focus in the one of the coordinate windows then focus will advance to the next coordinate field. Pressing 'Enter' with focus in the Y/northing/latitude field will just add the control point.
- Added new right-click option to the Control Center allowing you to scale a selected layer based on a user-specified length of a selected line feature in that layer. This is useful if you know the actual length of a line feature in a vector layer and want to scale the layer so that the line length is correct without caring about where on the earth the layer is placed.
- Added new right-click option to the Control Center to allow opening Windows Explorer to the folder that a selected map file is in.
- Added new Combine Terrain operations to filter and keep the first layer value when it is greater than the second layer value and also less than the second layer value.
- When selecting two vertices of a single line feature with the Digitizer Tool, the status bar will list the length of the line between the two selected vertices.
- Made creating areas from line features maintain the per-vertex elevations of the

connected lines (if there were any).
- Fixed behavior of water level controls on the 3D view options dialog.
- Restored old 3D view behavior of going behind main window and having separate button on Windows start bar.
- Fixed flicker of main view when moving your cursor over a 3D path profile.
- Improved accuracy of affine and triangulated rectification operations.
- Significantly increased speed of contour generation.
- Automatically treat signed 16-bit samples from imagery TIFF files with values of -32767 as void areas.
- Fixed problems reading projection information from some newer MrSID files.
- Added display of the target compression ratio used when creating a MrSID file to the metadata display for that layer.
- Allowed cropping to selected areas when batch converting to vector formats.
- Added support for controlling multi-band GeoTIFF exports from scripts using a new BAND_EXPORT_SETUP parameter for the EXPORT_RASTER command.
- Added support for exporting a new raster with the same color/palette type as the file being exported using the EXPORT_RASTER command by using the PALETTE=KEEP_SOURCE parameter.
- Corrected creation/flattening of terrain from 3D area features with islands.
- Made Lidar files share the elevation shader with all loaded elevation and Lidar layers, making them consistently color across multiple layers.
- Fixed problems with missing data from Italian TAF that have invalid records.
- Made scaling of built-in custom shape symbols work properly.
- Fixed handling of multi-line text in map layouts when saved to a workspace.
- Fixed problem with map layout text becoming upper-case when loaded from a workspace.
- Improved detection of datums from P190 files.
- Corrected display of elevations on real-time cursor display for path profile display when doing a line-of-sight analysis with earth curvature enabled.
- Changed shortcut key to toggle all vector layers on and off to Ctrl+Shift+V from just 'V' since the 'V' shortcut key was already used to enable snapping only to vertices.
- Fixed range of elevation legend display and shader colors when the min/max elevation values are overridden for a loaded terrain layer.
- Allowed non-integer starting number values when creating new point features spaced along selected line or area features using the Digitizer Tool.
- Allowed naming of points sequentially or based on distance when creating new point feature spaced by distance along selected line or area features using the Digitizer Tool.
- Made "display elevation legend on right" toggle work properly.
- Fixed bug in PDF export that caused labels for lines with a Null drawing style to not be exported.
- Fixed bug with road icons assigned to existing line features not being maintained when saving and restoring a workspace.
- Corrected progress bar behavior during Vertical Mapper export.
- Updated creation of terrain when flattening areas to flatten based on drawing order, so the top-most drawn area that is flattened will be the flattened part in the terrain (useful for

nested 3D areas, like for a building).

- Fixed crash when closing a layer that a search is active on in the vector search dialog.
- Fixed problems in v11.xx loading some ASRP/USRP data sets.
- Added support for additional HDF data sets.
- Added recognition of .190 as a P-190 file extension.
- Added option to Measure Tool to allow calculating grid distance rather than great circle distance for distance calculations.
- Fixed DTED export sizes near latitude change boundaries in the Southern Hemisphere.
- Fixed bug loading points from some MapInfo TAB/MAP or MIF/MID files.
- Added option when finding features with duplicate attribute values to delete the duplicates.
- Fixed half-pixel shift of Vertical Mapper grids from v11.01 release (v11.00 was ok).
- Added options to the Advanced Section of the General tab of the Configuration dialog to disable the automatic interpolation of reprojected or resampled raster layers on export and when zoomed way out on a layer.
- Fixed problem with HATCH entity pattern name being saved as display label when loading DXF files.
- Fixed added of extension to files when gridding to selected areas and the name used for an export file already has a period in it.
- Fixed incorrect interpretation of 4th color band as an alpha channel for some ECW files.
- Fixed display of bearings relative to magnetic north.
- Fixed problems accessing WMS through secure (https) connections.
- Added progress reporting to potentially lengthy transfers of features to a new layer or simplification of multiple line/area features.
- Added support for customizing the pixel radius used when snapping to existing features using the DWORD registry key 'HKEY_CURRENT_USER\Software\Global Mapper\SnapToPixelRadius'. The default value is 10 pixels.
- Significantly sped up the deletion of large numbers of vertices from the vertex dialog.
- Added option to the Advanced section of the General tab of the Configuration dialog to 'Disable Display of Pan Arrows on Map Edge', allowing one to disable the map-edge pan arrows displayed in most tools.
- When using the File->Rectify Imagery menu command to rectify and export images, maintain the DPI (if available) of the original image and create GeoTIFF files with an alpha channel if the source image has transparency.
- Improved handling of layer translucency when exporting Global Mapper package files.
- Fixed bug decoding custom point symbol names with multi-part names, like DOT_EMPTY, VERT_BAR, DIAG_CROSS, etc.
- Updated display of most error messages to include the build version and to also copy the error text to the Windows clipboard for easy pasting.
- Updated import of 3D face features from DXF files to automatically mark them as Tin Face areas so they will export by default as 3D Face features to new DXF files.
- Added options to control whether or not LAYER and ELEVATION attributes are added to MapInfo MIF/MID and TAB/MAP exports.
- Fixed option to default to exporting screen bounds work even if you don't activate the Export Bounds tab during an export.

- Sped up the load of MrSID LIDAR files when loaded in preview mode.
- Added support for specifying area border widths as a fixed width in meters.
- Made export of 3D area Shapefiles using loaded elevation layers work when done using the EXPORT_VECTOR command in a script file.
- Added vertex elevation (if available) to ZMap+ XYSegID format export.
- Made the image rectification dialog display the errors in the X and Y direction for each pixel in addition to the total error.
- Added support for customizing the number of decimal digits written out for the X and Y coordinates for a Simple ASCII Text export through the use of a DWORD registry key 'HKEY_CURRENT_USER\Software\Global Mapper\ASCIIExportCoordPrecision'. For example, set this value to 6 to get 6 decimal digits for each X and Y coordinate.
- Made the print header and footer font selections be remembered.
- Made Ctrl+Left Click on a photo point from an EXIF JPG file in the Feature Info tool bring up the normal Feature Info dialog rather than the image.
- Added ELEVATION and TIMESTAMP attribute to EXIF JPG picture points if the EXIF data contains an elevation value or creation timestamp for when the picture was taken.
- Made loading a workspace file with the File->Open Data File menu command correctly restore the zoom bounds of the workspace file.
- Updated the 3D Shapefile and Simple ASCII Text export to obey the export elevation units selection on the Vertical Options tab of the Configuration dialog.
- Made DGN exports that have other DGN files as the source data maintain the level numbers and names on export to the new DGN file if possible.
- Made the Control Center remember its size between runs.
- Added support for Idrisi Raster files with a .img extension.
- Fixed half-pixel shift when scaling or rotating symbols.
- Fixed issue with "always on top" fixed screen layers displaying twice in exported PDF files with non-zero margin values.
- Fixed issue with labels marked not to display still showing up in exported PDF files.
- Fixed issue with the scaling of the header/footer text in exported PDF files, particularly at low DPI values.
- Fixed issues with the placement of right-aligned and centered text in exported PDF files.
- Fixed error loading some raster KMZ files from workspace files.
- Fixed problem with area labels not moving with the area if it is moved.
- Fixed error loading some multi-band PDS files.
- Changed batch conversion to Arc ASCII Grid files to use .asc extension instead of .agr.
- Added PLAY_SOUND script command to allow playing a sound file from a script.
- Fixed out of memory errors when working with very large numbers of JPG files.
- Fixed issues loading DXF files with lines 256 characters in length.
- Added new option to the Advanced section of the General tab of the Configuration dialog to "Auto-Fake Location of Unpositioned Rasters".
- Allowed Arc ASCII Grid files that are too large to load into memory still be loadable.
- Made the option to 'Crop Right and Bottom to Export Bounds' on the Gridding tab of Export dialogs work when gridding to fixed pixel size tiles.
- Significantly increased display and export speed for some very large CIB/CADRG/RPF data sets.

- Put GPX <time> field for <wpt> features directly after <ele> field so that Garmin's MapSource can read those GPX files.
- Fixed matching on empty name/attribute values when using the ASSIGN_TYPES script command.
- Allowed for placement of fixed screen layers and map layout items (like scale bar and elevation legend) in centimeters (in addition to inches, degrees, and percent).
- Made grayscale export option work properly Optimi Clutter export.
- Sped up marking large numbers of features as deleted using the Digitizer Tool.
- Made right-click when drawing a new line in trace mode with the Digitizer Tool cancel the operation.
- Changed shortcut key for toggling vector layers on and off from Ctrl+Shift+V (which was already assigned for the special paste-and-keep function) to Ctrl+Alt+Shift+V.
- Updated the 3D viewer so that extruded areas only extend to the terrain surface instead of well below it.
- Fixed problems loading GXF files with lots of comments.
- Made PDF exports maintain the proper paper size in Acrobat and other PDF readers.
- Added support for pulling additional <Placemark> tags from KML files and using them as attributes for the created features, like <address> and <snippet> tags.
- Added support for creating new area and line types with line widths that are specified as a fixed width in meters.
- Fixed assignment of point attributes to areas when the projection of the point and area features was not the same.
- When exporting Lidar LAS files from vector point data, use the value of an INTENSITY attribute for the intensity value exported to the LAS file.
- Fixed export of tiled GeoTIFF elevation files.
- Updated GPX file to use type name for <desc> element when the description is unknown.
- Updated TerraServer-USA links to point to MSRMaps.com as Microsoft changed the name and URL.

WHAT'S NEW IN Global Mapper v11.01

- **3D Viewer Improvements**
  - The 3D Viewer now supports displaying 3D vector features in space above or below the terrain surface. You can also extrude 3D area features to create building-like displays.
  - You can now save 3D screenshots of much higher resolution.
  - You can now get descriptive text (tooltips) about the 3D toolbar buttons by hovering your mouse over them.
  - Added new button to toolbar to toggle wireframe display on and off.
- **Other Significant New Features**
  - Added new GPS menu option to send any loaded data map directly to a compatible Garmin GPS device, such as a Colorado or Oregon handheld, for display as a raster map on the unit. This allows display of anything, including imagery, on compatible Garmin GPS devices!
  - Added support for creating buffer areas some fixed distance around selected area

and line features. This option is available from the Advanced Feature Creation submenu of the right-click menu in the Digitizer Tool.
- Allowing sorting search results by any attribute rather than just the name.
- Added support for controlling at what zoom levels a map layer will appear, similar to the functionality available with a map catalog. You can configure this by right-clicking on a layer in the Control Center and selecting the new option to setup what zoom levels a map will display at.
- Added support for generating multi-band GeoTIFF files with 1 and 2 bands as well as 32-bit floating point samples.
- Added support for generating 8-bit (256-color) GeoTIFF files with transparency.
- Added support for importing BIL and GeoTIFF imagery files with 32-bit floating point samples.
- Fixed major performance issue from v11.00 with triangulating and gridding 3D vector data. It should now be 5-10 times as fast as in v11.00.
- Added support for generating tiled GeoTIFF files.
- Added new Search menu option to allow finding and editing loaded vector features with the same attribute values. This is useful for enforcing things like an attribute that needs to be unique.
- Made elevation statistics calculated for area features include slope statistics.
- Added font/label scaling option when exporting (Geo)PDF files, allowing you to easily grow or shrink labels written to the PDF file.
- Added ability to export to a fixed scale when exporting (Geo)PDF files.
- Added support for generating MapInfo TAB files for most raster format exports.
- Changed behavior of drawing lines using the trace mode of the Digitizer Tool to work while the mouse button is depressed and complete when you release it. This makes the trace mode work much better with digitizing tablets. Also, if your drawn feature is nearly closed, you will be prompted whether to create an area or a line feature.
- Improved the labeling of areas so that the area label will always be inside the area.
- Updated KML export to allow displaying point features above the terrain surface.
- Updated KML vector export to have option to use symbols displayed in Global Mapper for point features rather than default push-pin.
- Added new Lidar import option to pull in data in "preview" mode, which just pulls in every 10th point for quick load and display. You can now also choose to only pull in ground-shot points during a Lidar point cloud import.
- Added option to Control Center to create a layer with a point feature at the center of each gridded elevation layer cell center. This provides a handy way to edit elevation layers as you can easily edit the elevation values of the created points or remove problem points, then create a new elevation grid from the edit points.
- When displaying a 3D path profile of a 3D line feature, show the 3D line feature as well as the elevation profile.
- Allow selection of the text font to use when displaying a 3D path profile rather than just the color of the text to display.
- Updated printing to a file to allow the full resolution of the selected printer always be available, regardless of paper size.

    - Added new option to range ring creation to allow creating rectangles of the specified range rather than rings.
    - Added LOAD_STYLE_FILE script command to allow loading .gm_style files saved from the Styles tab of the Configuration dialog from scripts and also created new custom types from scripts.
    - Updated Shapefile exports to maintain the field type and length values (if possible) from the source data files if they are Shapefiles or DBF files.
- **New Supported Formats**
    - Added support for reading Idrisi Vector (VCT) format files.
    - Added support for reading side-scan sonar data from XTF (eXtended Triton Format) files.
    - Added support for reading Italian CML (Cadastral Markup Language) format files.
    - Added support for reading Italian TAF (Confidence) format files.
    - Added support for reading DWG 2010 format files.
- **Map Layout Changes**
    - Allow map scale to be displayed at a fixed percentage of the output device width.
    - Updated map layout to support adding text anywhere on the map.
- **Projection/Datum Changes**
    - Added built-in support for Bessel 1841 Ellipsoid, IGN72 Grande Terre (New Caledonia), and RGNC91-93 (New Caledonia) datums.
    - Added support for creating custom datums that use a prime meridian other than Greenwich.
    - Fixed problems loading Touratech TTQV.cal files that use commas for decimal delimiters rather than periods.
    - Updated Robinson projection to properly crop to world edges by default.
    - Added the text NADCON to any datums that use NADCON datum transformation tables.
    - Corrected definition of EPSG code 3057 (ISN93 / Lambert93).
    - Corrected Swiss Grid definition (azimuth should be 90 instead of 0).
    - Made longitude/meridian parameters be displayed and entered relative to the prime meridian associated with the selected datum rather than always relative to Greenwich.
- Allowed cropping DWG, DXF, and several other exports to a selected crop area.
- Added right-click option to 3D path profile dialog to create a new point feature at the current cursor location.
- Made 3D path profile CSV export include slope value for each segment.
- Added Vertices button to feature edit dialog when editing an existing line or area allowing you to edit the vertices for that feature.
- Greatly improved appearance of most loaded EMF files by making them come is as a raster layer rather than a vectorized one.
- Added new button to the view shed options dialog to allow having ground-relative transmitter and receiver heights calculated based on just a subset of the loaded elevation layers. This is useful if for example you have a layer with the bare ground elevations, then another gridded elevation layer that includes buildings that you want to use for line-

of-sight purposes. With this new option you can choose to have the transmitter and receiver heights relative to the bare ground layer.
- Added display of calculated scatter angle for the active line of sight when showing path details for the path profile/LOS.
- When moving one or more line and/or area features with the Digitizer Tool and a single vertex on those features is selected, made snapping work so that selected vertex will snap to other existing features.
- Greatly improved initial display of OS Mastermap data from GML files. Most areas will now automatically be displayed using the OSGB-recommended colors.
- Made fill of small gaps during raster export work even at 'T' intersections of no data lines. The average of colors across the diagonals will be used at those intersections if available.
- When gridding exports to selected area features and not cropping to the area boundaries, use the full bounding box of the area for each export rather than the intersection of the area bounding box with the specified export bounding box.
- Made custom shader dialog resizable.
- Added new option when batch converting to Simple ASCII Text files to control whether or not a blank line is used to separate features.
- Added new option when batch converting the CSV files to allow using a space separator rather than a comma.
- Fixed problems loading TIF files created by AutoCAD Raster Design that specify they both have strips and tiles (they really have tiles).
- When digitizing a line with the stream mode, delay any simplification until the feature completes and also don't remove quite as many vertices when simplifying.
- Added new keyboard shortcut (Shift+T) to go into line trace mode in the Digitizer Tool.
- Added new ASCII import option to skip a fixed number of lines at the start of a file.
- Fixed problem saving new measure areas and lines to new layers.
- Fixed problem with small red rectangle displaying for new point features using the 'No Symbol' symbol type.
- Improved loading of Shapefiles with overlapping island areas within a parent.
- Fixed bug cropping to selected areas during batch conversion. This bug was introduced in the v11.00 release.
- Drastically reduced memory requirement for Surfer Grid exports, allowing basically unlimited size exports.
- Made generated contour lines be oriented such that the higher elevations are to the left of the line.
- Fixed error saving workspace files with a PDF loaded.
- Updated the ETA reporting on progress dialogs to add a completion date if the operation is estimated to take more than 12 hours.
- Fixed problem getting DigitalGlobe imagery in some locations.
- Added option to PDF export to control whether or not fonts are embedded.
- Fixed problem with background values stored for exporting multi-band GeoTIFF files.
- Added option to BIL export to allow exporting shorter ESRI/Arc format .hdr file.
- Improved import of HATCH entities from DXF files to maintain islands/holes inside areas.
- Reduced simplification threshold used when saving active GPS tracklogs from 1.5 m to

0.5 m so more detail will be kept from recorded track logs.
- Added new GPS menu option allowing you to disable the simplification of track logs.
- Fixed crash loading some large Erdas Imagine .img files.
- Added support for import and exporting DGN v8 files in 64-bit builds.
- Added support for interrupting the draw of a large raster layer by pressing the ESC key.
- Updated KML "super overlay" export to work better with transparent layers.
- Removed warnings about unknown attributes during S-57 imports.
- Fixed problem importing some S-57 files resulting in crossing lines and lines with gaps.
- Fixed problems in v11.00 connecting to online data sources through some proxy servers.
- Made map catalog loads report any files that cannot be found.
- Updated Lowrance LCM export to include water label points for any labeled water areas.
- Updated the ECW 64-bit export to multiply your target compression ratio by 0.6 so that the end results are comparable to the 32-bit ECW export with the same target compression ratio.
- Fixed one half sample spacing shift of raster/elevation layers when exporting them to a new raster format with vector data included.
- Fixed error when doing Lowrance USR export (this started with v11.00 release).
- Made workspace and script files show up in the normal File->Open Data File dialog.
- Made "Select From" checkbox options on the Vector Display tab of the Configuration dialog always reset to checked when you start a new instance of Global Mapper rather than being remembered.
- Added new option to Google Maps and Bing Maps (Virtual Earth) exports to allow skipping empty tiles.
- Added option to map catalog dialog to allow using a non-default drawing style.
- Added option to DigitalGlobe export to allow using premium un-watermarked access only when exporting and just browsing using free watermarked imagery.
- When creating a new line with distance/bearing/COGO input, display a bullseye at the line start location.
- When creating a new line with distance/bearing/COGO input and a single point feature of line/area vertex is selected, give the user the option to start the line at the selected point/vertex.
- Fixed problem with creation of distance/bearing/COGO line by right-clicking in the Feature Info dialog not working.
- Made elevation display units setting from Vertical Options tab of the Configuration dialog be remembered between runs.
- Fixed bug in Lidar LAS export with the wrong sentinel value being written for variable length records used to store projection information.
- Fixed problems loading 3D polyface meshes from DXF files.
- Added support for transparency (i.e. alpha channel) from tiled TIFF files and TIFF files with something other than 3 bands of data.
- Made 3D path profile remember sample count setting if changed.
- Added new option to not get elevation values from any attribute on the vector type options dialog. This will allow elevation requests on export to fall through to underlying elevation data for data sets that already have elevation attributes.
- Fixed error in calculating cut-and-fill volumes along a line feature.

- Added 'V' shortcut key to toggle the display of vector layers on and off.
- Updated 'Save Workspace As' option to default the filename to the existing workspace filename.
- Fixed bug with auto-cropping of collars from some file types when those files are displayed from a map catalog.
- Improved recognition of elevation values from generic ASCII import. Now values without a space between the elevation value and units will be allowed for an elevation column.
- Make sure improperly formatted <time> values are not exported to GPX files.
- Fixed blending of online layers (i.e. TerraServer-USA, WMS layers, etc.) with underlying DigitalGlobe layers.
- Fixed error loading OCAD files with bad offsets in their header.
- Fixed problems loading some MapTech PCX charts.
- Added support for reading annotation and traffic line features from S-57 (ENC) files.
- Added 'nautical miles' as an available distance unit when creating distance/bearing/COGO lines.
- Added new option to allow disabling the automatic snapping behavior of the Digitizer Tool. This option is in the general option list on the Vector Display tab of the Configuration dialog.
- Updated creation of point features sampled along a line or area boundary with a fixed distance between samples to allow a start label to be used and to label with the distance rather than an incremented number.
- Updated the Digitizer Tool option to assign area attributes to lines in those areas to not replace existing values in the line attribute list but only add new attributes.
- Added support for creating 24-bit TIFF files when batch converting to raster KMZ files.
- Made double-clicking on a line type on the Line Styles tab of the Configuration dialog bring up the default attribute list for that type.
- Made double-clicking on an attribute on the default attribute list dialog for a type automatically bring up the edit dialog for the selected attribute.
- When creating point features from selected line vertices and the line has per-vertex timestamp values, add a TIMESTAMP attribute to each new point.
- Allowed selection of only vertices from already selected line or area features by holding down the 'S' key when left-clicking or dragging a box in the Digitizer Tool.
- Write more precision for sample sizes in exported Gravsoft Grid files to prevent problems with large files exported with degree units.
- Made Configuration dialog remember the tab it was on when last closed.
- Fixed bug in placement of TerraScan LIDAR files with non-default origin or units.
- Made import of marine features from MP files using extended type notation (0x01XXXX) correctly have MARINE=Y attribute added.
- Fixed smoothing of area features to behave the same as smoothing a line feature with the same boundary.
- Added support for specifying prefix text when creating points spaced along a selected line or area feature with the Digitizer Tool.
- Added support for tracking NMEA GPS devices that don't separate the NMEA sentences with newline characters.

- Made area features created from lines in the Digitizer Tool automatically have measure attributes added to them.
- Fixed error from v11.00 with some polynomial (4-point) image rectifications.
- Corrected DXF imports and exports to treat color index 0 as black, not white.
- Added option to disable the alpha channel for raster layers on the Band Setup tab of the Options dialog for the layer. This is useful for layers with bad alpha channel values.
- Added support for loading KML files with multiple alternate names for the <Placemark> tag.
- Added support for disabling automatic export of BigTIFF formatted files when exporting to very large GeoTIFF files from a script by adding a DISABLE_GEOTIFF=YES parameter.
- Added support for 16-bit Vertical Mapper clutter (.grc) files.
- Fixed problem with text size on elevation legend and distance scale saved to PDF files.
- When creating view sheds from selected point features, made the attributes of those selected point features be copied over to the new tower point that is created.

WHAT'S NEW IN Global Mapper v11.00

- **Significant New Features**
    - Created native 64-bit version of Global Mapper, allowing users of 64-bit versions Windows to work with much larger data sets.
    - Added support for exporting loaded data directly to geo-enabled PDF files. This includes keeping all vector features as separate entities rather than rasterizing them.
    - Added support for directly loading PDF/GeoPDF® format files.
    - Added support for exporting loading vector data to DWG format files.
    - Built-in DigitalGlobe imagery access was updated to have much better worldwide coverage.
    - Added free built-in access to global street-level maps from OpenStreetMap.org via the File->Download Online Imagery menu command.
    - Added support for exporting GeoTIFF files with 3 or more bands of data and 16 bits per band, thus allowing multi-spectral input files to be output without losing any information.
    - Added new Map Layout option under the Tools menu and on some right-click menus to allow more control over the display of the elevation legend and distance scale, as well as new support for adding margins and a north arrow to your map display/exports.
    - Added real-time display of current cursor information (location, distance, elevation) to 3D Path Profile dialog. In addition, you can now also click to define a sub-path on the 3D Path Profile dialog and get information about that sub-path displayed.
    - Added ability to easily create symbols from common shapes like dots, squares, diamonds, and stars of a user-selected size and color anywhere that a point symbol can be selected.
    - Added ability to add custom point symbols from PNG, GIF, and JPG images (in

addition to the current support for BMP and ICO files). This includes support for translucent symbols by using PNG files with an alpha channel for transparency.
    - Added ability to add custom point symbols from vector format files, including EMF, DXF, and Global Mapper symbol (.gm_sym) files, which are just ASCII XYZ files.
    - Added support for scaling point symbols, allowing you to change of existing point symbols either by some fixed percentage or to make them a fixed number of meters in height on the display.
    - Updated vector exports that are cropped to a selected area to actually crop the line and area features being exported to the selected area.
    - Added new option to display a whitened highlight area in terrain areas that are getting direct sunlight. The amount of whitening can be controlled on the Vertical Options tab of the Configuration dialog.
    - Added new option to vector KML/KMZ export to generate an index KML file. This can help manage large collections of vector KML files that would otherwise overwhelm Google Earth.
    - Added support for averaging your GPS position to create a more accurate waypoint when tracking a connected GPS device.
    - Added new Search->Search and Replace menu option to allow easily searching for a particular text item and replacing that with a new value, including appending or pre-pending text to existing values.
    - Prompt users for location of missing files when loading workspaces rather than just skipping the load of those files.
    - Added estimated completion time to progress dialog for operation that take longer than 30 seconds.
    - Added support for named views that are saved to a workspace file rather than globally shared, thus allowing you to easily share views view workspace files.
    - Added support for adding area and line features to a running instance of Global Mapper using the External Control API interface.
- **Digitizer/Edit Tool Enhancements**
    - Added toolbar for Digitizer/Edit Tool to make it easier to perform many commonly used operations.
    - Added ability to create new line features by tracing them without clicking at each vertex with the Digitizer/Edit Tool.
    - Added ability to rotate and scale features.
    - Added ability to combine arbitrary area features.
    - Added ability to find the intersection of two area features.
    - Added ability to crop selected line features to a selected area feature.
    - Added ability to apply attributes to selected line features from selected area features that the lines are completely enclosed within.
    - Added a new feature to the Digitizer/Edit tool allowing you to select one or more points, then right click and assign attributes to those points based on the top-most area feature with attributes that each point is contained in.
    - Added a new feature to the Digitizer/Edit tool allowing you to create labeled point features at a regularly spaced interval along selected area and line features. This is

in the Advanced Feature Creation right-click menu.
    - Added a new feature to the Digitizer/Edit tool allowing you to resample selected area and line features at a regularly spaced interval along selected area and line features. This is in the Advanced Feature Creation right-click menu.
    - Added a new feature to the Digitizer/Edit tool allowing you to simplify (reduce the vertex count) of selected line and area features by removing vertices that do not significantly contribute to the shape of the feature.
    - Added a new feature to the Digitizer/Edit tool allowing you to smooth selected line and area features by moving existing vertices to create a smoother appearance.
    - Added option to split selected line features into separate line features for each segment under the Advanced Feature Creation sub-menu in the Digitizer Tool.
    - Added option to calculate view sheds at each point feature selected with the Digitizer Tool rather than just at the clicked location.
    - Allow generation of 3D path profiles from selected area features using the Digitizer Tool (previously only lines were supported).
- **New Supported Formats**
    - Added support for loading from and exporting to PDF/GeoPDF® format files.
    - Added support for exporting loaded vector data to DWG format files.
    - Added support for exporting loaded data to Window bitmap (BMP) format files.
    - Added support for loading MrSID MG4 Lidar files.
    - Added support for loading Vertical Mapper (MapInfo) Grid/Clutter format files.
    - Added support for loading QCT (Quick Chart) and QED format files.
    - Added support for loading Google SketchUp (.skp) format files.
    - Added support for exporting loaded vector data to OSM XML (OpenStreetMap.org) format files.
    - Added support for loading HTF (Hydrographic Transfer Format) files.
    - Added support for loading SPS (Shell Processing Support) format files.
    - Added support for loading MapMaker Drawing (DRA) format files.
    - Added support for loading LMN (Spectra Line Management Node) files.
    - Added support for loading GSD (Swedish DEM Grid) format files.
    - Added support for loading BAG (Bathymetric Attributed Grid) files.
    - Added support for loading FCC ASR (Antenna Registration System) data files.
    - Added support for loading Japanese DEMs in LEM/CSV format.
    - Added support for loading Garmin TCX (Training Center Database) files.
    - Added support for loading CXF (Italian Cadastral Format) files.
    - Added support for exporting loaded point and line data to UKOOA P1/90 format files.
    - Added support for exporting loaded vector data to Lowrance LCM format files for display on Lowrance GPS devices.
    - Added support for exporting loaded elevation data to Vertical Mapper (MapInfo) Grid format files.
    - Added support for exporting loaded data to tiles for displaying on the web with Zoomify (use File->Export Web Formats->Export Zoomify menu command).

    - Added option to import features from ASCII text files using the Well-Known-Text (WKT) format for storing feature geometry.
- **Image Rectification Enhancements**
    - Added checkboxes to allow easily turning individual control points on and off to see how it affects the rectification.
    - Added an optional crosshair display traversing the entire zoomed and reference image views.
    - Added dynamic cursor location display for reference image view.
    - Added display of the selected rectification method to the dialog title bar.
    - Added support for using a Helmert (similarity) transformation when rectifying imagery and vector data layers.
    - Made polynomial rectification with 6 or more control points use a 2nd degree (N=2) equation.
    - Made Ctrl+Left Click in the Zoomed View automatically fill in the projected coordinates and also zoom the Reference View to the same approximate location and zoom scale if possible.
    - Made Ctrl+Left Click in the Reference View automatically fill in the pixel coordinates and also zoom the Zoomed View to the same approximate location and zoom scale if possible.
    - Added option under the Options menu to automatically save the control points (GCPs) to a GCP file when closing the dialog.
    - Made the control point list resize when the dialog is resized.
- **Projection/Datum Changes**
    - Added built-in support for the Japanese Projection System (zones I - XIX), the Philippines Grid projection (zones 1-5), and the Sinusoidal (Integerized) projection.
    - Added built-in support for Clarke 1866 Authalic Sphere, ED50 (North Sea), ED50 (Norway Offshore N62), ED50 (Norway Offshore S62), JGD2000 (Japan), LKS92 (Latvia 1992), NAD83 (South Carolina HPGN), Naparima 1972, Rome 1940 [Monte Mario] (w/ Rome meridian), SIRGAS 2000 (Brazil), South American 1969 (Brazil), Wisconsin - Burnett County, Wisconsin - Douglas County, and special MODIS spheroid-based datums.
    - Added support for a Central Longitude parameter for the Geographic (Lat/Lon) projection to allow re-centering a lat/lon display on a longitude other than 0. This allows for easily wrapping maps near the anti-meridian.
    - Added built-in support for Mars 2000 sphere and polar sphere datums and ellipsoids.
    - Added support for Maine CS2000 State Plane zones.
    - Updated the built-in Lambert-93 projection to now be a zoned projection supporting the base Lambert-93 definition as well as the CC-42 through CC-50 zones
    - Renamed 'Central Meridian Scale Factor' in projection selection dialog to just 'Scale Factor' so that it would fit on the screen better.
    - When writing out State Plane projections to PRJ files, save the name of the State Plane zone in the projection name at the start of the PRJ file.

- Added support for modifying the location relative to which the extra scale factor is applied to State Plane projections. This is for advanced users with some very unusual modifications to State Plane projections.
- Corrected EPSG codes and added new ones for many State Plane projections.
- Fixed problem with an extra scale factor being applied to some State Plane zones extracted from ECW files (this bug was introduced in v10.01).
- Corrected transformation for Kertau 1948, PRS92, and Timbalai 1948 datums (incorrect since v10.01).
- Improved accuracy of NTF France datum conversions (they now agree with the official results to within 1 centimeter).
- Improved accuracy of ROME 1940 and WGS72 datum transformations.
- Updated Robinson projection to use newer PROJ4 library definition rather than older GCTPC library definition that does not seem to be consistent with any other applications.
- Added support for using inches as a linear unit with projections.
- Increased valid range for scale factor parameters from [-2,2] to [-10,+10].
- Allowed use of WGS84 with Austrian Grid, Belge1972, and Dutch Grid projections.
- Updated MrSID imports to treat false easting/northing values embedded in the SID file as GeoTIFF tags as always being provided in meters as that seems to be how the MrSID library treats them.

- **Scripting Language Changes**
  - Added new LOAD_TYPE_FILTER script command for loading area, line, and point filters from GMF (Global Mapper Filter) files.
  - Added new EXPORT_PACKAGE script command to allow exporting loaded data to Global Mapper Package files.
  - Added new GENERATE_REPORT script command to allow creating a text report about the loaded vector layers, including feature counts, combined line length, and total covered area, broken down by feature name, type, or attribute value.
  - Added new GENERATE_LAYER_BOUNDS script command to allowing generating a layer with bounding areas for the loaded data from a script.
  - Added support for splitting a vector export into a separate file for each group of features with the same attribute values using the SPLIT_BY_ATTR=YES parameter. The new FILENAME_ATTR_LIST and FILENAME_INCLUDE_ATTR_NAME parameters can be used to control the file naming when splitting an export using this new functionality.
  - Modified specification of vertical exaggeration for VRML exports to allow manual number entry rather than using a slider to allow for a greater range of values and a more intuitive experience. The VERT_EXAG value used for the EXPORT_ELEVATION script command also now uses a normal value rather than a strange scaled value.
  - Made GEN_WORLD_FILE parameter work for all export formats with EXPORT_ELEVATION and EXPORT_RASTER script commands.
  - Updated default SIMPLIFICATION parameter value for

GENERATE_CONTOURS command to match what is used in the user interface.

- Added new collar cropping option to allow manually specifying a degree boundary to crop each side of a loaded layer to. For example you might specify that the crop boundary for a layer is at even degree boundaries.
- Added new option to Search->Search by Attributes dialog to allow searching on a value in any attribute, rather than just a single selected attribute.
- Automatically use bilinear interpolation when exporting reprojected or resampled raster layers that are not palette-based.
- Added ability to label features based on the feature type, description, and/or source filename as well as attributes when setting up feature labeling for a vector layer via the Options dialog for the layer from the Control Center.
- Added support for exporting loaded area data to multi-patch Shapefiles.
- Dramatically increased speed of raster and elevation exports cropped to areas with a large number of vertices.
- Updated to save user settings in Application Data area of Windows rather than in Program Files folder. This is more in line with the requirements of newer Windows versions like Vista and Windows 7. The location of your user data folder will now also be displayed on the Help->About dialog.
- Allowed modifying the options for multiple selected vector layers and the User Created Features layer from the Control Center.
- Added new option to vector KML/KMZ export to allow specifying that the feature description be based on custom HTML text that can include attribute values and other feature information in whatever manner the user deems appropriate.
- Added new option to vector KML/KMZ export to allow specifying the character encoding to specify in the header. This is useful if you are exporting things like UTF-8 text to KML files.
- Added much better looking 24-bit color toolbar buttons (thanks to Bruno Bellazzi for these). You can switch back to using the older higher-contrast toolbar buttons using an option under the View->Toolbars menu.
- Added toolbar button to restore the last drawn view.
- Added new right-click option to the Control Center to allow ordering the loaded layers by resolution or by the bounding box of the layers.
- Added button to copy the contents of the Feature Vertices to the clipboard as text.
- Added reporting of DPI to metadata for (Geo)TIFF files.
- When batch converting from TIFF files to new TIFF or JPG files, maintain the DPI value specified in the original file (if there was one).
- Made GPX exports write out <time> attributes for <wpt> elements if TIMESTAMP, TIME, or UTCDATE and UTCTIME attributes are available for the point being exported.
- Made the preview window on the feature edit dialog for points and the create strike-and-dip dialog display the portion of the map under the point location so that you can see exactly how the symbol will look on the map when you create it.
- Added new option specify that any raster layers should automatically have anti-aliasing (interpolate) enabled when loaded to the Advanced section of the General tab of the Configuration dialog.

- Added support for loading text associated with features from USGS DLG-O files.
- Added support for loading compressed GXF files.
- Made FONT_HEIGHT_METERS attribute actually be used when importing point features.
- Changed FONT_HEIGHT_METERS to FONT_HT_M when writing out style information via attributes so that it would fit inside the 10 character attribute length limit for DBF/Shapefiles.
- Added a new option to the Advanced section on the General tab of the Configuration dialog to specify that lat/lon values in the status should be displayed in WGS84 rather than the current datum selected on the Projection tab of the Configuration dialog.
- Sped up gridding of Lidar LAS files when using the option to remove ground shot points during the gridding operation.
- Allowed use of up to 20 zoom levels (instead of 19) when generating tiles for display in Virtual Earth.
- Fixed problem with specified sample spacing not being maintained when gridding to a fixed width in ground units during export and also applying overlap. This bug was introduced in the v10.02 release.
- Updated custom shader creation to allow initializing values between currently specified min/max values when using the 'Evenly Space Elevations' option rather than just replacing the existing number of values.
- Added support for loading rotated MrSID format files.
- Added support for loading additional MODIS data sets from HDF format files.
- Added support for loading data from netCDF format files with multiple plottable data sets in them.
- Fixed problem with duplicate points being exported to SEGP1 files when points are in both line and point form.
- Updated KMZ vector exports to copy any files referenced by "link" attributes to the output file.
- Added support for loading gzipped text files using the File->Open Generic ASCII Data File menu command.
- Updated 3D path distance reported in path profile to work correctly for multi-segment lines.
- Added support for using styling information from KML/KMZ files that use 'StyleMap' tags.
- Updated the TomTom OV2 export to generate a BMP file with the same name as the OV2 file with the first symbol found in the points being exported.
- Allow creating/flattening terrain from areas with per-vertex elevations rather than just a single elevation attribute.
- When calculating view sheds and using area features as obstructions, added option to control whether or not the top of the area features are allowed to be marked as visible or not.
- Added support for modifying the intervals used for designating minor and major contours during contour generation via registry keys. To change the minor interval, create a DWORD value 'HKEY_CURRENT_USER\Software\GlobalMapper\ContourInterval_Minor' and set it to

the desired multiplier (5 is the default). To change the major interval, create a DWORD value 'HKEY_CURRENT_USER\Software\GlobalMapper\ContourInterval_Major' and set it to the desired multiplier (10 is the default).

- Corrected issues loading BIL/BIP/BSQ images with signed 16-bit samples rather than unsigned 16-bit samples.
- Added support for gridding Terragen exports.
- Fixed problem in v10.02 release with rotated symbols being mirrored in the X direction.
- Reduced default simplification applied during contour generation to improve appearance of contours generated with default settings (at the expense of the default settings now resulting in contours with more vertices).
- Added new options to the right-click menu in the Measure Tool allowing you to set the bearing format to degrees (the previous display format), the two-directional format used in surveying, or mils. In addition you can also choose whether to display bearings relative to True North, Magnetic North, or Grid North.
- Increased precision of decimal bearings displayed when measuring and also provided a registry key to control this at 'HKEY_CURRENT_USER\Software\Global Mapper\BrgPrecision'.
- Fixed problems exporting MapInfo MIF/MID and TAB/MAP files with US Survey Feet coordinates.
- Added a new shortcut key (Ctrl+Shift+L) to copy the cursor location and the elevation at the cursor location to the clipboard.
- Updated elevation legend display when a Slope Shader is used to be restricted to the min/max slope range setup for the Slope Shader.
- Fixed problems with missing time-stamps when tracking some connected NMEA GPS devices.
- Added support for additional colors when export to and importing from DXF files.
- Allow selection of any color for label font display rather than just a pre-selected list of colors.
- Fixed issues with some data not importing from OSGB GML files.
- Added support for loading PNG files embedded in KMZ files.
- Increased precision of elevation values written to Arc ASCII Grid files (now will be up to 3 digits of precision in nearly all cases).
- Changed PNG and BMP world file extensions for screen captures to .pgw and .bpw respectively, rather than .pngw and .bmpw.
- Improved performance exporting from some WMS data sources.
- Allowed GPS-triggered redraw to happen up to 3 times per second rather than just once per second.
- Added support for rods and varas as a unit of measure when using distance/bearing/COGO input.
- Added support for using bearings relative to the current projection/grid system rather than true north when using distance/bearing/COGO input.
- Fixed problems with cropping to rectangles or polygons during draw not working for online sources, like DigitalGlobe, Terraserver-USA, or WMS sources.
- Added support for loading ellipse/circle and rectangle features from EMF files.
- Added support for saving elevation values from multi-point Z Shapefiles.

- Added option to combine all vector layers into a single layer when exporting a Global Mapper Package file.
- Significantly sped up access to the SRTM and NED data sources using the File->Download Online Imagery menu command.
- Updated the Feature Info dialog so that if you double-click on an attribute with a filename as the value, that file will be opened with the associated Windows application.
- Sped up display or rotated or rectified ECW and JPEG2000 files.
- Added support for associating a text or web file to display when loading a workspace with a particular file. This association is set via the right-click menu on the Control Panel.
- Fixed rare positioning problem with some Arc Binary Grid (ADF) files.
- Sped up Global Mapper Grid exports from large collections of files (like map catalogs).
- Added option to batch convert vector files to the InRoads ASCII format.
- Fixed problem exporting areas with duplicate islands/holes when the export boundary passes through one or more duplicate islands/holes.
- Updated KML import to use feature names for type assignment if type assignment based on folder names doesn't find a matching type.
- Added support for specifying the Image ID to use when exporting a Polish MP file.
- Updated Polish MP exports to use 'EndLevel' rather than 'Levels' and [POLYLINE] and [POLYGON] sections rather than [RGN40] and [RGN80].
- Made Polish MP export report any literal types that are exported which may cause problems in cGPSMapper.
- Added area and line vertex count to metadata for layers.
- Added support for gpxx:Depth and gpxx:Temperature attributes when importing GPX files.
- Significantly sped up exports to extremely large ECW (multi-GB) files that had previously slowed to a crawl in some cases.
- Updated behavior of path profile generation along multi-segment paths to not always stop at vertices when generating a path with a user-specified fixed interval. Now that interval will be obeyed so the user will get the exact spacing that they requested.
- Added option to generate 24-bit PNG files when exporting to WorldWind tiles.
- Made fat road line styles and zoom-level based type filtering work properly when exporting to formats with multiple zoom resolutions, like Google Maps.
- Made the Add New Attribute option when editing one or more features remember the last added attribute to simplify adding the same attribute to lots of features.
- Added display of bounding box for area and line features to the Geometry section of the Feature Info dialog for those features when selected.
- When adding a new WMS data source, if an existing WMS data source is selected initialize the server URL to that of the selected WMS source.
- Updated CSV export to include all available attributes, even if the values for all of them are empty.
- Added support for Yards as a unit for specifying the radius of range rings.
- Corrected problem with the default font being written to style files saved from the * Styles tabs of the Configuration dialog rather than the font assigned to a type.
- Updated the Path Profile/Line of Sight tool to draw using the 'Measurement' line style, so you can now customize the appearance of that line.

- Added support for loading data that is in .zip files contained within .zip files, like the new Tiger 2008 data is typically distributed.
- When measuring cut-and-fill volume from the Path Profile or Digitizer Tools, initialize the cut elevation for each vertex to that of the input path if possible.
- Added ability to save your 3D cut line to a CSV file on the Volume Calculation dialog.
- When splitting Shapefiles by layer on export, use the type name rather than the description string for anything other than unknown types.
- Corrected positioning of some OSGB TIFF tiles.
- Added support for loading arc (BUE and BUEP) features from SOSI format files.
- Fixed problem loading area features with holes from SOSI format files.
- Added Location button to Feature Info dialog displayed for point features allowing display and editing of point feature location from there.
- Renamed Virtual Earth export to Bing Maps to reflect new naming by Microsoft.
- Added support for positioning raster files with SOSI .sos files.
- Updated saving of Surfer CLR shader files to allow saving the actual elevation values rather than the standard elevation percentage values that Surfer uses. This makes it easier to save and restore shader settings within Global Mapper.
- Reduced size of built-in bullseye symbol to make it less obtrusive.
- Added option to use space separator rather than comma when batch converting to Simple ASCII Text and XYZ grid files.
- When using the File->Rectify Imagery menu command, make the export option be unchecked by default.
- When exporting to a raster (image) format, check the 'Save Vector Data if Displayed' option by default if any vector data is loaded.
- Made SEGP1 import just ask the user to confirm the datum as the projection is already known.
- Corrected application of color intensity when feather blending.
- Improved bearing calculations in Global Mapper to use the Vincenty formula.
- Made attribute values with multiple leading zeroes be treated as text fields rather than numeric when exported to DBF/Shapefiles.
- Made Global Mapper Package exports maintain the names for palette entries if they exist.
- Fixed problem with slow terrain draws from the last release.
- Added progress reporting when loading an archive (.zip or .tar.gz) file with multiple files to load inside it.
- Fixed bug with changes on the Palette tab of the Options tab for TIFF files not being applied to overview layers (i.e. it only worked when zoomed in on the layer).
- Dramatically improved performance of exports from large numbers of MrSID files.
- Updated GeoTIFF exports to write out the ellipsoid parameters.
- Updated TIN generation when flattening areas to automatically delete any triangles outside the area feature(s) being flattened.
- Reversed the order of colors in the HSV shader.
- Made CSV exports include non-default symbol names as well as an IMAGE_LINK attribute for EXIF point features.
- Added support for additional HDF-formatted data sets.
- When loading .gm_style files via the * Styles tabs of the Configuration dialog, prompt

the user to add any types that aren't found on the system.
- Added support for controlling the accuracy and collection system values stored in exported DTED files through the 'HKEY_CURRENT_USER\Software\Global Mapper\DTEDAccuracy' and 'HKEY_CURRENT_USER\Software\Global Mapper\DTEDCollectionSystem' string registry keys.
- Added new option on the Vector Display tab of the Configuration dialog to disable the automatic add of measurement attributes to newly created area and line features.
- Added new option on the Vector Display tab of the Configuration dialog to treat duplicate vertices in area borders as 'Pen Up' or 'Pen Down' commands, thus allowing for having some segments of an area border be not drawn.
- Made export of generated TIN polygons to DXF files generated 3D face features rather than 3D polylines.

WHAT'S NEW IN Global Mapper v10.02

- **Significant New Features**
  - Added ability to easily create strike-and-dip points by right-clicking in the Digitizer Tool. You can now place your strike-and-dip points and specify the dip value, azimuth angle, and symbol to use and get the appropriate symbology displayed on the map.
  - Added support for adding custom area fill styles from image files. New fill styles can be added on the Area Styles tab of the Configuration dialog.
  - Added support for rotating point symbols by a user-specified angle. This option is on the Point Styles tab of the Configuration dialog as well as on the edit dialogs for point features.
  - Added option to the Digitizer Tool to calculate the minimum, maximum, and average elevation values within selected area features.
  - Added support for specifying that lines should draw a particular number of meters in width. Line width selections on the Line Styles tab of the Configuration dialog and anywhere else that you setup a line drawing style now include an option to specify a fixed width in meters for the line.
  - Added new input option to distance/bearing/COGO input for lines to allow one-handed-input using the number pad with either quadrant/bearing/distance input or distance/bearing input. Also added support for entering DM or DMS bearings as decimal values, like 40.3020 for 40 degrees, 30 minutes, and 20 seconds.
  - Added new right-click options to the Area Styles, Line Styles, and Point Styles tabs of the Configuration dialog to allow saving the current style settings to a file and restoring style settings from a file.
  - Added new ASSIGN_TYPE command to the scripting language to allow classifying loaded vector features based on one or more attribute/display label value queries.
  - Added support for loading SOSI format files (commonly used in Norway).
  - Added ability to easily shift loaded data by some fixed distance by right clicking on them in the Control Center and selecting a new option to shift the selected layer(s).

- Made batch conversion remember the last used import and export formats as well as the last used settings for a previously used import/export format combination.
- Made GPX files with links pointing to local image files behave just like JPG files with EXIF positioning data and show the image when you click on the point with the Feature Info tool. The linked images will also export to KMZ files.
- Added new Slope Direction shader to allow coloring loaded terrain files by the direction that the slope faces (the coloring can be setup on the Shader Options tab of the Configuration dialog). You can also now export slope direction values to Float/Grid files.
- Added option to batch converter to add a watermark image.
- Added new option to only display area labels when the label is completely contained within the parent area to the Vector Display tab of the Configuration dialog.
- Made the option to display selected feature measurements (including combined values) in the Digitizer/Edit Tool work even if only line features are selected.
- Added ability to display any custom "elevation" units string that you want on the elevation legend by right-clicking on the legend and selecting the option to specify a custom unit string.
- Added support for exporting to DeLorme track and waypoint formats.
- Added support for exporting loaded area and line features to ZMap+ XYSegId text files.
- Added option when generating Global Mapper Package files to store each layer in its native projection rather than in the current view projection or in lat/lon/WGS84.
- Added new option to the Vector Display tab of the Configuration dialog to always show vertices for features selected with the Digitizer/Edit Tool. This makes it easier to edit the vertices of area and line features without being overwhelmed by displaying all feature vertices.
- Allowed rasterization of vector data to any size to exported image file (previously you were limited by the largest bitmap that could be allocated on your system).

- **Projection/Datum-Related Additions and Changes**
  - Added built-in support for the Wisconsin County coordinate systems.
  - Added built-in support for Deir Ez Sor, Egypt Gulf of Suez S-650 TL, Estonia 1997, FD 1958, Herat North, ISN93, Jordan, Korean 1985, Korean 1995, Ocotepeque (Costa Rica), Reykjavik 1900, and Trinidad 1903 datums.
  - Added built-in support for the Clarke 1858, Danish 1876 and Clarke 1880 (IGN) ellipsoids.
  - Added built-in support for linear units of Clarke Feet.
  - Added EPSG codes for KGD (Korean Geodetic Datum) and Mercator projection used in Google Maps and Virtual Earth (code 3785).
  - Fixed problem with Dutch (RD) datum transformations in the v10.01 release.
  - Added support for decoding Bonne projections from OziExplorer .map files.
  - Added support for decoding projection names from ECW files stored as EPSG:<epsg_code> in the projection name and also encode unknown projections that way in exported ECW files.

    - Improved accuracy of KKJ datum conversions and added KKJ projection EPSG codes.
- Added option to Path Profile/Line of Sight dialog when matching the elevation scale to the draw scale to allow users to enter a vertical exaggeration to apply.
- Added new batch conversion option to skip existing output files.
- Added new batch conversion option to disable anti-aliasing (interpolation) in all cases, even when it is automatically applied for reprojection or resampling.
- Added new batch conversion option to minimize the main window while the conversion is running.
- Updated batch conversion to not report any errors in the conversion until all conversions have been completed. This prevents a batch conversion operation from stalling in the middle waiting for a user to clear an error message.
- Updated the set position dialog to have an elevation field when editing the location of a single vertex from a 3D line or area feature using the Digitizer Tool.
- Added options when gridding exports to break each row (or column if naming is reversed) into its own folder as well as an option to not place an underscore between each piece of the export filename.
- Improved decoding of waypoints from GPS TrackMaker .gtm files. An appropriate symbol should now be assigned if possible and the correct naming is now used.
- Don't use EXIF information from JPG files if you open the files with the File->Rectify Imagery menu command to force rectification.
- Fixed crash when loading Terrascan .bin files from v10.01 release.
- Added new Ctrl+Shift+D shortcut key to toggle the display of deleted features.
- Allow initialization of custom shaders from other custom shaders in addition to the Global Shader and also added option to re-base and offset the elevation values used in a shader.
- Fixed problems with labels for very short lines not showing when zoomed way out on them.
- Reduced memory requirements for loading Helava DEM format files.
- Fixed color problems with CMYK-encoded JPG files from Adobe Photoshop.
- Fixed problem generating iso-height contour areas in some rare situations.
- Added a new option when batch converting to Float/Grid format files to export slope values rather than elevations.
- Updated the DXF export to use the Elevation Display/Export Units setting on the Vertical Options tab of the Configuration dialog to determine whether to export feet or meters for elevation values derived from loaded terrain data during export.
- Updated Google Maps exports to use a separate folder for each row in a particular zoom level to avoid overloading a single Windows folder with more files than it can efficiently handle.
- Fixed problem with incorrect slope values of 0 being written out to Float/Grid format files in some cases.
- Fixed bug with slope values written out to Float/Grid files being slightly smaller than they should be, especially in very steep areas.
- Fixed problem with KML_ZOOM_SCALE_FACTOR script parameter not working.
- Added support for overriding the default naming convention for Lidar class names using

a lidar_classes.txt file enumerating Lidar classes and the new name to use for those classifications.
- Fixed problems with some features being missing when loading some ESRI personal geodatabase (.mdb) files, like those from the NHD.
- Updated KML import to support color specified for icons.
- When batch converting files that are loaded in the main map view with contrast adjustment enabled, use the contrast adjustment settings of the loaded files during the conversion.
- Added support for loading clutter and height files similar to MSI Planet but with .cl or .he extensions and a List file rather than a Index file.
- Added new option to Google Maps and Virtual Earth exports to allow skipping existing tiles. This provides a mechanism for restarting cancelled exports or just updating part of a data set.
- Improved compression ratio achieved in LZW-compressed GeoTIFF files.
- Fixed problem exporting Shapefiles split by layer/description when the layer/description includes special characters like '<' or '>'.
- Allow the Control Center dialog to be resized to be more narrow.
- Added option when batch converting from USGS DRG files with accompanying FGD metadata files to use the quad name from the FGD filename as the output filename.
- Drastically sped up the loading of Canada3D files.
- Updated distance/bearing input dialog to allow bearings to be specified with formats other than decimal degrees (like DMS, DM, etc.).
- Added new option to the Options menu on the Path Profile/LOS dialog to allow modifying the start distance for the distance scale in the path profile graph.
- When gridding during export and using a letter to name rows and/or columns, keep the letter as lower case if it was originally specified that way.
- Fixed problem with default line simplification not being applied during contour generation unless you actually click on the Simplification tab.
- When gridding to selected area features, allow the overlap setting to be applied if you are just cropping to the bounds of each area feature.
- Corrected half-pixel shift in the placement of loaded GXF files.
- Fixed problem reading palette color labels with spaces in them from .pal files.
- Made the shot point number field in exported SEG-P1 files be right-justified.
- Increased the number of recently opened files that are remembered on the File menu from 4 to 6.
- Made the Search->Search by Attributes dialog always display the current number of selected items.
- Added option to feather blend to the outside of a polygonal boundary rather than to the inside.
- Added option to generate ERS files when doing elevation-format BIL exports.
- Allowed cropping a raster layer to multiple selected polygons when using the Cropping tab on the options dialog for the layer.
- Fixed error reading some MapInfo MIF/MID format files.
- Added support for .jgwx as a JPG world file extension.
- Made the dialog displayed when editing multiple features at the same time be resizable.

- Updated the create/flatten terrain from areas option of the Digitizer Tool when treating the area elevations as relative to the ground perform the relative adjustment of the terrain at each sample location within the area rather than picking a single representative elevation for the entire area. This is useful for adjust all elevation values within an area feature by some amount.
- When loading files that have contrast adjustment automatically applied, make them use a shared contrast adjustment by default. This makes loading multiple high color (i.e. 16-bit per color channel) files adjust them consistently automatically rather than doing a separate adjustment for each image.
- Added new right-click option to the Control Center to allow easily setting the current view/export projection to the native projection of the layer that is right-clicked on.
- Corrected placement of text points from DGN v8 files.
- Added support for rotated text from DGN v8 files.
- Added GPS toolbar with buttons for marking waypoints and showing GPS information.
- Fixed problem with the placement of area centroids/labels for fully closed areas.
- Added support for loading GeoTIFF files with a *.gtif extension.

WHAT'S NEW IN Global Mapper v10.01

- Added support for loading JPG files with embedded EXIF GPS position data. These files will be loaded as point features with picture icons. When you select one of these with the Feature Info Tool, the JPG image will be displayed.
- Added support for tracking and managing multiple GPS devices via an input GPS data stream including $PRAVE sentences. With a compatible receiver, you can now use Global Mapper for fleet management. There is a new Manage GPS Devices option under the GPS menu that provides extensive functionality for managing the collection of GPS devices being tracked.
- Added new Color Grade tab to raster options dialog to allow complex manipulation of color channel values and saturation for loaded raster files. This allows 'grading' each color channel from a specified input range for a color channel to a specified output range.
- Added support for exporting loaded data to NITF format files.
- Added support for exporting an alpha channel to ECW and JPG2000 format files, thus allowing creating of files in those formats with transparency built-in.
- Added button to the toolbar for the Search->Search by Attributes menu command.
- Added option to add X and Y coordinate attributes to selected point features via the right-click menu in the Digitizer Tool.
- Added new option to the distance/bearing/COGO input to close a path using the 'compass rule' and to edit the start location.
- Added ability to right click on a point in the Search by Attributes dialog and start a new distance/bearing/COGO line from that point.
- Added new batch conversion option to "Make a Single Color Transparent". This will allow you to choose a color to make transparent when batch converting raster format files.
- Added support for loading PDS/Vicar format data, which is commonly used by NASA for planetary data sets.

- Added new item to the right-click menu in the Digitizer Tool when area features are selected to populate the attributes of those areas from the attribute tables of a single point contained within those area features.
- Added new Advanced Creation Options sub-menu to the right-click menu in the Digitizer Tool when area and/or line features are selected. This menu now contains the options to create lines from area, create areas from lines, create terrain from areas, as well as a couple of new options (see below).
- Added option to the Advanced Creation Options menu of the Digitizer Tool to create new point features at the centroid of selected area features.
- Added option to the Advanced Creation Options menu of the Digitizer Tool to create new point features from the vertices of selected area and line features.
- Added new options to the right-click menu option of the Digitizer Tool for creating rectangular/square area and line features by manually entering the rectangle coordinates.
- Added new built-in point types for LIDAR point types to make it easier to filter out different LIDAR points loaded from LAS and Terrascan LIDAR files.
- Sped up export to GeoTIFF files when a large number of input files are being exported.
- Added support for adding multiple custom symbols at once when adding custom symbols on the Point Styles tab of the Configuration dialog.
- Added automatic positioning of OSGB 10K grid cells in TIFF format.
- Improved generation of image-optimized palettes in cases where over 16.7 million pixels with the same color are involved in the export.
- Added ability to select which layers to load from an ESRI personal geodatabase (MDB) file.
- Added new palette option during batch conversion to use the same settings as the source file. This allows you to convert a mixture of RGB and palette-based files and maintain their original settings.
- Added built-in support for the Double Stereographic and System 1965 (Uklad 1965) projection systems.
- Added built-in support for IRENET95, Malongo 1987, PRS92 (Philippines Reference System 1992), and SWEREF99 datums and associated EPSG projection codes.
- Added new EPSG codes for Swedish Grid (3021 and 2400).
- Added built-in datums for each of the custom Minnesota county ellipsoids as well as for Sheboygan County, Wisconsin.
- Added more accurate 7-parameter datum transformations for Kertau 1948 and Timbalai datums.
- Allowed use of linear units other than meters (i.e. feet) for New Zealand projections.
- Corrected definition of Guam State Plane zone.
- Added option when shifting selected features with the Digitizer Tool and selected control points when rectifying imagery to shift based on a distance and bearing as well as fixed X and Y offset distances.
- Added Speed and Bearing display for each leg in the Feature Vertices dialog when a time-stamp is present for each vertex (i.e. such as GPS tracklogs).
- Added support for getting positioning information for raster files (like JPG, etc) from a greater variety of KML files.
- Sped up display of dense point data sets with labels. This was slower in v10 due to new

automatic label placement feature.
- Added new right-click option to the Search by Attributes dialog to allow zooming to the selected feature(s).
- Increased the size of the displayed elevation and lat/lon position on the GPS Information dialog.
- No longer generate transparent PNG or TIFF files for KML raster exports using the super overlay feature if vector data is being exported. This is to prevent problems with the multiple layers of images showing through in Google Earth when zoom in on transparent areas which are prevalent in vector exports.
- Made filename parameters for script commands referencing loaded files (like COMBINE_TERRAIN, UNLOAD_LAYER, etc.) also match against the description of loaded layers in case no matching filenames are found. This allows matching against created layers that are not backed by a filename, like the results of a previous COMBINE_TERRAIN or GENERATE_CONTOURS command.
- Allowed use of PROJ_EPSG_CODE parameter with LOAD_PROJECTION script command.
- Fixed problem decoding projections from MapInfo files with units other than meters and specified false easting/northing values.
- Added option to view shed generation to specify a receiver height above the terrain surface to check for visibility at when use a beam with restricted transmission angles.
- Improved export of 3D line and area features to PLS-CADD XYZ files.
- Update PLS-CADD export to write out a sequential ID number in the first field for point features with no POINT_DESC attribute value.
- Fixed problem loading some WMS data sets.
- Added new option to the Global Mapper Package export dialog to specify that the full style for all features should always be saved to the generated file, even if a feature is using the default style for a type. This makes it easier to save data sets with the same styling for sharing between users.
- Made Feature Edit dialog resizable.
- Made types that are disabled in the type filter on the Vector Display tab of the Configuration dialog not show up in the Feature Edit dialog.
- Updated raster/elevation export plugin architecture to add a new flag (EP_Flags_ElevAndColor) that allows an elevation format to also have the color callback function called for each exported sample for formats that store both elevation and color information.
- Added display of current data download speed to export progress dialogs that are exporting data coming from online sources, like WMS or DigitalGlobe imagery.
- Fixed bug in v10.00 that prevented export to some formats from a script file.
- Fixed bug with incorrect Z value being written out to new 3D DGN files for 3D points that have no display label.
- Added new File menu command to the Path Profile/LOS dialog to allow saving the path profile results to a CSV file with X, Y, elevation, and distance (both segment and cumulative) values.
- Added support for loading JPEG2000 files from associated .TAB files.
- Added display of target compression ratio to metadata display for ECW and JP2 format

images.

- Added support for tracking NMEA GPS devices that use $IN* sentences rather than $GP* sentences.
- Corrected zone number used for GeoTIFF files for the Mississippi West State Plane zone.
- Greatly sped up export to large ECW files from map catalogs.
- Updated date fields imported from DBF files to use 4 digit years.
- Updated Lidar LAS export from vector data to use feet for the elevation units if the 'Elevation Display/Export Units' setting on the Vertical Options tab of the Configuration dialog is set to 'Statute (ft)'.
- Fixed problem batch-converting to GeoTIFF files using a min-is-black or min-is-white palette.
- Added options to Erdas Imagine export to control the block size, whether or not compression is used, and whether or not to add overview (pyramid) layers.
- Added progress bar for lengthy area volume calculations.
- Made Surfer BLN files be automatically detected and imported with no user intervention.
- Made Delft 3D .ldb files be automatically detected and imported with no user intervention.
- Added support for reading place point features from OpenStreetMap (OSM) files.
- Fixed problem with attribute display in Search by Attributes dialog when loading new files with the dialog open.
- Added new line drawing style, "Solid with Black Edges".
- Fixed bug in v10.00 which caused vector features to not be selectable if any fixed screen position layers that are set to always draw on top are loaded.
- Modified the bearing display in Global Mapper to be based on the Position Display Format selection on the General tab of the Configuration dialog. So if you have that set to DMS, your bearings should show up that way as well.
- Added support for MPR/MPH files larger than 2GB.
- Reduce memory requirements for loading large ENVI DEM format files.
- Fixed problem in v10.00 release with users being prompted to confirm projection for NAD83-based projections from old-style PRJ files or prj.adf files.
- Added support for loading truncated Lidar LAS files.
- Added support for loading very large 16-bit BMP files.
- Corrected color display in the status bar as you move the cursor around the map over loaded TIFF files.
- Added support for user-specified tile size when generating KML super overlays.
- Made the last palette selection be remembered for batch conversions.
- Added support for additional flavors of MODIS data in HDF format, like the SST (sea surface temperature) data.
- Fixed problem with some new line styles from v10.00 not drawing properly when used as area borders.
- Corrected rotation of text labels from some DXF files.
- Fixed problem with multiple consecutive spaces being reduced to a single space when reading in attributes from ASCII text files.
- Made the text '\n' be interpreted as a newline character in attribute values read from ASCII text files.

- Added LEVEL_DESC attribute to features imported from DGN v8 and later files if the file contains a text description for the level of the feature.
- Fixed problem with translucency setting not always working with TIFF files in map catalogs.
- Added ability to use custom palettes when exporting GeoTIFF, PNG, or Erdas Imagine files from scripts by providing the palette filename as the value of the PALETTE parameter, like PALETTE="C:\my_palette.pal".
- Greatly sped up the addition of JPG files to map catalogs.
- Made NAME and LABEL fields be preferred for labeling over fields that just start with NAME or LABEL when loading Shapefiles.
- Added support for addition font style information from attributes using FONT_STYLE, FONT_WEIGHT, and FONT_PLACEMENT attributes.
- Changed name of automatic MODIFIED_DATE attribute to MOD_DATE to avoid attribute name length issues with Shapefiles.
- Fixed problem when geo-coding to loaded data from a file that contains the address number and street name in the same field.

WHAT'S NEW IN Global Mapper v10.00

- **Significant New Features**
  - Added support for importing ESRI personal geodatabase (MDB) files.
  - Added support for importing and exporting BigTIFF files, which allows working with (Geo)TIFF files larger than 4GB.
  - Added support for generating super overlays in raster KML/KMZ exports to allow for the viewing of massive quantities of data in Google Earth. The existing option to automatically grid data on the KML/KMZ raster export options dialog enables this behavior.
  - Added support for selecting/changing the layer that features are in when editing existing features and creating new ones with the Digitizer Tool.
  - Added ability to generate raster KML/KMZ files using the EXPORT_RASTER script command.
  - Added new Coordinate Convertor option under the Tools menu to allow easily converting a coordinate between any two supported projections/datums/units.
  - Added ability to Search Vector Data dialog to limit your search to the existing search results. This effectively allows you to query on multiple attributes/values.
  - Added support for creating new feature coordinates based on distance/bearing and/or COGO values from a start location using the Digitizer Tool.
  - Added more control over placement of labels for point features. Now when choosing the font to use for point features, you can also choose where to place the label for the point relative to the point location. An automatic setting will try different locations to try and make the label fit.
  - Added a large collection of new available line styles to use when rendering line features or area feature borders.
  - Added option to crop a loaded raster layer to the currently selected area feature to the Cropping tab of the Raster Options dialog accessible from the Overlay Control

Center.

- Added support for exporting loaded vector data to the MapInfo TAB/MAP format.
- Added support for exporting loaded 3D line and point data to the SEGP1 format.
- Added support for exporting loaded area features to the DeLorme Polygon Text format that some DeLorme products can import.
- Added support for loading IKT track files generated by MagicMaps software.
- Added support for loading Gravsoft Grid format files.
- Added option on the Gridding tab for exports to grid to the currently selected area features. This will create a separate export file for each selected area feature. Naming can be done using the display labels or an attribute of the selected area feature(s).
- Added support for generating 3D DXF and Shapefiles (including using any loaded elevation data as a source) when batch converting to those formats.
- Made automatic collar cropping work for BSB charts.
- Added arrow buttons to the Overlay Control Center to make it easier to change the overlay draw order.
- Added support for loading files from web URLs using the IMPORT command in a script file. Just pass the URL with the FILENAME parameter.
- Alphabetized the area, line, and point type lists on the * Styles tabs of the Configuration dialog and on the vector type options dialog.
- Added new 'Pseudo Natural Color' blend mode to combine the color channels in a layer using a common algorithm for generating natural color imagery from CIR imagery.
- Added option to the Digitizer Tool to select multiple area features and right click and display measure information about each feature and the combination of features on a dialog.
- Added options when editing multiple features to rename attributes and also to copy the values of one attribute to a different attribute.
- Added new option when combining terrains to filter one terrain layer based on another by keeping the values in one terrain layer only when the other terrain layer also has a valid value.
- Added options to the View menu to save the current view with a name and then restore named views from a list of the saved views with names.
- Added option to the View menu to restore the last drawn view. This allows you to back up through up to the last 20 drawn views.
- Added option to the View menu to zoom the view to a particular sample spacing (pixel size).
- Added support for extracting positioning information for image files from KML files. This allows you to load KMZ files that contain embedded raster images.
- Added option when creating an elevation grid when loading Lidar data formats (like LAS and Terrascan files) for the user to specify options such as the grid tightness, whether or not to fill to the entire bounds of the data, and whether or not to only consider ground-shot points in the gridding process.
- Added new option to initialize custom elevation shaders from a palette file.

- Made the distance scale displayed on the main map view and on the path profile dialog use the currently selected distance measure units. This allows display of nautical and other units on the scale.
- Added option for fixed screen layers to force them to always be drawn on top of other layers (including grid lines and user created features) regardless of the layer order in the Control Center. This is useful for forcing things like legends to always be display on top of other data.
- Added new option when pasting features from the clipboard to not clear the clipboard after pasting the features (shortcut key is Ctrl+Shift+V).
- Added option when printing to select the area to print rather than just always using what is on screen.
- Significantly improved the speed and reliability of accessing the Landsat7 Global Imagery Mosaic data layer through the File->Download Online Imagery menu command.
- Added built-in access to several new aviation chart (GNC, ONC, TPC, and JNC) layers through the File->Download Online Imagery menu command.
- Made rotated line labels be exported to DXF files when exporting line labels to DXF files 'Include Display Labels as Separate Text Layer' option.
- Added new option to the Font selection dialog to control the label fill background mode. Now you can force the background to be transparent, which allows labels centered on line features to be drawn with no filler behind them if you want.

- **Projection/Datum Changes**
  - Added built-in support for the MSTM (Mississippi Transverse Mercator) and New Brunswick Double Stereographic projections as well as a configurable RSO (Rectified Skew Orthomorphic) projection.
  - Added built-in support for the ED87, JAD69 (Jamaica 1969) and JAD2001 (Jamaica 2001) datums.
  - Improved accuracy of datum conversions involving the Tananarive datum by using improved conversion parameters from IGN.
  - Fixed accuracy problem with ED50 (Spain and Portugal) and OSGB36 datum conversions very close to and just east of the prime meridian.
  - Improved accuracy of datum conversions involving the Bogota Observatory (Bogota 1975) datum.
  - Allow the Azimuthal Equidistant projection to cover the entire world rather than just half the world around the projection center.
  - Added support for users to add their own EPSG codes definitions or modify the existing ones by modifying the epsg_codes.txt file in the Global Mapper installation folder.
  - Added recognition of additional EPSG codes for projections (like MGI/Balkans).
  - Updated EPSG projection definitions for State Plane Illinois zones (FIPS 1201 and 1202). New codes 3435 and 3436 are for these zones using feet units and existing codes 26971 and 26972 now use meters as units.
  - Added support for two extra false easting/northing attributes to the State Plane projection system to support users that use a State Plane projection system with an extra scale factor (such as for ground vs. grid coordinates) and then apply an XY

offset to the coordinates after that.
    - Added zones 6-9 for Gauss Krueger Germany (3-degree zones) projection.
    - Added additional S-42 (Pulkovo 1942) datum specializations and made the base S-42 (Pulkovo 1942) datum automatically select an appropriate specialization to use.
- Added support for easy creation of multi-line text for area and point features by adding the text '\n' to display labels for points when creating/editing them with the Digitizer Tool.
- Allowed the label for area features to be rotated.
- Automatically combine address ranges for Tiger 2007 line segments that have multiple address ranges to make address searching more effective.
- Added support for additional MTFCC (feature type) codes from Tiger 2007 data so that features like state and county boundaries can be automatically classified on import.
- Added new selection mode to the Digitizer Tool. If you hold down the 'I' key when dragging a box, only features that are completely contained within the box will be selected. This is useful for things like selecting a point feature on top of a line or area feature.
- Corrected ERS header export to be correct when exporting BIL files or files with export units of arc degrees.
- Fixed bug when exporting raster KML/KMZ files to a filename with a special character not allowed in XML files, like an ampersand.
- Fixed problem with per-vertex time-stamp values being lost in some cases when graphically moving or deleting vertices with the Digitizer Tool.
- Added new built-in point type 'Address Label'. You can disable this type to turn off the center address labels automatically applied to downloaded online sources, like TerraServer-USA and DigitalGlobe.
- Added new built-in area type 'County Subdivision'.
- Added option to maintain the map location under the cursor position when using the mouse wheel to zoom. You can do this either by checking the option on the Advanced list on the General tab of the Configuration dialog or holding down the Ctrl key when scrolling the mouse wheel.
- Added new options to Google Maps export to allow easily adding additional controls to the map displayed by the default HTML file that is generated, such as a map type selected. Also made double-click zooming be enabled by default.
- Added transparency slider to the Google Maps and Virtual Earth export dialogs to allow setting the default transparency level for the exported maps.
- When importing generic ASCII text files, make the default attribute list for the type being assigned to a feature automatically be applied to the attribute list for that feature.
- Added automatic type and style assignment from attribute values when loading DBF point files.
- Updated the 'Find by Name' dialog to allow recentering on a feature without showing the bullseye icon if you hold down the ALT key when double-clicking on an item.
- Added new Ctrl+Alt+L shortcut key for automatically copying the current point/cursor coordinates to the clipboard in the current selected projection with a tab separated the X and Y coordinate values.

- Corrected placement of ECW/JPEG2000 files that use a projection code of TMNEWYEM. They were previously very slightly shifted.
- Made the COMBINE_TERRAIN script command by default use the intersection of the bounding box of the two layers being combined rather than the union of the layer bounding boxes.
- Fixed problem with elevations sometimes not being saved when recording a tracklog for a connected GPS device.
- Made saved CSV export options be remembered during a run of Global Mapper.
- Fixed problems loading LAS, Terrascan, and DMDF files from workspace files.
- Added support for loading latest GNIS (USGS Geographic Names) database from http://geonames.usgs.gov/domestic/download_data.htm.
- Added option when capturing the screen contents to an image to save a text file containing metadata about the file, like the bounds, pixel size, etc.
- Increased precision of lat/lon coordinates displayed on the status bar.
- Improved automatic detection of alpha channels and non-standard color channels when loading ECW and JPEG2000 (JP2) format files.
- Changed font used for elevation legend and distance scale display text so that it can display correctly on all systems, regardless of language.
- Fixed problems loading 24-bit RGB MPR/MPH files.
- Fixed error when trying to load DBF files greater than 2GB in size.
- Made gridded elevation grid generation from loaded vector data automatically overlap the edges during generation to generate a smooth, non-overlapped output.
- Fixed problem when gridding elevation grid generation and manually specifying the sample spacing to use.
- Fixed problem loading SID files with corrupt world files accompanying them.
- Fixed problem with features being exported to the non-populated upper layer(s) of MP files in some cases.
- Made files loaded at a fixed screen position be maintained as fixed screen location files when saved to Global Mapper Package (GMP) files.
- When loading generic ASCII text/CSV files, keep a name/label column as both an attribute value and the display label if multiple attributes exist to allow easily changing what attribute(s) to display as the label.
- When exporting to the Arc Ungenerate formats, write out coordinates in the projection selected on the Projection tab of the Configuration dialog rather than just lat/lon values.
- Added automatic detection of grid cell registration type (i.e. pixel-is-point or pixel-is-area) for netCDF grids like those created using GMT.
- When generating Simple ASCII Text files from a script using the EXPORT_VECTOR command, allow specification of attribute export except for style attributes by using the parameter EXPORT_ATTRS=NO_STYLE.
- When importing files from a script/workspace, warn the user if a file does not exist.
- Improved detection of invalid (void) values for elevation GeoTIFF files that use very large negative numbers for invalid values and the files do not contain any valid data.
- Added support for loading palettes from Idrisi SMP files.
- Added option to make background pixels transparent when batch converting to raster KMZ files.

- Added option to generate 8-bit palette-based PNG files when batch converting to raster KMZ files.
- Added automatic detection and correction of incorrect State Plane zone encodings in some .aux files, such as those produced by a New York imagery site.
- Fixed problem reading the timestamp for tracklog points from GPX files that are on the 31st day of a month.
- Fixed problem with TriangulationLib.dll files sometimes not being installed by auto-downloading them if needed.
- Fixed rare error loading some DNC data sets.
- When importing ASCII data files, automatically detect lines with a series of 999.0 values and allow the user to treat these as feature separator lines rather than coordinates.
- Sped up import of GML files, particularly when importing lines or areas with a lot of vertices.
- Drastically improved speed when displaying some NAIP 2008 JPEG2000 imagery.
- Added support for using TFWX files as world files for TIFF files.
- Added display of the number of grid cells being exported when doing a gridded raster or elevation export.
- Added display of the area covered by the screen to the View->Properties dialog.
- Fixed crash when doing more than one export to a web-based format (like Virtual Earth, Google Maps, etc.) from a single Global Mapper session.
- Fixed HTML file created for Virtual Earth export when using the JPG format.
- Added option to Download Online Imagery menu command to delete the caches for the various sources.
- Added Alt+R as a shortcut key to save the current view.
- Improved decoding of block labels and attributes from some DXF files.
- Added support for 2 additional resolution level exports for Google Maps exports, allowing up to 2 cm resolution imagery to be accurately represented.
- Allowed for the specification of negative grid cell width and/or height values when exporting and using the Gridding tab. When a negative value is specified the grid cells will be snapped to the right and/or bottom of the export bounds rather than the left and/or top as is normal.
- When assigning areas to be islands in other areas with the Digitizer Tool, allow the user to add areas as islands even if they are not completely contained within the topmost area at the clicked location.
- Changed the cursor used when selecting features with the Digitizer Tool to a crosshair from a pointer.
- Added new Ctrl+Shift+M shortcut key to the Digitizer Tool to activate move mode.
- Allow 2 line features that do not share a common endpoint to be combined by automatically adding a line segment connecting the 2 closest ends of the line when using the Combine Selected Line Features command in the Digitizer Tool.
- Added display of some projection information on the Metadata tab of the metadata dialog for layers and also in the output of the EXPORT_METADATA script command.
- Added option to the batch conversion dialog when converting raster files to disable the automatic use of contrast adjustment. This is useful when you have files with more than 8 bits per color channel that look better with no contrast adjustment applied.

- Added new PROMPT_IF_TYPE_UNKNOWN parameter for the IMPORT script command to allow disabling the type prompt when importing files for which the type could not automatically be determined.
- Added new option to the NASA World Wind export to allow manual specification of the level 0 tile size to use.
- Allowed use of the Delete key to delete ground control points from the rectification dialog.
- Fixed problem loading some MapTech BSB charts with unusual projections (like Polyconic).
- Fixed problem with image rectification that would occasionally cause polynomial rectification to be used instead of triangulated even if triangulated (piecewise-affine) should have been used.
- Corrected half-pixel shift when loading SRTM30 and SRTM30+ files.
- Added Ctrl+S as a shortcut key to the image rectifier dialog to save the GCP list to a file.
- When loading a GCP file in the image rectifier dialog, prompt the user to remove all of the current control points if there are any.
- Added option to the advanced section of the General tab of the Configuration dialog to specify that when cropping to an area feature on export that any cell that has any part in the crop area should be kept rather than just those for which the center of the cell is inside the crop area.
- When cropping to selected area features during batch conversion, prompt the user to see whether they want the export files to have the bounds of the file being converted or the selected area features.
- Made the screen capture dialog remember the last format used and select it by default within a single run of Global Mapper.
- Improved display of some BSB charts that cross the anti-meridian.
- Fixed error loading some NITF imagery data sets that use JPG2000 compression.
- Improved positioning of NITF imagery that uses RPC (polynomial-based) positioning.
- Prompt the user to specify whether 16-bit JPEG2000 and ECW files are elevation or imagery files rather than just assuming they are elevation.
- Fixed problem with view background color not being in generated image optimized palettes in all cases.
- Made script exports automatically create the destination directory for the new file being created if it doesn't already exist.
- Added new GRID_NAMING_PREPEND_ZEROES parameter to the script export commands to allow controlling whether or not zeroes are prepended to named grid tiles during export.
- Added new GRID_NAMING_SEPARATOR parameter to the script export commands to allow users to control what separator character is used between pieces of a grid name. The default is an underscore.
- Added support for appending column names before row names when gridding on export from a script by using the GRID_NAMING=SEPARATE_COLS_FIRST parameter.
- Improved resizing of main map window so that the map data is not constantly redrawn as you drag the window to a new size.
- Increased the size of the displayed elevation on the GPS Information dialog.

- Added option when batch converting vector data to KML/KMZ files to allow the inclusion of displayed text labels for exported area and line features with labels.
- Fixed problems reading some TIFF files larger than 2GB in size.
- Added new shortcut key (Ctrl+1) to zoom the map to the full detail for the raster/elevation map at the center of the screen.
- Fixed error when trying to export vector-only data to a raster BIL file.
- When exporting Polish MP files using an image ID from a template file and also gridding the export into multiple pieces, automatically increment the image ID of the output files to prevent duplicate image ID values.
- Added new option to always display line labels on the center of the longest segment of the line to the Vector Display tab of the Configuration dialog. This prevents line labels from jumping around as you zoom and pan around.
- Added new option to only snap to area and line vertices by default when drawing new features to the Vector Display tab of the Configuration dialog. Holding the 'V' key when drawing the new features will toggle this behavior.
- Enable snapping to existing features when inserting vertices into existing area and line features using the Digitizer Tool. The shortcut key to stay in "insert vertex" mode was changed to the 'I' key from ALT since the ALT key is used to disable snapping behavior.
- Added option to crop Shapefile exports to selected area features. This will only include point features inside the selected area features and line and area features that intersect the bounding box of the selected area features.
- Updated GeoTIFF export to always write out all projection information and parameters even when an EPSG code is matched and written.
- Added support for additional parameters for recommended route (0x0108) and marine contour (0x0105) lines when exporting vector data to Polish MP files.
- Fixed memory leak when running a script file with EXPORT_RASTER commands that includes vector data from the command line.

WHAT'S NEW IN Global Mapper v9.03

- **Significant New Features**
  - Added support for loading Tiger 2007 Shapefiles with full attribution and automatic styling and type assignment from http://www.census.gov/geo/www/tiger/tgrshp2007/tgrshp2007.html.
  - Added support for loading Vulcan3D triangulation files.
  - Added support for exported loaded gridded elevation data to Vulcan 3D triangulation (.00t) files.
  - Added support for loading OpenStreetMap (OSM) format vector maps.
  - Added support for loading NITF data sets using JPEG2000 compression.
  - Added option to directly export the results of the triangulation and gridding of loaded vector layers from the Overlay Control Center to Global Mapper Grid files rather than loading them in the main map view, thus allowing larger areas to be triangulated and gridded at once without memory issues.
  - Added ability to add per-vertex elevations to features that don't already have them.

    - Made the vertex display dialog automatically highlight all vertices that are selected in the dialog on the map.
    - Made the Search by Attributes/Name dialog automatically highlight all of the result features that are selected on the map.
    - Added support for exporting loaded point features to TomTom OV2 format files for creating new point databases for loading onto TomTom GPS devices.
    - Added support for exporting loading vector data to Delft 3D (.ldb) format files.
    - Added option to KML/KMZ vector export to make labels for line and area features display on the map in Google Earth.
    - Added option when generating elevation grids from vector data to ignore zero elevation values.
    - Added automatic recognition of potentially iconized road names when editing road features. This allows you to do things like enter a road name of 'I-35' and have it automatically be recognized as an interstate highway iconized road name.
    - Added new option to the File menu of the rectification dialog to allow easily saving a world file that represents (if possible) the transformation defined by the currently provided control points.
    - Added option to the vector filter dialogs to save and restore a filter to a file.
    - Added yards and chains as available units of measure when using the Measure Tool.
- **Projection/Datum Changes**
    - Added built-in support for the MGA (Map Grid of Australia) projection.
    - Added built-in support for the Aratu and Camacupa datums.
    - Improved accuracy of OSGB36 datum conversions by using the OSTN02 tables.
    - Made Bonne projection work properly when the origin latitude is in the Southern Hemisphere.
    - Added support for decoding Albers Conic projections from Ozi .map files.
    - Added support for correcting the projection of multiple raster files at once (only if all of the raster files being corrected have the same projection to start with).
    - Fixed problem with displaying the equator grid line when using the Van der Grinten projection.
    - Fixed problems encoding and decoding Lambert Cylindrical Equal Area projection to/from GeoTIFF files.
- Added option to the Shader Options tab of the Configuration dialog to reverse the color order of the selected shader (previously only the HSV shader was reversible).
- Added support for reading the track style information written to GPX files by the ExpertGPS software application.
- Added new right-click option to the Feature Info dialog to allowing easily zooming to the extents of the selected feature.
- When an elevation legend is displayed, make selecting the View->Full View menu command zoom the map so that the elevation legend does not obscure any of the loaded data.
- When editing existing elevation values on the custom shader dialog, edit the value in the selected elevation units rather than always in meters.
- When digitizing new point features, display the distance from the last digitized point to

the current cursor position in the status bar.
- Added option to the Vector Display tab of the Configuration dialog to allow drawing dots at line endpoint locations (this is a subset of the existing option to display all area and line vertices).
- Fixed problem that prevented the description of the 'User Created Features' layer from being modified in some situations.
- Fixed bug with enabling transparent colors for gridded elevation maps that made them disappear in some cases.
- Added support for parsing coordinate values that use commas rather than periods for the decimal separator character.
- When exporting new Polish MP format files, check the default attribute list for the type of a feature if the feature does not have a particular attribute in its own attribute list (this was already being done for the MP_TYPE attribute, but has now been extended to all supported MP attributes, like PERIOD for light points).
- Fixed problem with icon symbols not being correctly exported to Polish MP files if the export was based on a MP template file using a LBLCoding value other than 9.
- Sped up exports to ECW and JPEG2000 files from map catalogs.
- Fixed snapping to existing line and area feature boundaries when the data being snapped to is in a different projection than the current view projection.
- Made the display label for selected area features be displayed if the option to only highlight the border of selected areas is selected.
- Improved default elevation unit selection when loading multiple files so that it doesn't always default back to meters.
- Fixed problem with some grid line labels being drawn at strange angles.
- Added new SPLIT_BY_LAYER parameter to the EXPORT_VECTOR command in the scripting language to allow splitting Shapefile exports into files based on the layer/type of each feature.
- When drawing new line and area features with the Digitizer Tool, render the vertices if we are displaying the vertices for other line and area features.
- Made the Feature Info dialog display the enclosed area in addition to the length in the Geometry field for closed line features.
- Allowed band selection for NITF imagery with 3 or more bands of data.
- Made the bit depth be displayed in the metadata list for MrSID and NITF imagery.
- Added support for WMS servers using secure HTTP (i.e. https:// addresses).
- Improved accuracy of area calculations when using the Mercator projection.
- Updated WASP .map area export to support roughness values in a RV attribute in addition to ROUGH_L and ROUGH_R.
- Write out "LOCAL" as the projection name when exporting ECW files using a projection that is not recognized for storage in ECW files.
- Added support for per-vertex elevations for area features from Shapefiles in all cases (previously only simple areas with no holes were supported).
- Made the calculated error at each control point in a rectification be saved in a GCP file saved through the File menu on the rectification dialog. It will be the last column for each control point.
- Improved great circle distance calculations by using the more accurate Vincenty

algorithm.
- Fixed remaining problems loading portions of some Erdas Imagine .img grid files with floating point samples.
- Fixed bug with image-optimized palette selection generating 24-bit RGB PNG and Erdas Imagine files when batch converting to those formats.
- Fixed problem with gap showing up between lines that end at the same location.
- Added built-in point types for bank and restaurant.
- Added built-in line type for invisible boundaries (such as those commonly found in Tiger/Line files).
- Fixed rare problem with very long vector lines or large area features not printing correctly.
- When loading KML/KMZ files, use the folder names from the files to automatically assign Global Mapper types if possible (i.e. if a matching type name exists).
- Added ability to specify water level in feet in addition to meters in the 3D viewer.
- Fixed problems loading some complex entities from DXF and DWG files.
- Fixed problems adding package files with multiple layers to map catalogs.
- Made default attribute lists be applied when changing the feature classification of multiple features at a time.
- Corrected placement of image files positioned using world files with rotation.

WHAT'S NEW IN Global Mapper v9.02

- **Significant New Features**
    - Added support for exporting any loaded data into tiles for use in Microsoft Virtual Earth. In addition, an HTML file will also be created allowing immediate viewing of the maps. The menu option for creating the tiles is under the new File->Export to Web Formats menu.
    - Moved web mapping formats, like Google Maps, World Wind, etc., to a new File->Export to Web Formats menu from existing export menus.
    - Added ability to batch convert to DTED and raster KMZ formats.
    - Added Vertices button to the Feature Info dialog to allow displaying and editing the location and per-vertex elevations for line and area features and displaying per-vertex time stamps for line features.
    - Added ability to apply elevation values from loaded terrain data to point features using a right-click option in the Digitizer/Edit tool.
    - Added new right-click menu option in the Digitizer Tool to allow easily shifting (offsetting) selecting features by some distance.
    - Added ability to combine multiple attribute values into the display label for features on the vector layer options dialog available from the Overlay Control Center.
    - Added new external control interface to allow external applications to control the view of Global Mapper and also display point features on the map loaded in Global Mapper. See the Developers page at http://www.globalmapper.com for details.
    - Added option to the path profile/line of sight dialog to allow matching the

elevation scale to the distance scale.
    - Added support for selecting multiple colors as transparent for palette-based raster files.
    - Added new Palette tab to Options dialog for raster layers with palettes to allow easy display and modification of the palette used for loaded raster layers.
    - Added support for loading PCI Geomatics RAW files with AUX headers.
    - Added support for loading German Topo map files in MPR/MPH format.
    - Added support for loading block polygon ASCII data files from the Minerals Management Service department of the US Department of Interior (DOI).
    - Added support for loading TMC Location Database files from (point.dat and poffset.dat files).
    - Added support for loading Lowrance USR v3 files with depth data.
    - Added support for automatic detection and loading of PLS-CADD XYZ files.
    - Made the dialog for drawing a box around the area to export be resizable and also allow zooming and panning the map.
    - Added support for having lines a fixed width in meters based on attribute values named WIDTH_M or LINE_WIDTH_METERS.
    - Added new GENERATE_ELEV_GRID script command to allow generating an elevation grid from loaded 3D vector data.
    - Made time stamps for each vertex in a GPS tracklog be saved if available when tracking a connected GPS device or when loading a tracklog from a GPX file.
    - Made tracklogs exported to GPX files contain time stamps if the tracklog had time information for each vertex.
    - Added new options to hide all offscreen layers and close all hidden layers to the right-click popup menu in the Overlay Control Center.
- **Projection/Datum Changes**
    - Added built-in support for the Belge 1972 (Belgian Lambert 1972) grid system, Laborde (Madagascar) projection, and Transverse Mercator (South-Orientated) projection.
    - Added built-in support for the NGO 1948 datum based on the Oslo prime meridian vs. Greenwich.
    - Added built-in support for the Tananarive 1925 datum based on the Paris prime meridian vs. Greenwich.
    - Added decoding support for some Polar Stereographic, Austrian Grid, and Norwegian grid EPSG projection codes.
    - Fixed Oblique Stereographic and Dutch Grid projections (they were broken in v9.00).
    - Fixed Lambert Azimuthal Equal Area projection to work properly with all datums. This fixes problems with the CORINE land cover data not lining up properly.
    - Fixed problems using New Zealand Map Grid with any datum other than NZGDA49.
    - Renamed some datums (i.e. ED50 and OSGB36) to make them shorter and reflect their more common usage.
    - Fixed problem loading new format (WKT) PRJ files with a datum using a

meridian other than Greenwich (i.e. the NTF Paris datum).
    - Added support for decoding Vertical Near-Sided Perspective projections from OziExplorer .map files.
    - Fixed bug using the Aitoff-Wagner projection.
    - Added centifeet (hundredths of feet) as an elevation unit for export.
- Made further improvements to triangulation and gridding to allow even larger data sets to be gridded.
- When gridding 3D point data sets using the File->Open Generic ASCII Data File menu command, made the elevation specific options (like tightness threshold and grid spacing) appear on a separate dialog after selecting the ASCII options.
- Added option to make specified export bounds be exactly maintained at the expense of the specified sample spacing (the reverse is the default) to the Advanced section of the General tab of the Configuration dialog.
- Allowed map catalog files to be added to existing map catalog files. In these cases, all files referenced in the map catalog being added will simply be added to the map catalog they are being added to.
- Added "Save As" button on the map catalog options dialog to allow changing the filename associated with a map catalog.
- Added new 'SPOT Natural Color' blend mode to combine the color channels in a layer using the common algorithm for generating natural color imagery from the SPOT HRV multi-spectral sensor.
- Fixed bug writing out 3D area features to DGN files.
- Made the 'Copy to Clipboard' button on the Feature Info dialog copy the actual feature to the clipboard for pasting into Global Mapper in addition to copying the text attribution for the feature to the Windows clipboard for pasting in a text application.
- Added new option to the Vector Display tab of the Configuration dialog to allow auto-iconizing road feature names on import if they are recognizable icon names (like I-70, US63, etc.).
- Made holding down the 'P' key when left clicking with the Feature Info tool only select area features (i.e. nearby lines and points will be ignored).
- Fixed problem generating image-optimized palettes during export when the input files are all palette-based files whose combined palette has over 256 colors.
- Allowed for the generation of .tab files for ECW and JPEG2000 when batch converting.
- Made results on Search by Attributes dialog not include features in hidden layers or features with the types disabled for display.
- Allowed splitting of selected area features at selected vertices with the Digitizer Tool when more than one feature is selected.
- Added option to several raster export formats (like ECW, JPG, JPEG2000) to fill small gaps between valid data samples.
- Fixed problems loading some projections from ECW and JPEG2000 files.
- Made additional speed-ups to ECW and JPEG2000 exports when exporting from large numbers of loaded files.
- Added option to feathering to just crop to the specified feather boundary rather than actually feather-blending.
- Added option to palette-based exports to use a custom palette from a .pal file (such as one

saved from the transparency dialog in Global Mapper).
- Added new Option menu command on the rectification dialog to allow displaying the transformation equations used for the specified control points.
- Added new option to the Advanced Selection menu in the Digitizer Tool for easily selecting all of the island areas associated with a parent area and deselecting the parent.
- Prompt for the type of 16-bit Erdas Imagine .img files (i.e. are they elevation data or imagery).
- Improved loading of HATCH entities from DXF files.
- Improved loading of text from MTEXT entities in DXF files.
- Added option to Google Maps export to select the default Google Maps background layer that is displayed (i.e. street maps, imagery, or terrain).
- Made the last searched address be remembered on the Find Data Online and Find Address dialogs.
- Made point classification and intensity be available for Lidar points from Terrascan format files.
- Made the Search by Name and Search by Attributes dialogs show a bullseye on the map when you double click on a search result.
- Made running script files that make changes to the main view automatically update the main view window when they complete in all cases.
- Made the 'Run in Context of the Main Map View' setting on the Run Script dialog be remembered between runs.
- Allow selection of elevation units when batch converting to the Lidar LAS format.
- Fixed bug with color intensity values not being used in some cases for some raster files.
- Added option to the elevation grid generation dialog to allow the user to specify that they want the generated elevation grid to fill the entire bounding box of the input data rather than stopping at the convex hull of the data set. This should really only be used for data sets that very nearly fill the bounding box but have corners cut off or something.
- Added support for reading raster layout information from .glcf data files.
- Fixed problems loading portions of some Erdas Imagine .img grid files with floating point samples.
- Added support for auto-detecting connected NMEA GPS devices running at 9600 baud (in addition to the standard 4800 baud).
- Fixed error exporting vector data to SHP file if there are more than 100 attributes with the same name to 10 characters associated with a single feature.
- Added support for getting positioning information for JPG files from JGC files.
- Fixed problems loading CDF files where the pen goes up and down within a single string of coordinates.
- Added new RP_RenderStarted and RP_RenderFinished functions to raster/elevation import plugin API to allow plugin DLLs to be notified of raster begin and end operations with the bounding box being rendered.
- Significantly sped up the loading of line and area features with a lot of vertices from KML/KMZ files.
- Fixed problems loading some new MicroDEM DEM format files.
- Fixed problems converting some Erdas Imagine elevation files with void areas to Arc ASCII Grid format files.

- Made elevation values from loaded terrain data be used when batch converting to Simple ASCII Text files and selecting to include elevation data.
- Ignore duplicate point features in DXF BLOCK sections.
- Fixed error in some cases when generating view sheds while checking Fresnel zone clearance.
- Made cut-and-fill volume calculation operations for areas report the 3D surface area of the calculation area in addition to the 2D surface area.
- Slightly increased the precision reported for some measurements.
- Added option to the right-click menu on the Overlay Control Center to allow disabling selection of vector features from a layer.
- Added support for using a MP_BIT_LEVEL attribute value to specify the maximum zoom bit level that a particular feature (or feature type for default attribute lists) should be visible at in exported Polish MP files.
- Added new area fill styles (black cross and black dot on white backgrounds).

WHAT'S NEW IN Global Mapper v9.01

- **Significant New Features**
    - Added support for exporting any loaded data into tiles for use in Google Maps. In addition, an HTML file will also be created allowing immediate viewing of the maps.
    - Made significant improvements to the triangulation and gridding of 3D point, line, and area data. Not only is the process now MUCH faster (especially for large triangulations), but it also now supports treating lines as constraints (i.e. breaklines), saving the generated triangulation as a separate vector layer, and making elevations for source vector features be relative to the elevation from loaded terrain data. You now also grid a much larger number of points at once (well over 10 million points have been tested with no problems).
    - Added option to Shapefile export to split the export into separate files by layer. This allows you to easily break your data up into separate Shapefiles based on the layer/description of the features being exported. The layer name for each file will be appended to the end of the selected export filename.
    - Added fuzzy transparency support to allow for transparency for a raster layer to be set up so that all colors near a selected transparent color can be marked as transparent. This is useful for removing collars from lossy formats, like JPG, ECW, and MrSID.
    - Allowed 3D area features to be created in Shapefile export.
    - Added support for loading RIK (Swedish Topo) format raster files.
    - Added support for loading OCAD format files.
    - Added support for loading MapTech PCX charts. Load these from the MapTech .hdr file in the ChartHdr folder.
    - Added support for loading OziExplorer .rte format files.
    - Added support for loading Garmin PCX5 .rte format files.
    - Added support for loading UKOOA format post plot data files. They are listed under the format SEGP1/UKOOA.

    - Added support for loading HF2/HFZ format elevation grid files.
    - Added support for exporting loaded gridded elevation data to HF2/HFZ format files.
    - Added new item to the Options menu on the Path Profile/Line of Sight dialog to allow specification of how many sample points (either by number or by a spacing distance) to use when generating the path profile.
    - Allowed feather blending to use multiple polygons.
    - Added several new built-in symbols for different well types used in the petroleum industry.
- Made minor improvements to Polish MP export, including option to keep ID value from [IMG ID] section during templated exports, to copy the [FILES] and [MAP] sections from template files, to allow Text attributes longer than 80 characters, and to automatically remove the labels from marine spot depth and height points.
- Added new option to JPG export to allow specification of a DPI value to store in the exported JPG file.
- Added DXF vector export option to use the filename for the input feature as the layer name in addition to the default of the feature description or the feature label.
- **Scripting Language Changes**
    - Added new COMBINE_TERRAIN command to the scripting language to allow combining terrain layers to generate a new layer using a script file.
    - Added new ADD_MEASURE_ATTRS command to the scripting language to allow adding measure attributes to loaded vector layers from a script.
    - Made the OVERWRITE_EXISTING=NO parameter work properly when gridding an export from a script.
    - Added new PIXEL_SIZE parameter for use with the EXPORT_RASTER script command. This parameter allows you to specify the desired pixel size of your export result. The format is PIXEL_SIZE="<width>x<height>", or PIXEL_SIZE="1024x768" as an example.
    - Made the value of the INC_VECTOR_DATA parameter default to YES with the EXPORT_RASTER command if only vector data is loaded.
    - Allowed use of SPATIAL_RES parameter with the IMPORT_ASCII script command to manually specify the grid resolution to use when generating a gridded elevation layer.
    - Added new LAYER_BOUNDS_EXPAND parameter to script commands taking a bounding box so allow using an expanded version of a bounding box obtained using a LAYER_BOUNDS parameter.
    - Added new DGN_GLOBAL_ORIGIN_LL, DGN_REPLACE_DARK_COLORS, and DGN_UNIT_RESOLUTION parameters to the EXPORT_VECTOR script command to allow specifying additional options for DGN export.
    - Made GEN_WORLD_FILE parameter work for ECW and JPEG2000 exports from script files.
    - Added new PROJ_EPSG_CODE parameter to IMPORT commands to allow specifying the projection by EPSG code.
- Allowed easy movement of view sheds by moving the transmitter point feature at the center of the view shed using the Digitizer/Edit Tool. When this is done, the user will

now be prompted to recalculate the view shed at the new location if they want.

- Added option to lock the current active workspace file while you are working with it to prevent other users from opening and using that same workspace file. This is useful in network environments where you don't want one persons work to accidentally overwrite another's. This option is in the Advanced section of the General Options tab of the Configuration dialog.
- Added option to have cells from DGN v8 and later files to be imported as point features at the cell's origin rather than be exploded into the features referenced by the cell. This option is in the Advanced section of the General Options tab of the Configuration dialog.
- Added option to have the color number for lines from DGN v8 and later files to be add to the feature description text in addition to the level number. This option is in the Advanced section of the General Options tab of the Configuration dialog.
- Added option to generate world files and PRJ files during Terragen terrain export.
- Added support for getting depth values from a connected GPS device that embeds $STDBT or $IIDBT NMEA sentences containing the depth values. For GPS devices that provide depth, the depth will be used as the Z coordinate for track logs rather than the elevation value.
- Added option to Options menu on rectification dialog to automatically add control points at the image corners.
- Fixed creation of attribute list when marking new waypoints from a connected GPS device. Previously the elevation and time stamp attributes were no longer being saved.
- Fixed problem with elevation units other than meters not being usable for Lidar LAS and Terrascan files loaded as point cloud data sets.
- When loading TIFF files with 4 color channels and the 4th color channel is of unspecified type, prompt the user to see if this should be treated as an alpha channel or an additional data channel (like infrared). This allows TIFF files created with Photoshop with an incorrectly marked alpha channel to be loaded and displayed properly.
- Added new option to the Advanced section of the General Options tab of the Configuration dialog to automatically save backup copies of the current workspace every so often. These backup copies will be created in the same folder as the workspace file and have the suffix "auto_backupX", where X is a number from 0 to 9.
- When generating new area features from the bounds of layers in the Overlay Control Center, make those new areas have an attribute list consisting of the metadata from the layer.
- Made the last selected file type be remembered between sessions on the GeoTIFF export dialog.
- Made the last selected export target compression ratio be remembered between sessions on the ECW and JPG2000 export dialogs.
- Made the last selected quality setting be remembered between session on the JPG export dialogs.
- **Projection/Datum Changes**
    - Added the Winkel Tripel projection as a built-in projection.
    - Added built-in support for the BD72 (Belgium 1972), M'Poraloko (Gabon) and Google Maps datums.
    - Improved the accuracy of the ED50 - Spain and Portugal datum transformation by

having it use a NTv2 transformation file.
    - Improved the accuracy of the MGI Austria and Potsdam (DHDN) datum transformations.
    - Added Indian Yard as an available unit for projections.
    - Allowed EPSG datum codes to be used to specify a datum on the projection selection dialog using the 'Init From EPSG' button.
    - Added support for decoding Polyconic (American) projections from OziExplorer .map files.
- Made the map/chart type for CADRG maps (i.e. TPC, ONC, etc.) be included in the layer description and metadata for those maps.
- Fixed problem with elevation override data not being applied to elevation WMS layers (like SRTM and NED) loaded from a script or workspace file.
- Made the Vertical Units control actually work when combining terrain layers.
- Made the addition operation work when combining terrain layers in areas where only one of the two input layers has a valid elevation.
- Made Surfer CLR files saved from the custom shader dialog actually be compatible with Surfer.
- Added support for correctly importing line and point features in Polish MP format files that have multiple Data0 coordinate records.
- Added option to PNG export options dialog to easily specify the sample spacing in units other than the current export projection units.
- Improved performance of raster exports from map catalogs when one or more files referenced by the map catalog are missing.
- Added support for automatically cropping the collar of Canadian topographic maps with CanMatrix XML metadata files.
- When exporting filled area features to DXF files, write out the fill color of the area to the DXF file.
- When exporting raster layers to Global Mapper Package files, make those layers support transparency so that they will overlay properly on other layers when re-loaded.
- Made feather-blended elevation layers visually feather blend better in to underlying layers rather than just smoothly blending the elevation values.
- When loading files from workspace, script, and map catalog files, if the file exists at the full path specified, don't check for a new location relative to the metafile location.
- When rectifying imagery, allowed new control point values to be entered as lat/lon coordinates regardless of the native projection of the layer.
- Fixed problem with manually specified grid spacing being ignored when flattening areas using the Digitizer Tool.
- Added option to World Wind export to allow generating the filenames required by the Java edition of World Wind.
- Updated area calculations to be done in the native units for a layer rather than always be done in lat/lon coordinates. This can make area calculations from Global Mapper for large areas more consistent with what you see in other applications.
- Fixed bug with fill style not being read from generic ASCII files properly.
- Fixed errors rendering ECW and JPEG2000 files to monitors with extremely high resolutions (typically multi-monitor setups).

- Added option to Help menu to disable the automatic check for updates at application startup.
- Made it possible to batch convert from ASCII text files (like XYZ) to gridded elevation formats.
- Fixed bug in batch conversion that caused the horizontal extents of raster or gridded elevation data exported using a custom spacing to be incorrect in some situations. Also fixed problem with an extra column and or row being exported when the custom spacing option was used.
- Added attributes for database linkages to loaded DGN files.
- Improved the handling of break lines imported from DMDF format files.
- Fixed problems loading some Garmin PCX5 files.
- Added new File menu commands to the rectification dialog to allow loading control points and projection information from CompeGPS .imp and Touratech TTQV .cal files.
- Added option to specify offset and scale values to apply to coordinates loaded from EMF format files.
- No longer save the 'Render Areas', 'Render Lines', 'Render Points', and 'Render Area and Line Vertices' options from the Vector Display tab of the Configuration dialog between runs as this tends to cause confusion. The first three will always be enabled by default when you start Global Mapper and the vertex display will now always be disabled by default.
- Corrected positioning of ENVI files that don't use the top left coordinate as their reference point.
- Fixed problems exporting attributes with special characters like # and - in their name to MapInfo MIF/MID format files.
- Added support for loading ERS files with missing cell sizes. These are apparently defined as having a cell size of 1.0.
- Made the last exported bounds be available between runs of Global Mapper.
- Added an option to the Advanced section of the General tab of the Configuration dialog to make the full path to files be displayed in the Overlay Control Center for layers that do not have any description other than the filename.
- Allowed selection of which bands are used from multi-spectral FAST-L7A Landsat imagery layers.
- Added support for loading 16-color (4-bit per pixel) PCX files.
- Made holding down the 'P' key when selecting a new location in the Reference View of the rectification dialog or when using the Measure or Digitizer Tools, cause the new location to be snapped to the nearby point features.
- Made the default attribute list for a feature type be applied when changing the classification of an existing feature through the single feature edit dialog.
- Fixed problem with missing start row and column of DTED tiles in some cases when exporting to DTED format.
- When cropping to selected area features during a batch conversion operation, made the bounds of the exported data also be cropped to the selected area features.
- Added support for loading Ozi .map files with grid coordinates in multiple UTM zones.
- Significantly sped up export of large number of files to ECW and JPEG2000 format files.
- Added support for modifying the default projection used when rectifying imagery by

supplying a default_rectification.prj file in the Global Mapper installation folder containing the desired default projection.
- Added Ctrl+R as shortcut key to restore last saved view.
- Made the compression type used for TIFF files be displayed in the metadata for the file available from the Overlay Control Center.
- Made the image collar specified in the "MainPolygonBitmap" section of CompeGPS IMP files be used when automatically cropping the collar of imagery loaded with positioning information from the IMP file.
- Fixed problem with the 'Update GCP' button on the rectification dialog causing the name of the control point being updated to be lost.
- Added ability to automatically add/update a MODIFIED_DATE parameter to vector features when they are modified. This option is found in the options list at the bottom of the Vector Display tab of the Configuration dialog.
- Added control of the JPEG-in-TIFF quality setting with a new DWORD registry setting at "HKEY_CURRENT_USER\Software\Global Mapper\JpegInTiffQuality" to control the JPEG-n-TIFF quality. The default value is 75.
- Added control of the default search string used in the Search by Attributes dialog with a new string registry setting at "HKEY_CURRENT_USER\Software\Global Mapper\DefaultVectorSearchStr". The default value is '*'.
- Made it possible to batch rectify ECW and JPEG2000 format files using the File->Rectify Imagery menu command.
- Made LiDAR LAS export write out the point count for each number of returns in the header.
- Made LiDAR LAS support reading and writing projection information.
- Added an 'Invert Selection' option to the popup menu when you right click on the search results list on the Search by Attributes dialog.
- Made the Add/Update Feature Measures option in the Digitizer Tool report the combined length of all selected line features and the combined enclosed area of all selected area features at the end of the operation.
- Added new 'Deleted Line' and 'Selected Line' line classifications so that users could modify the drawing style used for deleted and selected line features.
- Fixed saving of Lambert Conformal Conic projections to MapInfo MIF/MID files (this was broken in v9.00).
- Updated elevation legend to only display the valid range for visible gridded elevation files.

WHAT'S NEW IN Global Mapper v9.00

- **Significant New Features**
  - Added direct access to high resolution Digital Globe, GlobeXplorer, and AirPhotoUSA imagery for the entire world through the File->Download Online Imagery menu command. Free access is provided to watermarked imagery for reference only, with access to un-watermarked imagery that can be exported to new files can be purchased.
  - Added support for exporting ECW files of unlimited size. Previously there was a

limit of 500 MB of uncompressed data for ECW exports.
    - Added support for exporting loaded data to JPEG2000 format files.
    - Added support for exporting loaded raster/elevation data to KML/KMZ file for display in Google Earth (use File->Export Raster and Elevation Data->Export KML/KMZ menu command).
    - Added support for exporting loaded gridded elevation data to DTED format files.
    - Added support for exporting loaded gridded elevation data and 3D vector data (including LIDAR point clouds) to LIDAR .LAS format files.
    - Added ability to make area features partially transparent. Everywhere that you can edit an area style now has a transparency slider allowing you to adjust how translucent a solid filled area will be.
    - Added new File->Combine Terrains menu command to allow combining loaded terrain layers with a variety of operations, including differencing terrains, averaging terrains, and using the min and/or max elevations from two terrains.
    - Added new option to the Color/Contrast Adjust option dialog for raster layers to allow specification that the contrast adjustment should be shared between multiple layers. This allows a consistent contrast adjustment to be applied to all images with that option checked.
    - Added option to view shed calculation to generate area features for the covered areas. These generated area features could then be exported to vector formats like Shapefiles.
    - Added support for feather-blending elevation layers in order to smoothly blend the elevation values of one layer with an underlying one near some edge (either a polygon or the rectangular edges of the top file).
    - Added support for loading DMDF (Digital Map Data Format) files, such as those used for Alberta DEM files.
    - Added support for loading vector data from EMF (Windows Enhanced Metafile) files.
    - Added support for loading Erdas .LAN format files.
    - Added support for loading PCX format image files.
    - Added support for loading point Arc Vector Coverage files (lab.adf).
    - Added option to the Vector Options dialog to allow selecting the attribute to use for elevation values for vector features. This is useful if you want to get elevation values from something other than the default elevation field for a layer.
    - Added option to the Digitizer Tool to split an area feature into 2 pieces along the segment connecting 2 selected vertices.
    - Made the Search->Search by Attributes/Name/Desc dialog be "modeless" so that you can interact with the map underneath the dialog without closing the dialog.
- Added new "Select All" option under the Edit menu to allow easily selecting all loaded vector features.
- Added support for loading files in a fixed location relative to the screen with the position of the file being specified in width or height percentage values or relative to an absolute latitude/longitude value in addition to the previously available inches from edge values.
- When specify custom crop bounds for a raster layer, allow control of which sides will be cropped through check boxes activating which edges to actually crop. The default is all

edges.

- Added a new "Hill Shading Shadow Darkness" control to the Vertical Options tab of the Configuration dialog. This control allows you to control the maximum darkness of shadows (the default is black). With this setting you can cause the shadowing to be capped in high relief areas, thus allowing the use of other controls to better bring out detail in low-relief areas.
- Added support for drawing the location for a connected GPS device as a circle or transparent triangle with a dot at the center for the GPS location. This support is provided by the new GPS->Vessel Shape submenu.
- Added option to DXF vector export to allow elevation values from loaded elevation layers to be used as the Z coordinate for exported vertices if available.
- Added option to DXF vector export to allow coordinate values to be written out as ECEF (earth-centered earth-fixed) coordinates rather than in the current selected projection.
- Added support for performing batch geocode operations from data files using currently loaded road data. Previously batch geocoding was limited to the US using an online geocoder. With this new feature, geocoding can be done using load and properly attributed road data along with input address data split into appropriate fields.
- Allowed drawing of rectangle, square, circle, and ellipse shapes anchored at the top left rather than center with the Digitizer Tool by holding down the 'T' key when left clicking to start the shape.
- **Projection/Datum Changes**
    - Added option to the projection selection dialog to allow a projection to be initialized from an EPSG projection system code.
    - Made the parameters used for most grid system and zoned projections, like British Grid and UTM, be displayed in the attribute section of the projection selection dialog (which will be disabled for those projections).
    - Added support for the India Zoned Grid, Korean Grid, Krovak, Lambert (Marta), Lambert (NOAA), Marta Satellite, and Winkel I projections.
    - Added built-in support for the Dealul Piscului 1970, Ireland 1965 (with 1975 Adjustment), Korean Geodetic (KGD), Lisbon (DLx), S-JTSK, Solomon 1968 (GUX1 Astro) datums as well as a generic GRS80 ellipsoid datum.
    - Improved accuracy of the Beijing 1954, Hungarian Datum 1972 (HD72), NGO1948, and Portugese 1973 (Datum 73) datums.
    - Added Bessel (Modified) as a new built-in ellipsoid.
    - Added support for adding new ellipsoids to create custom datums from on the custom datums dialog.
    - Fixed crash when exporting to some formats with the Old Israel Grid or New Israel Grid projections selected.
    - Made the extra scale factor for State Plane projections be applied AFTER any false easting and northing values for the underlying projection for the State Plane zone, rather than before the false easting/northing values as before.
- **Scripting Language Changes**
    - Allowed exports cropped to a polygon from a file be cropped to multiple polygons with the new POLYGON_CROP_USE_ALL parameter for the export commands.

    - Added CLIP_COLLAR_FLAGS parameter to IMPORT script command to allow saving of per-edge collar cropping flags.
    - Added COLOR_INTENSITY_FULL parameter to IMPORT script command to allow specification of higher resolution color intensity for raster layers (from 0 to 512 rather than 0 to 20).
    - Allowed the polygon to use when feather blending to be specified from a file using a FEATHER_BLEND_POLY_FILE parameter with an IMPORT command in a script file.
    - When using the EXPORT_RASTER script command in conjunction with a polygon crop file, only use the bounds of the crop polygon for the export as the export bounds if the export bounds are not explicitly specified. In addition, for gridded exports with a crop polygon, don't export grid cells that are completely outside of the crop polygon.
    - Fix error with some layers not showing up in the output when using the EXPORT_RASTER script command in conjunction with gridding.
    - Added new parameters to the EXPORT_* script commands to allow specifying how gridded tiles should be named.
    - Allowed FEATURE_SEP values for exporting simple ASCII text files with the EXPORT_VECTOR script command to specify feature separators other than just none or a blank line.
    - Fixed problem using SET_BG_COLOR in scripts called from the command line.
- Made the area covered by the bounding box of a layer be reported as part of the metadata for that layer.
- For BIL and Erdas Imagine elevation exports, if all of the input files use the same NODATA value use that rather than the default of -9999.0 for the NODATA value for the export.
- Fixed problem loading complex shapes from older (pre-v8) DGN files. This problem was introduced in the v7.04 release.
- Improved decoding and encoding of some Lambert-based projections with default units of feet with ECW files.
- Fixed garbled display of some rare ASRP/ADRG/USRP format maps.
- Fixed problem with features being duplicating when copying and pasting selected features from multiple data layers at a time.
- Made blending and translucency between layers within a map catalog work properly.
- Fixed display of selected features when dragging a map to pan.
- Made nearby point locations be snapped to when selecting the transmitter location for view shed analysis.
- Fixed problem with scale bar being cut off when printing to scale with a footer string.
- Fixed problem in v8.03 with some features in the a User Created Features layer not responding to the show/hide checkbox in the Overlay Control Center.
- Fixed problems loading area and line features with more than about 200,000 vertices from Polish MP format files.
- Increased precision of angular coordinates (like arc degrees) written to text file formats, like Simple ASCII Text export, to support approximately the same level of ground truth precision as linear coordinates (like meters).

- Fixed problem with offscreen islands not being exported when exporting simple ASCII text format files.
- Fixed problems loading uncompressed CIB imagery.
- Fixed problems with edited labels for Shapefile features not being saved to workspaces.
- Split line features with more than 5,000 vertices into multiple pieces on export to DGN files as some applications (like Microstation) do not support lines with more than 5,000 vertices.
- Added option to DGN export for converting dark line colors (like black) to white. This is useful as many DGN viewers automatically use black as the background color, making dark colors very difficult to see.
- Added option to the GPS Status dialog to copy the current GPS location to the clipboard.
- Added support for loading polyface mesh features from DXF files.
- Added support for loading DXF files with nested BLOCK references.
- Fixed problems handling some SPLINE entities in DXF files.
- Added new View->Properties menu command to allow displaying properties about the current view, including bounds, scale, and resolution.
- Made ERS files be used for positioning information if needed for additional formats, like JPG, ECW, TIFF, and PNG.
- Increased the resolution of the color intensity slider on the raster options dialog and also made the current intensity value be displayed.
- Made filenames in the Overlay Control Center be displayed with the same casing as they have on disk rather than always being all upper case.
- Added new option to the Advanced section of the General tab of the Configuration dialog to allow users to specify that the default export folder should be the folder of the first loaded file rather than the last exported-to folder.
- Added new option to the Advanced section of the General tab of the Configuration dialog to specify that lines in generated world files should be separated with CR/LF (carriage return and line feed) characters rather than just a LF (line feed) character.
- Updated GNIS files to use the NAD83 datum as the USGS switched to that in 2005. In addition, GNIS files that use meters for elevation values will also handle those correctly and less error messages will be shown for GNIS files.
- Allowed clearances greater than 100% of the first Fresnel zone to be checked when performing line of sight and view shed analysis.
- Made the minimum clearance display for line-of-sight analysis display in the currently selected 'Position Display Format' if the From and To locations are also displayed using it.
- Fixed problem with the per-vertex elevation list for 3D area and line features not being maintained when copying and pasting those features.
- Fixed problems with loaded data from some VPF data sets with only one tile of data, namely UVMAP3 data.
- Fixed memory leak when generating an elevation grid from some loaded 3D vector data sets. This problem was introduced in the v8.02 release.
- Added a new right-click option to the Overlay Control Center to allow you to save a workspace file containing just the selected layers and their settings.
- Changed export of transparent areas to new 24-bit RGB PNG files to use an alpha

channel rather than a single color transparency as some applications only support the alpha channel method.
- Fixed error loading some RPF (i.e. CADRG/CIB) data sets.
- Fixed file size error loading some Geosoft Grid files.
- Made Global Mapper workspace (.gmw) files be loaded from archive files (.zip, .tar.gz, etc.). If any .gmw files are encountered and loaded from a workspace file, no other data files will be loaded from the archive file.
- Made it possible to rectify MrSID files with the File->Rectify Imagery menu command.
- Fixed error loading some DGN v7 or older files with tags in them.
- When digitizing new area, line, and point features, notify the user if their features will not be displayed immediately after creating it due to vector display settings.
- Make the default attribute list for the default classification be properly initialized when digitizing new features.
- Make sure that the user wants to switch away from the Digitizer Tool if doing so would result in the loss of a significant number of digitized points.
- Display progress while saving workspace files.
- Added support for reading vector features from KML files that use multiple Schema directives to change the name of Placemarks.
- Fixed rare problem with a handful of iso-height areas not generating properly during contour generation.
- No longer break lines over 256 vertices into smaller pieces on export to the Polish MP format as cGPSMapper can now properly handle lines of any length.
- Made double-clicking on layers in the Overlay Control Center bring up the Options dialog for that layer. If you hold down the 'M' key when double-clicking the Metadata dialog will appear instead.
- Added support for the Swiss Grid projection in ECW files.
- Fixed problems batch converting Lidar LAS format files to some other formats, like Shapefiles.
- Made automatic DRG-style collar cropping work for high latitude Canadian topo maps.
- Added support for loading MSI Planet files with a .dat extension.
- Made GML files from the UK Ordnance Survey load.
- Allowed border and line widths up to 30 pixels wide (up from 10) to be selected.
- Updated raster/elevation import plugin API to allow the plugin DLL to notify Global Mapper that the data in a layer has changed and needs to be redrawn, thus allowing for dynamically updating layers.
- Updated raster/elevation export plugin API to add an EP_ExportEvent function that is called whenever an entire export operation is started and ends.
- Reduced memory requirements for loading and displaying CMYK TIFF files.
- Dramatically sped up the process of moving overlays to the top and bottom of the draw order when there are a lot of layers loaded.
- Don't attempt to load DBF files from archive (.zip, etc.) files if they don't have obvious positioning fields in them.
- In the location selection dialog, made the Latitude and Longitude fields initialize with the coordinates formatted according to the currently selected position display format. Also swapped the fields so that the Latitude is on top.

- Made the elevation readout on the status bar display up to 3 digits beyond the decimal rather than just 1.
- Made DEM files exported with the Geographic (Lat/Lon) projection write out full elevation profiles for every column, even if there are invalid data values at the beginning and/or end of the profile. This is to ensure compatibility with other software.
- Added support for the user providing an explicit format and/or projection to use in the service name string when adding a new WMS data source. For example, if a data source is available in both JPG and PNG formats and you want to get the JPG data, use a service name of 'WMS&format=image/jpeg' when adding the data source. Use the SRS parameter to explicitly select a projection to use.
- Added support for specifying extra WMS parameters (like map=) in the Server URL when creating a new WMS source. This allows you to now have parameters after a question mark be used rather than ignored.
- Added new right-click option to the Measure Tool to specify that no unit labels (like 'm' or 'ft') should be appended to the measure attributes added to new line and area features.
- Fixed half-pixel shift of GeoTIFF files that were forcefully positioned using a world file rather than embedded positioning information.
- Added new advanced selection option to the Digitizer Tool to allow selecting all line features contained within a selected area feature.
- Made the false easting/northing values for UTM projections in units other than meters be stored correctly when saved to WKT format PRJ files.
- Made the list of user-provided web-based ECW links be stored in a text format in the user_web_files.wfl file rather than a hard to edit binary format.

WHAT'S NEW IN Global Mapper v8.03

- Added support for loading GML format files.
- Modified the Overlay Control Center to display a checkbox next to each layer for controlling the displayed state of the layer. This replace the previous text of "(Displayed)" and "(Hidden)" used for each layer and also provides an additional mechanism to turn the layer on and off.
- Added new option on the "Select Online Data Source to Download" dialog to specify the download location as a lat/lon and a radius.
- Added option when batch converting and exporting most raster formats to generate an ERS file for use with ERMapper.
- Added new menu commands to the Options menu on the Path Profile/Line of Sight dialog to allow users to manually specify the range of elevation values displayed. This options allows for consistent results between multiple profiles if desired.
- Added option when drawing line or area arcs to have the arcs be a fixed radius rather than drawing them.
- Added option to use a template file when batch converting to new Polish MP format files.
- Added option to the Generic ASCII Import dialog to allow the specification of a column to break area/line features on when the value of that column changes. This allows importing formats like the Landmark polygon format that runs all of its features together but changes a feature index in a particular column to indicate a new feature.

- Allowed batch conversion to raster/elevation export formats added via plugin.
- Added a new line type ("Digitizer Tool Line") that controls the drawing style used when digitizing new line and area features with the Digitizer (Edit) Tool.
- Added option to the transparent color picker dialog for palette-based files to save the palette to a .pal file.
- Added built-in support for the Tananarive Observatory 1925 and Yacare datums.
- Corrected datum conversions involving the Hermannskogel datum.
- Fixed export to ECW format when export units are not arc degrees, meters, or US survey feet.
- Fixed errors during lengthy exports to ECW files when data from online sources was loaded.
- Fixed problems with not being able to change the label attribute used for Shapefile features that have a 'LABEL' attribute associated with them.
- Fixed reading of altitude values for waypoints in somee Garmin PCX5 .WPT format files.
- Fixed rendering of TIFF files with overview layers when raster display options are changed from the defaults. This problem was introduced in v8.02.
- Allow color band setup for TIFF files with just 3 color bands.
- Fixed slowdown in rendering/exporting TIFF files. This was introduced in v8.02.
- When batch converting ADRG/ASRP files to new raster formats, use the name of the internal .IMG file for the export results rather than the TRANSH01.THF file which is too generic.
- Made most of the metadata for SDTS vector layers be available on the main metadata tab for that layer to allow easy copying to the clipboard.
- Fixed problems with translucency, blending, and feathering over the top of TerraServer-USA data layers.
- Fixed vertical flip of some GMT grids in netCDF format.
- Added Projection tab to the Options dialog for raster and gridded elevation layers to allow easily changing the native projection interpretation of the coordinates for that layer. This allows you to easily correct files that have the wrong projection/datum used for them at load time.
- Made the vertices of holes/islands in areas be displayed when displaying area and line vertices.
- Fixed rare problem decoding some sections of Arc Binary Grid format files.
- Fixed error when exporting vector data to Erdas Imagine .IMG files.
- Made online data display more responsive to canceling the render with the ESC key.
- Improved exporting of data to palette-based images with multiple colors in the export palette being very near each other.
- Added BANDROWBYTES, TOTALROWBYTES, BANDGAPBYTES, and NODATA fields to the .hdr file exported for elevation BIL format exports.
- Added support for reading <MultiGeometry> features from KML files.
- Fixed problems when adding loaded map files to a map catalog when the loaded files were loaded from an archive file, like a .zip or .tar.gz.
- Added support for loading some additional Moss/Genio format files and made *.inp be a recognized file mask for that type of file.

- Fixed crash when generating contour lines at only the 0 height contour.
- Fixed problems with the global projection being reset when using the VECTOR_ONLY=YES parameter for the UNLOAD_ALL script command.
- Allowed .clr palette files for BIL/BIP/BSQ format files to be delimited with commas, tabs, or semi-colons in addition to spaces.
- Added support for additional NITF format imagery files, such as those using JPG compression.
- Added support for reading vector features from KML files that use a Schema directive to change the name of Placemarks.
- Improved the name displayed for Arc Vector Coverage layers in the Overlay Control Center.
- Make default export elevation units for DEM and Global Mapper Grid exports be decimeters if metric units are the default so that the full precision of nearly all data sets will be preserved by default.
- Added option to save custom shaders to Surfer CLR format files when editing them. When coupled with the current ability to initialize a shader from a Surfer CLR file this provides an easy way to makes copies of custom shaders.
- Added support for loading new tab-delimited GNIS format files.
- Fixed problems exporting attributes as tags to DGN format files (this problem was introduced in v8.02).
- Made graphic group codes for 2D lines and points from DGN v7 files be used as elevation values.
- Made the 'z' scan range value for 2D lines and points from DGN v8 files be used as elevation values.
- Added new GRID_KEEP_CELL_SIZE parameter to the scripting language to allow specification that grid cell size should be maintained at the expense of sample spacing.
- Added support for reading 8-bit palette and grayscale Intergraph COT format files.

WHAT'S NEW IN Global Mapper v8.02

- Added the ability to load layers (like graphic images) to be displayed at a fixed location on the screen rather than tied to earth coordinates. This allows you to add things like headers and watermarks very easily. There is a new File menu command called "Open Data File at Fixed Screen Location" that allows this.
- Added ability to export any loaded data to tiled images for use in NASA's World Wind application. The new World Wind export option under the File->Export Raster and Elevation Data menu will correctly break your data up into tiles at various zoom levels and also create the necessary XML file to view your data in World Wind.
- Added the ability to copy features selected with the Digitizer Tool to the clipboard and then paste that copied data into any running instance of Global Mapper by using the new Edit menu options.
- Added new right-click option to the Search->Search by Attributes dialog to allowing copying the selected features to the clipboard. Those features can then be pasted into any running instance of Global Mapper by pressing Ctrl+V.
- When triangulating and gridding 3D vector data, like LIDAR and XYZ data, made all

sample locations outside of the bounding polygon of the input data to be discarded to avoid the spurious data outside of the bounds.

- When triangulating and gridding 3D vector data that includes area features with height values, make any regions inside an area feature be flattened rather than just treating the area features as 3D lines. This allows making good elevation grids from things like buildings as well as allows easily flattening an area like a lake.
- Added option to smooth generated contour lines to improve their appearance. This option is enabled by default.
- Added option when generating contour lines to directly export them to Global Mapper Package (GMP) files rather than displaying them on the main map. This allows very large areas to be contoured when used in conjunction with the Gridding option during contour generation.
- Added ability for users to add support for additional raster and elevation export formats through a DLL-plugin architecture. See the Developers/SDK page at http://www.globalmapper.com for more details.
- Allowed Global Mapper to use up to 4GB of RAM on 64-bit Windows. On 32-bit Windows Global Mapper (like all applications) is limited to 2GB of RAM.
- Added option to rotate point labels when selecting the font to use for points of a particular type.
- **Digitizer Tool Changes**
    - Added option to the Digitizer Tool to create/flatten terrain within any selected area features that have an elevation value associated with them.
    - Allowed quick insertion of multiple vertices in selected features with the Digitizer Tool by holding down the ALT key when adding vertices. This will cause you to stay in insert vertex mode rather than reverting back to the default mode.
    - Allowed modification of insert vertex behavior to insert vertices on the existing selected line feature if the SHIFT key is held down when adding vertices. This allows you to emulate the behavior of releases earlier than v8.01 if you prefer things to work that way.
    - Allowed quick deletion of selected vertices with the Digitizer Tool. Simply use the CTRL+DELETE hotkey to delete selected vertices. This saves having to right-click and select the delete vertices option from the popup menu.
    - Added new right-click option to the Search by Attributes dialog to allow selecting all of the selected search results with the Digitizer Tool to allow further editing after closing the dialog.
    - When reversing the order of line vertices also reverse any left or right type attributes like addressing attributes.
    - Added option to add address attributes to selected point features using addressing information from the nearest line feature to those selected point features.
- **Scripting Changes**
    - Added new IMPORT_DIR_TREE command to allow importing all files in a directory tree that match a list of filename masks. This is the same functionality offered by the File->Open All Files in Directory Tree menu command.
    - Allowed the user of files with multiple polygons when using the POLYGON_CROP_FILE parameter for any of the EXPORT_* commands. If

multiple polygons are found in the specified file the polygon with the largest overlap over the loaded data will be used as the crop polygon.
    - Added ability to specify template file to use for MP export when scripting (TEMPLATE_FILENAME parameter for EXPORT_VECTOR command).
    - Added ability to specify an image id to use for MP export when scripting (MP_IMAGE_ID parameter for EXPORT_VECTOR command).
    - Made User Created Features layers be exportable via scripts run in the context of the main view window.
    - Added new SAVE_CURRENT_VIEW and RESTORE_LAST_SAVED_VIEW script commands to allow saving a restoring views from within script files.
    - Added OVERWRITE_EXISTING parameter for EXPORT_ELEVATION, EXPORT_RASTER, and EXPORT_VECTOR script commands to allow user to specify that they want to skip existing files.
    - Made passing a filename of 'USER CREATED FEATURES' to the UNLOAD_LAYER script command of a script being run in the context of the main map view unload any user-created features.
    - Added new parameter (VECTOR_ONLY) to the UNLOAD_ALL script command to allow easily unloading all of the vector layers but leaving the other layers loaded.
    - Fixed handling of export bounds and spacing when exporting DXF 3D Face, DXF Mesh, STL, and VRML files with the EXPORT_ELEVATION command.
    - Added SMOOTH_CONTOURS parameter to the GENERATE_CONTOURS script command to allow the user to control whether or not generated contour lines are smoothed to improve their appearance.
    - Added REQUIRE_WORKSPACE parameter to the GLOBAL_MAPPER_SCRIPT command to allow specification that a script/workspace file can only be run if another workspace file is already loaded.
    - Added ENABLE_PROGRESS parameter to the GLOBAL_MAPPER_SCRIPT command to allow specification that no progress reporting dialogs should be displayed while running a script. Use ENABLE_PROGRESS=NO to disable the display of progress.
- **Projection/Datum Changes**
    - Added the Cassini Malaysia (state zones), Hungarian National Grid (EOV), Lambert Cylindrical Equal-Area, RSO East Malaysia (Borneo), RSO West Malaysia (Peninsular), and Two Point Equidistant projections.
    - Added the ATS77 (Nova Scotia), Hungarian 1972 (HD72), and Indian (Nepal) datums.
    - Added the ATS77, Everest 1830 (1967 Definition), and Everest 1956 ellipsoids.
    - Added support for supplying an extra scale factor to State Plane projections. This allows for using things like grid vs. ground coordinates.
    - Modified the Timbalai 1948 datum to use the Everest 1830 (1967 definition) ellipsoid internally.
    - Fixed problem with Hotine Oblique Mercator A projection acting exactly like a Mercator projection.
    - Corrected false northing value for Lambert IV Corse projection.

    - Corrected central meridian for the Quebec MTM Zone 2 projection.
    - Added ability to specify a scale factor for Mercator projections.
    - Improved handling of some Lambert France projections in GeoTIFF files.
    - Fixed decoding of Ireland 1965 datum from TAB files.
    - Fixed problem from v8.00 release that caused some PRJ files to not be loadable.
    - Fixed problems with northing values for a handful of State Plane zones, like the NM East zone with the NAD27 datum.
    - Fixed problems with saving and restoring the Hotine Oblique Mercator B and the derived Michigan Georef projections to/from PRJ files.
    - Fixed problems saving projections using a "longitude of pole" or a "true scale latitude" parameter to new format PRJ files.
- Made the current view scale be display on the status bar.
- When running the cursor over line features with recognized addressing attributes the address under the cursor will be displayed on the status bar.
- Added support for points to have dot or square symbols of any size and color when loaded from a file. Symbol attributes now support symbol names of DOT_CUSTOM_<SIZE>_<RED>_<GREEN>_<BLUE> and SQUARE_CUSTOM_<SIZE>_<RED>_<GREEN>_<BLUE> where the <SIZE> value is the radius in pixels of the dot or square, and the <RED>, <GREEN>, and <BLUE> values represent the color to use.
- Made any text rotation and size be obeyed when loading DXF files.
- Made fixed size text and text rotation angles be saved to exported DXF files.
- Added 'inches' as a supported elevation unit.
- Made township, range, section, and meridian values be recognized from additional attribute values when exporting to Platte River Survey files.
- Made batch converting from LIDAR and TerraScan formats to gridded elevation formats work.
- Added support for additional NTF grid formats, like the LandRanger DTMs.
- Added new right-click option to the Measure Tool to save the current measure text to the Windows clipboard.
- Added option to show pixel coordinates of the current mouse location in the topmost raster layer in the status bar. This option is in the Advanced Options section on the General tab of the Configuration dialog.
- Added new option to the Advanced Options section on the General tab of the Configuration dialog to specify that default display label fonts should use the OEM character set (code page 437) rather than the ANSI character set (code page 1252). This option can be helpful if you are having problem with accented characters not displaying correctly from some data sets (those data sets encoded in code page 437 rather than 1252).
- Added support for cropping Polish MP exports to a selected area feature. Note that this will only crop point features to the selected area feature. Exported area and line features will only be cropped to the bounding box of the selected area.
- Fixed storage of contour line elevations to Polish MP files when a template file with elevation units of meters is used.
- Made Polish MP exports using template files be done in the datum specified in the

template file if the datum name is known.
- Fixed automatic map ID generator for Polish MP exports so that valid map IDs will always be generated.
- Made the Z-level value for custom area types be stored in the custom_area_types.txt file. This allows the user to customize the Z-ordering of custom area types to get them to draw where they want. Currently this requires editing the custom_area_types.txt file and editing the value in the 7th column. A value of 0 will cause the type to draw below all other area features.
- Fixed problems loading text from some DGN v8 files.
- Fixed error when loading some DGN v8 files with raster data in them.
- Made the last selected type be remembered on the Area Styles, Line Styles, and Point Styles tabs of the Configuration dialog.
- Made the 'Restore Default Settings' button on the General tab of the Configuration dialog also restore the vertical display settings to their default values.
- Made alpha channels from ECW files be used.
- Fixed conversion of offset and min/max elevation values in feet units on Alter Elevations tab of the raster Options dialog when pressing the Apply button.
- Fixed export bug when using blend modes and transparency at the same time.
- When rectifying, made holding down the CTRL key and right-clicking in either the zoomed or reference map views zoom the clicked view out to the full extents of the available data.
- When rectifying, made holding down the SHIFT key when left-clicking in the reference map view with a lat/lon projection in arc degrees clamp to the nearest 30 second interval rather than the nearest 1 minute interval.
- Fixed error in polyline flags for 3D area features exported to DXF files.
- Made the correct elevation for 3D point features imported from DXF block entities be used.
- Made HATCH and SOLID entities be loaded from DXF files.
- Allowed loading of RPF (i.e. CADRG, CIB, etc.) files with absolute file paths.
- Added support for using positioning and projection information from Fugawi JPR files.
- Added support for loading multi-patch Shapefiles.
- Added support for providing offset and scale values for STL export.
- Added option when printing to specify an extra margin. This is useful when printing to things like a PDF file that do not have any natural margins.
- Fixed problem with label settings not being saved toworkspace files when changing the label attribute of Shapefiles to '<No Name Field>'.
- Removed error about bad OziExplorer .map format when loading MapInfo .tab files from which the projection cannot be automatically determined.
- Added ability to directly load Ozi .map files to load the referenced imagery.
- Made the last used State Plane zone be remembered in the projection selection dialog.
- Added a new option ("Mark Sides of Roads with Addressing Information") to the option list at the bottom of the Vector Display tab of the Configuration dialog. If checked, any roads that are recognized to have addressing information available on one or both sides will have "hair" drawn on the side(s) of the line where that address information is available. This option can be useful for determining the coverage of your addressing data.

- Made the default face name used by labels in Global Mapper be stored in the registry and editable there. The `'HKEY_CURRENT_USER\Software\Global Mapper\DefaultFaceName'` registry key now holds that value and can be edited via regedit to change the default face name for all labels.
- Added support for loading some additional Moss/Genio format files.
- When using the File->Rectify Imagery menu command, made the control point list for each file automatically be initialized to the control points found in any associated .gcp file.
- When using the File->Rectify Imagery menu command, added an option to control whether or not rectified imagery is displayed in the reference view when rectifying multiple images. Unchecking this can speed up the process when rectifying lots of imagery.
- Fixed problems selecting some line features at some zoom levels.
- Added option to generate a PRJ file when exporting vector data to Simple ASCII Text files.
- Made information about the feature/location under the cursor be displayed in the status bar regardless of what the active tool is. For tools like the Digitizer/Edit tool the feature information will be displayed after any instructions.
- Made the 'Feature Type' value for selected features be displayed in the Feature Info dialog. The 'Description' value will only be displayed if it is different from the 'Feature Type' value.
- In the vector Search dialog, replaced the '<Feature Description>' searchable field with the more useful '<Feature Type>' field that always reflects the type of the feature.
- Fixed error introduced in v8.01 when exporting grayscale MrSID imagery to new files.
- When exporting to a Float/Grid file, write a 'cellsize' value to the .hdr file rather than 'xdim' and 'ydim' values if the X and Y sample spacing are equal. This should fix errors loading creating Float/Grid files into Arc/Info.
- Added support for loading Erdas Imagine .img files directly from archives (.zip, .tar.gz, etc.) files.
- Made additional SEGP1 format layouts be supported.
- Added an option to map catalogs to control whether or not the map bounding boxes are displayed when a map itself is not displayed.
- Added option to the Path Profile/Line of Sight dialog File menu to save the path profile to a BMP file and display it in a fixed location on the main map view. This is useful for easily getting the path profile graphic displayed along with the main map for presentation purposes.
- Fixed problems with features with HTML in their names or descriptions being exported to GPX files.
- Added band selection support for BIL, BIP, and BSQ files and their derivatives.
- Added support for additional band setups for GeoTIFF files (i.e. 5 band 8 bit-per-sample files, etc.).
- Fixed access violation with 16-bit tiled elevation TIFF files.
- Allowed custom lat/lon grid spacing to be specified in DD MM.MMMM and DD MM SS.SSSS format in addition to DDD.DDDDD.
- Make sure area features exported to KML files are closed (i.e. first and last vertex equal)

so that they will draw correctly in Google Earth when extruded.
- Improved accuracy of distance calculations.
- Made area features exported to MatLab format files be cropped to the selected export bounds rather than just including all area features that overlap the export bounds.
- Fixed positioning problems when batch converting files in a State Plane projection and using the datum override setting on the batch conversion dialog to change the datum.
- Allowed layers that have been rectified to be properly stored in map catalog files.
- Made the custom color palette on the color selection dialog for the View->Set Background Color menu command be remembered between runs.
- Made county and state boundary lines automatically be classified when imported from Tiger/Line files.
- Added option to the Vector Display tab of the Configuration dialog to "Hide Labels that are Partially Offscreen". This makes sure that you always get complete labels and is very useful if you are gridding vector data being exported to a raster format to ensure that you get a seamless set of tiles.

WHAT'S NEW IN Global Mapper v8.01

- Added new tab to the Options dialog for some multi-spectral raster files (currently only GeoTIFF files with more than 3 bands of data and Erdas IMAGINE, ECW, JPEG2000, and MrSID imagery with 3 or more bands of data) to allow controlling which bands are used for the red, green, and blue color channels during display.
- Added support to check for new releases of Global Mapper, both automatically and manually using a new Help menu option.
- Added support for feather blending raster data to a polygonal boundary rather than just along selected edges. This makes it much easier to feather blend the border of a large collection of adjacent files.
- Added option to associate a list of default attribute/value pairs with each area, line, and point classification on the * Styles tabs of the Configuration dialog. If a default attribute list is provided for a type any new features created with that type using the Digitizer Tool will automatically add those default attribute/value pairs.
- **New Import/Export Formats**
    - Added support for loading DWG files.
    - Added support for importing data from WAsP .map format files.
    - Added support for exporting lines with elevation and/or roughness values to be exported to WAsP .map format files for use in the WAsP wind analysis application.
    - Added option to export survey section (i.e. section/township/range) area features to Platte River ASCII Digitizer format files.
    - Added support for exporting gridded elevation data to PGM format grayscale grid files.
    - Added support for loading NTF-format contour files as supplied by the UK Ordnance Survey.
    - Added support for loading KINGDOM planimetric polygon files like those used by SMT (Seismic Micro-Technology) software.

- **Image Rectifier Changes**
  - Added option to shift all of the control points for a file when rectifying imagery or vector data. This effectively provides an easy way to shift a file by a given distance.
  - Added Apply button to the image rectification dialog to allow the results of repositioning a layer to be immediately seen in the reference map window.
- **Digitizer Tool Changes**
  - Added option to the Digitizer Tool to automatically create vertices at the intersections of selected line features.
  - Improved behavior of vertex insertion into area and line features so that the new vertex is inserted at the clicked location rather than the nearest point on the feature to the clicked location.
  - When inserting new vertices in selected line and area features with the Digitizer Tool, automatically select the newly added vertices to allow easy moving and joining of them.
  - Added option when creating range rings with the Digitizer Tool to create a "multi-ring" by combining the outer rings of multiple range rings into a single combined boundary.
  - When adding range rings and point features are selected, added option to add the new range rings at the selected point locations.
  - Changed behavior of moving features and vertices with the Digitizer Tool so that the move operation is terminated once the feature(s)/vertices are moved. This is to prevent inadvertently moving the features again.
  - Fixed problems in Digitizer Tool with horizontal and vertical snapping not working properly for the last vertex added to line and area features.
  - Changed "point-in-polygon" selection hot key from ALT to the 'P' key. Now if you hold down the 'P' key when left clicking to select with the Digitizer Tool, the top-most area feature containing the clicked location will be selected.
  - Made holding down the ALT key when selecting features and/or vertices automatically put you in Move mode after the selection, thus providing a quick way to manually reshape or move features.
- **Polish MP (cGPSMapper) Support Changes**
  - Added option to the Polish MP export to allow the use of a template MP file for getting the map settings to save in the newly created MP file.
  - Made addressing and routing attributes for line features be written to Polish MP files on export if they exist in the data being exported.
  - Made all point features except for known cities be written out to Polish MP files as RGN10 features rather than RGN20 features.
  - Made features in Polish MP files that do not have data at level 0 still be loaded.
- **Scripting Changes**
  - Added new EXPORT_METADATA command to the scripting language to allow exporting of text metadata for loaded layers to a file.
  - Added ability to grid exports from script files when using the EXPORT_ELEVATION, EXPORT_RASTER, and EXPORT_VECTOR script commands.

    - Added SAVE_DIST_Z_FILE parameter for GENERATE_PATH_PROFILE script command to allow specification that a file containing distance and elevation values should be saved rather than one with the XYZ coordinates of the path profile line.
    - Corrected behavior of POINT_SPACING parameter for GENERATE_PATH_PROFILE script command. It was generating one less sample point than needed.
    - Added new DEFINE_SHAPE script command. This is currently used for defining a polygonal feather blend boundary.
    - Added ability to export CDF format files from a script.
    - Allowed POLYGON_CROP_FILE to be used for EXPORT_VECTOR command. For now all line and area features will just be cropped to the bounding box of the specified polygon. Point features for some formats will actually be cropped to the polygon.
- **WMS Changes**
    - Fixed problems exporting WMS data layers to Global Mapper Package files. Now the full detail of the data layer will always be exported.
    - Removed limit on the length of WMS server URLs added through the "Select WMS Data Source to Load" dialog.
    - Added support for adding custom WMS sources with a question mark at the end of the server URL.
    - Added support for adding custom WMS sources with a service name other than WMS (this was not working properly before).
- Added option to 24-bit RGB and JPG-in-TIFF GeoTIFF exports to have any background/ no data pixels marked as transparent. This works by adding an alpha channel to the file. This might not be supported by all applications.
- Added support for loading the Z coordinates for 3D area features from most 3D shapefiles.
- Added option to the Simple ASCII Text export to write out the Y (latitude) coordinates before the X (longitude) coordinates if desired.
- Added support for cropping Simple ASCII Text exports to a selected area feature. Note that this will only crop point features to the selected area feature. Exported area and line features will only be cropped to the bounding box of the selected area.
- When exporting vector data to Simple ASCII Text files, made area features that extend outside of the export bounds be cropped to the export bounds.
- Added option on the File menu of the Path Profile/LOS dialog to save the sight line and the Fresnel zone line (if applicable) to a KML format file for display in Google Earth.
- Made overwrite of existing workspace files fail-safe by not writing out the workspace to the existing file until the workspace save is complete and error-free. This prevents any errors during a workspace save from wiping out an existing workspace file that was being overwritten.
- Added additional progress reporting when batch converting files.
- Dramatically sped up the loading of map catalog files with lots of files in different projections.
- Fixed problem with scale being slightly changed when printing to scale with a header

and/or footer.

- Made State Plane projections with NAD83 HARN/HPGN datums be properly saved and loaded from PRJ files.
- Added support for loading ECW and JPG2000 files with more than 8 bits per color channel, including elevation-based files.
- Made the TIFFTAG_SAMPLEFORMAT value be written out for 16-bit elevation TIFF files so that ESRI products can properly read them when negative values are present.
- Added option to skip files for which the projection cannot be automatically be determined when batch converting files.
- Added support for decoding some additional NITF imagery formats, in particular 2-band 16-bit per band imagery.
- Added POSGAR94 (Argentina) datum.
- Fixed bug in gridding while exporting with an overlap percentage specified that caused the overlap to not be applied to the right or bottom sides of some files when splitting up the export to a fixed ground size.
- Added support for loading MrSID imagery with more than 8 bits per color channel.
- Fixed display of ADRG/ASRP/USRP data sets with 4-bit count RLE compression.
- Added option to the Vector Display tab of the Configuration dialog to have only the border of selected area features highlighted.
- Added additional Lambert France projections to handle the newer projections with larger false northings. Made the attributes used for each of these Lambert projections be listed on the Projection selection dialog as well.
- Added support for decoding and encoding Lambert France projection codes from GeoTIFF files.
- Added support for automatically decoding projection and datum information from text metadata files accompanying Mexican topo maps.
- Fixed rare problems loading some NOS/GEO format files.
- Fixed bug cropping reprojected area features on export to MapInfo MIF/MID format files. The bug caused those areas to not be exported.
- Improved behavior of near-white colors when exporting to image-optimized palettes.
- When exporting 3D point features to DXF files, export the elevation information after the coordinate information rather than before.
- Fixed problems loading positioning information from Touratech (TTQV) .cal files where the first pixel control point is at (0,0). Also added support for automatically decoding Swiss Grid projections from those files.
- Fixed application of Fresnel zone analysis to view sheds. It had nearly no effect in the v8.00 release for view sheds (it did work properly for line of sight analysis however).
- Expanded support for FAST-format Landsat imagery to allow the direct loading of panchromatic, VNIR/SWIR, and thermal imagery without needing a _MTL.FST header file.
- Fixed problem with line vertices showing up slightly offset from the line when zoomed way in on line features that are also being reprojected.
- Improved display of 4-band Digital Globe QuickBird imagery with 8 bits per color band.
- Removed special TIFF and GeoTIFF metadata pages and placed all of the information on the main metadata page so that the information could be easily copied to the clipboard.

- Improved decoding of diacritic text from NIMA GNS point data files. The UTF-8 encoded text is now converted to the current system codepage for improved display of diacritic and other extended characters.
- Fixed very slow display of some large tiled TIFF files.
- Dramatically sped up export of TerraServer-USA data when it is being exported in a projection other than Geographic.
- Added JPEG2000 .jp2, BSB chart .kap, and Polish .MP files to the list of "Supported Commonly Used Types" list on the file selection dialog.
- Added option to CSV export to include LATITUDE and LONGITUDE columns even if the projection is not Geographic.
- Drastically reduced memory requirements when exporting vector data to Global Mapper Package files and saving generated vector features (like contour lines) to workspace files. This should eliminate all error messages when exporting package files and most when exporting workspace files.
- Added version to title bar.
- When exporting a VRML file, made the lowest vertical exaggeration setting on the slider correspond to no vertical exaggeration at all.
- Fixed bounds of exported VRML files so that they will tile properly. In addition, additional comments were added VRML file headers to describe the ground location of the data and additional digits of elevation precision were also written out in most cases.
- When using the 'Add Loaded Files' or 'Add Onscreen Files' batch conversion dialog buttons, allow the user to add files of types other than the specified input file type.
- Allowed for entry of azimuth and altitude light angle values at greater than integer precision on the Vertical Options tab of the Configuration dialog.
- Moved the Configuration button on the toolbar to be next to the Overlay Control Center button as that is a more logical grouping.
- Changed the globe button on the toolbar to launch the online TerraServer-USA/WMS data access dialog rather than going to the Find Data Online page at http://www.globalmapper.com.
- When marking a waypoint from a tracked GPS location, automatically add elevation (if available) and timestamp attributes.
- Fixed error message and lockup on Search->Search by Name dialog when searching on the last start letter (like 'Z') and having non-alphanumeric characters starting some of the strings.
- Made State Plane projections be recognized from ECW files rather than using the base projection (like Lambert Conformal Conic).
- Updated Surfer BLN export to use new comma-delimited format.
- Sped up some raster/elevation exports from map catalogs (exports that span many maps from the catalog in a single export row).
- Made elevation units for most gridded elevation exports default to the elevation units of the loaded data or, if the vertical display units are manually set to metric or statute on the Vertical Display tab of the Configuration dialog, to meters or feet respectively.
- Added option when gridding on export and naming the rows or columns with numbers to specify a step value by which to increment the row or column numbers rather than just 1.
- Made the default projection system displayed for files for which the projection cannot

automatically be determined be configurable. This default projection system can be set by saving a default.prj file in the Global Mapper installation folder.

WHAT'S NEW IN Global Mapper v8.00

- Added support for loading data from OpenGC WMS servers. This is done through the new File->Download Online Imagery/Topo Maps menu command (formerly the Download TerraServer menu command). Several sources are built-in, providing easy access to gridded elevation data for the US (NED) and the world (SRTM) as well as color imagery for the entire world. Users can easily add their own WMS data sources as well.
- Added support for exporting loaded vector data to the Polish MP format for use with the cGPSMapper application (www.cgpsmapper.com) which allows the creation of new maps for Garmin GPS units.
- Added support for loading Polish MP format files like those used by the cGPSMapper application.
- Added support for loading vector data from KML/KMZ format files.
- Added support for loading NITF (National Imagery Transmission Format) format imagery.
- Added support for loading Geodas Grid (GRD98) format elevation files.
- Added support for loading some Intergraph COT format files.
- Added support for loading CDF (GES Cartographic Data Format) files.
- Greatly improved the raster layer options by adding support for color balancing (individual red, green, and blue adjustment), linear min/max contrast stretch, setting transparency for multiple layers at a time, feather blending (see below) and cropping to native bounds or by a given number of pixels.
- Added feather blending support for raster layers to the Options available from the Overlay Control Center. This is an extremely powerful feature that allows smoothly blending raster layers with underlying layers. For example, you might have high resolution imagery on top of lower resolution imagery. With feather blending, you can smooth the sharp edge and make the transition at the border seamless.
- Added support for checking clearances with respect to the first Fresnel zone when calculating view sheds and performing line of sight analysis. This allows for a more accurate visibility calculation depending on the wavelength being transmitted.
- Added support for having labels be displayed at a fixed height in meters rather than at the same size at each zoom level. This option is on the bottom of the font selection dialog when either selecting a font for a classification on one of the * Styles tabs on the Configuration dialog or when selecting a font for a feature when editing it.
- Added option to always display the label for a particular feature or classification if labels are displayed. This option is on the bottom of the font selection dialog when either selecting a font for a classification on one of the * Styles tabs on the Configuration dialog or when selecting a font for a feature when editing it.
- **Digitizer Tool Changes**
    - Added an undo option when digitizing new features with the Digitizer Tool or drawing new measurements with the Measure Tool. Simply press Ctrl+Z and the last vertex added to the feature/measurement being drawn will be removed.

- Changed the snapping behavior in the Digitizer Tool so that snapping is disabled using the ALT key (rather than CTRL) and that snapping to vertices only is enabled by holding down the 'V' key (rather than SHIFT).
- When digitizing new features or moving existing feature or vertices using the Digitizer Tool, made holding down the CTRL key make the new location be snapped vertically, holding down the SHIFT key make the new location be snapped horizontally, and holding down both the CTRL and SHIFT keys snap the location diagonally.
- Added a new advanced selection option popup menu to the right-click popup menu for the Digitizer Tool when one or more area features is selected. This new menu has options for selecting all point and area features within the selected area(s), making it easy to select and edit features within a particular area.
- Added option to the Digitizer Tool to allow creating new line features from the boundaries of selected area features.
- When placing new range ring features with the Digitizer Tool, make the range ring center snap to existing features just like line, area, and point features do when drawing them. You can hold down Ctrl when placing the range ring to disable snapping.
- When adding areas as islands to existing features with the Digitizer Tool, prompt the user for whether or not the original areas should be marked as deleted. Previously the original areas were always marked as deleted, but this is not always desired.

- **Export Changes**
  - Greatly sped up exports to numerous binary formats, including Shapefiles, Global Mapper Grid files, and Surfer Grid files, especially when exporting to a network drive.
  - Added option when gridding data on export to have the column name be first and then the row name in the generated filename, rather than the default of row name first, then column name.
  - Added option when gridding data on export to turn off the prepending of zeroes to numeric column or row names in order to make them all the same length.
  - Added option to save a gridded file of slope values rather than elevations when exporting to a Float/Grid format.
  - Corrected text encoding recorded in exported KML/KMZ files to ISO-8859-1 rather than UTF-8.
  - Added option when exporting to KML/KMZ format files to fake an elevation for 2D area features in order to get the same draw order in Google Earth as you see in Global Mapper.
  - When gridding an export that is also cropped to a selected area feature, don't create files to any grid cells that don't intersect the selected area feature.
  - When exporting Shapefiles, remove any duplicate vertices from the exported lines.
  - Added option when exporting GeoTIFF files to generate PRJ files for the GeoTIFF files.
  - Added option when exporting 3D DXF Face files to generate the coordinates as

ECEF (earth-centered earth-fixed) rather than in whatever projection system is selected (use EXPORT_ECEF=YES parameter for EXPORT_ELEVATION command in scripting language to script this behavior).
    - Added option when batch converting to DGN format to control whether or not 3D DGN files are created.
    - Fixed problems saving some Lambert Conformal Conic based projections to ECW files. In the v7.04 release a bug was introduced which would cause some projections to not have a projection string written to a newly created ECW file.
    - Made transparency when exporting PNG files work when including either loaded vector data or the displayed scale, legend, and/or grid.
    - When exporting Simple ASCII text files, make the GM_TYPE attribute be exported when necessary if either attribute export option is enabled rather than only when the style attributes export option is enabled.
- **Rectification Changes**
    - When rectifying imagery, made snapping to nearby vector data in the Reference Map view be turned off by holding the Alt key when left clicking rather than holding down the Ctrl key. This allows both snapping and zooming to a clicked location to be done by holding down the Ctrl key.
    - When rectifying imagery, made left-clicking in the Zoomed Image and Reference Image views drop a small red dot to visually indicate the click location.
    - In the image rectification dialog, made holding down the Ctrl key increase the pan size to a half screen when panning with the edge arrow on any of the map views.
- **Projection/Datum Changes**
    - Made PRJ files be saved if possible in the newer PRJ well-known-text (WKT) format rather than the older ESRI-originated format that is no longer supported by ESRI products. There is an option to use the older PRJ format if desired on the General tab of the Configuration dialog.
    - Added support for the Bipolar Oblique Conic Western Hemisphere, Times, Old Israeli Grid, and New Israeli Grid projections.
    - Added Corrego Alegra, NID (New Israeli Datum), OID (Old Israeli Datum) and QND95 (Qatar) as built-in datums.
    - Added Clarke 1880 (Palestine), Clarke 1880 (RGS) and Sphere Radius 6371000 m as built-in ellipsoids available for use with custom datums.
    - Fixed problems using and saving the Quebec MTM projection for which support was added in the last release.
    - Made the names of state-plane zones listed on the projection selection dialog include the FIPS zone number of the zone.
    - Allowed the use of the NAD83 HARN/HPGN datums with State Plane projections.
    - Fixed problems decoding the Lambert France projections from old format PRJ files and workspaces.
    - Increased accuracy of OSGB36 datum conversions.
    - Made central meridian scale factor for Lambert Conformal Conic projections only be used in the 1SP (both first and second standard parallels the same) case since it can only be unity (1.0) in the 2SP case.

    - Fixed decoding of UTM zones in the Southern hemisphere from some new format PRJ files.
    - Fixed Transverse Mercator projections when used with datums based on perfect spheres (these would only have been custom datums based on a spherical ellipsoid).
- Added option to custom shader dialog to allow initialization of a custom shader from a Surfer CLR shader palette file.
- When creating or editing a map catalog and using the "Add Loaded Files" or "Add Onscreen Files" buttons, made files from other loaded map catalogs be added as well if they are not already in the map catalog being worked with.
- When saving a workspace with any gridded elevation data loaded, made the current shader and other vertical display settings be written to the workspace so that the view will be the same when the data is reloaded.
- Added new advanced options list to the General tab of the Configuration dialog to allow selecting advanced options like treating DXF INSERT entities as points, automatically adding custom types for DXF layers, exporting old format PRJ files, preferring world file coordinates over embedded coordinates for GeoTIFF files, and prompting for whether or not 16-bit BIL data is imagery or elevation data.
- Added SAVE_SCALE_AND_LEGEND parameter to the EXPORT_RASTER script command to allow saving the distance scale and/or elevation legend to generated raster format files.
- Added POINT_SPACING parameter to the GENERATE_PATH_PROFILE script command to allow specifying the spacing between sample locations along a path profile rather than the number of points.
- Fixed reading of Shapefiles with PolygonZ and PolygonM shape types which don't have Z or M values for all features.
- Allowed specification of the default elevation units to use for vector data with elevations from the Options button of the Overlay Control Center. This elevation units value will be used for any elevation values associated with vector features in that layer that do not explicitly contain a unit identifier (i.e. "ft" or "m").
- When saving/updating feature measure information for polygon features that have islands/holes, include the area of the island features as a separate ISLAND_AREA attribute. Also subtract the area of those islands away from the total polygon area stored in the ENCLOSED_AREA attribute to give a true representation of the actual area covered by the polygon.
- Greatly improved the load speed and reduced the memory requirements for most BMP format files.
- Improved auto-assignment of type names based on feature descriptions when loading DXF files to handle type names with spaces or underscores in them.
- Fixed error when saving a workspace file containing a map catalog with auto-collar cropping enabled.
- Fixed problems decoding NMEA GPS streams where the only valid sentence is the $GPRMC sentence.
- Fixed problem with the label background for labels set to display with filled backgrounds being white rather than the current view background color in some instances when raster

or gridded elevation data is also being displayed.
- Made the size of the vector search dialog be remembered between runs.
- Allowed ECW and MrSID files without embedded positioning information to use positioning information from additional sources, like world files.
- Replace underscores with spaces in waypoint names loaded from CompeGPS format files.
- Made symbols for waypoints from CompeGPS files be automatically set if the symbol name for the waypoint matches a Global Mapper symbol name.
- Fixed restoring of default drawing styles for area and line features from the tabs of the Configuration dialog. This has been broken since the v6.08 release.
- Added support for reading coordinates from world files where the coordinates are separated with tabs rather than being on separate lines.
- Made the list of layers in the Overlay Control Center be scrollable with the mouse wheel.
- Corrected image registration via CompeGPS IMP files with control points in multiple UTM zones or in a UTM zone in the Southern hemisphere.
- Improved decoding of CompeGPS IMP files using Lambert Conformal Conic projections.
- Sped up the import of large DTED files.
- Made symbol and type lookups by name work properly for types and symbols with accented characters.
- Don't allow multiple custom shaders with the same name to be used.
- Fixed loading of Arc ASCII Grid files with lines over 256 KB in length (up to a max of 2MB per line).
- Fixed bug with display of raster layers texture mapped over loaded elevation layers that do not use the shared default shader.
- Fixed bug in the encoding of area features in DLG-O files and allowed correct reading of incorrectly encoded DLG-O files with area features.
- Fixed display of tiled 16-bit grayscale TIFF imagery.
- Fixed recording of GPS tracklog when attached GPS device always reports an elevation of 0.
- Fixed auto-contrast adjustment for some large images with 16 bits per color channel.
- Made rotation values from BLW files used to position BIL files be used.
- Added option to Vector Display tab of the Configuration dialog to allow hiding any extra text displayed below road icons, like alternate names for the road.
- Added option to the General tab of the Configuration dialog to control whether or not grid lines should extend beyond the edge of loaded data.
- Added support for dragging Global Mapper Script (GMS) files onto a running instance of Global Mapper and have them be run.
- Added support for 16-bit per color channel separated (Geo)TIFF files with more than 3 bands of data.
- Improved rendering of some lat/lon data that crosses the anti-meridian (180 E/W), such as range rings.
- Added option to the Measure Tool to have measured lines and areas be drawn along great circles rather than on straight lines (all measurements are always along great circles).
- Fixed rare problem with min and max values being treated as invalid from some Surfer

Grid files.
- Made national wilderness and wildlife areas in 100K SDTS DLG files be detected and automatically classified as "National Park (Other)".
- Improved positioning of imagery using Ozi .map files that reference the Swiss Grid projection.
- Corrected positioning of imagery using Ozi .map files that specify a "map scale factor" (MSF) value other than 1.
- Added support for reading text from MTEXT entities in DXF files.
- Made link elements in GPX files be saved as attributes in the created features.
- Fixed very rare lockup when creating an elevation grid from 3D vector point features or during ASCII file import.
- Fixed problem with attribute tags in exported DGN files not being recognized by MicroStation.
- Added Gridding tab when generating contours to allow breaking up the contour generation into multiple smaller pieces.
- Improved the visual appearance of gridded elevation data along the edges of the data when interpolating (the visible seem is reduced or disappears altogether in some cases).

WHAT'S NEW IN Global Mapper v7.04

- Added KML/KMZ export function. This allows any loaded vector data to be exported to a KML/KMZ format file for use in Google Earth.
- Fixed problem on some systems that would cause the application to disappear or crash when attempting to select a new file for loading or saving. This problem occurred on Windows XP SP2 systems which also had Adobe Acrobat Reader v7 installed. Apparently the installation of Acrobat Reader changed some built-in Windows behavior in a way that broke Global Mapper (and several other applications).
- **DGN Import/Export Changes**
    - Allowed batch conversion of vector data to DGN format files.
    - Allowed export of DGN format files from Global Mapper scripts using the EXPORT_VECTOR command.
    - Made tag values be read in from DGN files and stored as attributes.
    - Made point features stored as 0-dimensional lines in DGN v7 files load correctly.
    - When exporting DGN files, made the current view background color be saved as the DGN background color.
    - When exporting DGN files, made the correct unit conversion and type values be used rather than reporting all units as meters.
    - When exporting DGN files, made the level number used for exported features that originally came from a DGN file be maintained.
    - When exporting DGN files, made text features be exported for line and area features that have labels.
    - When exporting DGN files, made text labels be sized proportionally to the font size used for the label in Global Mapper. The export options dialog also has an option to scale the text to make it larger or smaller and still maintain the proportionality.

    - When exporting DGN files, made generation of a 3D DGN file optional.
    - When exporting DGN files, added an option to also generate a PRJ file containing the native projection of the coordinates in the DGN file.
    - When exporting DGN files, added an option to specify the unit resolution to use, such as 100 to use centimeters when the export ground units are meters.
- Allowed saving of the 3D view to images of a size other than the 3D view window size on systems that support this operation. Many older or underpowered video cards will not support this operation, but newer video cards with the latest drivers should be ok.
- Added support for loading Japanese DEM (JDEM) .mem files.
- Added support for loading SEGP1 seismic shotpoint format data files.
- Added support for loading CompeGPS RTE, TRK, and WPT format files.
- Added option when batch converting to a zoned projection, like UTM or Gauss Krueger, to "Automatically Select the Best Zone" for each file being converted, allowing easy conversion of files that span multiple zones. The auto-selection option will be at the top of the zone list for those zones where it is available.
- **Export Gridding Changes**
    - Added option when gridding data on export into adjacent tiles to make those tiles overlap by some percentage of the tile size. This is to allow more easily overlaying the data in other non-mapping applications, like Photoshop.
    - Added option when gridding data on export and separately naming tile rows and columns to specify the start number or letter for the rows and/or columns rather than just using 1 and 'A'.
    - Added option when gridding data on export into a specified number of rows and columns to crop the right and bottom grid cells to the specified export bounds. This may make the grid cells not all have the same size, but will prevent extraneous data from appearing on the right and bottom edges.
    - Changed naming of numeric rows/columns when gridding data on export to make the numeric name for every tile be padded with 0's to the maximum length of the numeric label for any row/column. For example, if 100 columns of tiles were being exported, the columns names would go 001, 002, …, 100 rather than 1, 2, … 100.
    - Made most settings on the Gridding tab of exports be remembered between runs.
    - Added option when gridding data on export to not export grid tiles where the destination file already exists. This is useful for continuing a canceled export, or re-exporting just some tiles that you want different data in. Simply delete the tiles that you want to re-export, then do the export again with the option to skip existing files checked.
    - Added option when gridding data on export to specify a prefix to apply to the column and row names when separately naming rows and columns.
- When loading Shapefile, MapInfo, and DXF format files, use the layer name/attributes to try and auto-classify features.
- When exporting Shapefile and MapInfo MIF/MID features and including the description as an attribute, also include the classification as a GM_TYPE attribute if the description for any of the feature being exported is not the default of the classification name.
- Added built-in support for the Quebec MTM projection.

- Added support for western hemisphere zones when using the Gauss Krueger 6-degree zone projection.
- Added built-in support for the LUREF (Luxembourg) datum.
- Improved accuracy of the Dutch Grid projection and the Dutch (RD) datum.
- When performing cut-and-fill volume calculations, also calculate and display the surface area that needs cut and filled respectively.
- Made the "Path Details" dialog for a 3D path profile display the along-ground distance (i.e. distance with elevation changes taken into account) as well as the minimum and maximum elevation values along the path.
- Added support for loading USRP data sets (ASRP data with UTM coordinates).
- Made all appropriate border pixels be marked as transparent in ADRG, ASRP, and USRP data sets.
- Added option to Simple ASCII Export to make style attribute export be controlled separately from data attribute export.
- Added button to the custom shader edit dialog allowing the elevation value for an existing elevation/color range be changed.
- Added option to the Digitizer Tool when multiple point features are selected to identify any point features that are within a user-specified distance of other selected point features. This is helpful for finding duplicate points.
- Display the height of any gridded elevation data in the status bar as you move the cursor around, even if the cursor is near vector data (the height will be appended to the nearest vector feature description).
- When placing new point/text features or moving a single point/text feature with the Digitizer Tool, make the point snap to existing features just like line and area features do when drawing them. You can hold down Ctrl when placing the point to disable snapping.
- Made CSV files created by the Lowrance SonarViewer software be automatically detected and loaded rather than prompting the user for input parameters.
- Added option to CDF export to allow exporting coordinates in either the current projection system or lat/lon.
- Allowed DTED files with invalid column numbers in the data record to be loaded.
- Added support for loading Geosoft Grid files with right-handed vector orientation.
- Added automatic detection of world files that have an extra .txt appended to the filename.
- Improved loading of ATTRIB values from DXF values.
- Improved export of point/text features to DXF files.
- Fixed loading of 3D LINE entities from DXF files where the start and end points had different elevations.
- Made 3DFACE entities be loaded from DXF files.
- Added option to use the display label as the layer name when exporting to DXF files rather than the description/type if a layer name is available for a feature.
- Allowed "Crop to Selected Area Feature" option to be used when generating contours.
- Added option when generating contours to control whether or not unit indicator suffixes should be appended to labels for the generated contour features.
- Added INC_UNIT_SUFFIX parameter to the GENERATE_CONTOURS script command to allow specification of whether unit indicator suffixes should be appended to the labels for the generated contour features.

- Added Sphere Radius 6371204 m as an available ellipsoid for adding custom datums.
- Fixed problem with custom datums created by the user being written out to new files, like GeoTIFFs, as the Adindan datum.
- Fixed incorrect loading of some MSI Planet format height files (they would appear garbled).
- Fixed errors loading some GPX files with extremely long text strings in them.
- Fixed problem with missing lat/lon grid lines in some projections where the lat/lon grid is not valid over the entire data bounding box.
- Fixed automatic removal of collars for files with very curved lat/lon boundaries, such as the Antarctica DRGs.
- Fixed loading of attributes from MIF/MID files when one of the attribute names starts with "Index".
- Fixed errors trying to batch convert raster data with both the "Use Other Source Files As Filler" and "Auto Adjust Contrast" options enabled.
- Improved rectification based on an OziExplorer .map file when that .map file has a UTM grid and each control point has both lat/long and grid coordinates or the .map file has control points that are marked as excluded.
- Allowed ground control points specified for rectification with the IMPORT script command to be specified in a projection other than the specified projection for the file being rectified. The use of either the GCP_PROJ_NAME or GCP_PROJ_FILENAME parameters will cause the control points to be projected automatically to the file projection before rectification occurs.
- When loading LIDAR LAS data, save the class of each sample point as an attribute.
- When batch converting from LIDAR LAS data to other vector formats, add an option to only include sample points classified as "ground shot points" in the output.
- Don't display POLYLINE entities from DXF files that are marked as 3D polygon meshes or polyface meshes.
- When loading generic ASCII files with quoted fields, make sure the quoted fields are properly treated as a single field and that the quotes are removed for all fields. Also treat back-to-back double quotes as a single quote mark in the text that doesn't act as a field delimeter.
- When loading generic ASCII text files and using column names from the first line of the file as attribute names, don't include attributes from non-coordinates lines.
- Fixed problem introduced in v7.02 release with saving Transverse Mercator projections to ECW files (the projection name was not being saved for some users).
- Allowed view shed calculations to have a radius as small as one thousandth or a mile or kilometer rather than the previous minimum of one tenth of a mile or kilometer.
- Fixed some printing issues and improved printing performance when printing to large paper sizes.
- Added a registry key to allow specifying that positioning information from TIFF world files, if available, should be preferred over the positioning data stored within TIFF file headers. If you create a HKEY_CURRENT_USER\Software\GlobalMapper\TIFFPreferTFW DWORD value with the value set to 1, then the world file positions will be preferred.
- Added support for reading and writing oblique stereographic projections from/to

GeoTIFF files.

- Added support for reading and writing Gauss Krueger (6-degree zones) projections using the Pulkovo 1942 datum from/to GeoTIFF files.
- Added support for reading and writing the Potsdam/DHDN datum from/to GeoTIFF files as well as Gauss Krueger Germany (3 degree zones) projections with that datum.
- Added checkbox to the ASCII import file to allow using the same configuration for all files during that load or batch convert operation.
- Allowed positioning data from Ozi .map and CompeGPS .imp files to be used to position ECW files that do not contain embedded positioning information.
- Corrected positioning of some non-WGS84 MapTech maps. In some cases the wrong datum would be used. Now if there is any doubt the user is prompted to select the correct projection.
- Made user-defined projections be automatically decoded from MrSID files.
- Fixed export of NAD83 datums to Erdas Imagine format files.
- Made French Lambert projections be decoded and encoded from/to ECW files automatically.
- Improved positioning of NOS/GEO format charts by positioning them using the specified native chart projection if recognized.
- When using the GENERATING_CONTOURS script command, allowed negative intervals to be specified if the SINGLE_LEVEL_ONLY=YES parameter is specified.
- Fixed half pixel shift and other positioning problems when exporting to new Float/Grid format files.
- Fixed errors loading text from some single-precision E00 files.
- Dramatically sped up the calculation of auto-contrast statistics for large MrSID files.
- When loading MapInfo MIF/MID format files, don't set any numeric fields to have a value of 0 when their value is actually empty.
- Fixed bug from v7.03 release that could cause discontinuities in rectified imagery that used the triangulated rectification method.
- When displaying feature information for polygon features that have islands/holes, include the area of the island features as a separate item in the Geometry section of the Feature Info dialog. Also subtract the area of those islands away from the total polygon area to give a true representation of the actual area covered by the polygon.
- Improved compression of 24-bit RGB GeoTIFF files created by Global Mapper that are created with the LZW compression option.
- Improved consistency of multiple view sheds calculated from the same center point with the same sample spacing but different radii when the specified sample spacing is much larger than the spacing of the elevation files that are used.
- Sped up calculation of view sheds when the elevation data being used comes from a map catalog or Global Mapper Grid files.
- Sped up contour generation when the elevation data being used comes from a map catalog or Global Mapper Grid files.
- Added support for specifying a scale factor for Lambert Conformal Conic and Stereographic projections.
- Significantly sped up export to any raster format using a palette, such as palette-based GeoTIFF or PNG exports.

- Added option to do case-sensitive searches with the Search->Search by Attributes menu command.
- Made map catalogs be exportable to Global Mapper Package files.
- Fixed orientation of GPS heading arrow when the display projection is one in which north is not necessarily straight up.
- Reduced memory usage for E00 files with lots of attribute values.
- Fixed calculation of PERIMETER and ENCLOSED_AREA values for some range rings that had incorrect values stored.
- Fixed decoding of UTM zone 60 projections from NASA LandSat .met files.
- When rectifying data with vector data displayed in the Reference pane, made clicking near a vector feature automatically "snap" to that feature to assure exact matches.
- Made statistics (STX) files be generated for elevation BIL file exports.
- Added SHOW_3D_VIEW command to the scripting language to allow scripts and workspaces to bring up the 3D view window.
- Added option to generate XYZ grid files in row-major order.
- Added option to anti-alias pixels (interpolate) when batch converting between raster formats.
- Fixed rare problems loading some portions of Arc Binary Grid format files (technically, some 32-bit RLE encoded tiles with very large values were incorrectly decoded).
- Fixed problem with labeled areas exported to Landmark Graphics ASCII format files have two TEXT labels exported.
- Made image-optimized palettes always contain white and/or black if those colors are in the image being exported. This makes collars stay the color they are supposed to be.
- Made tracking of Garmin USB GPS devices work for newer devices, like the SP2720, that send some extra information when first connected.
- Added warning to exports when a large amount of TerraServer data would be exported to explain that it could be very slow and give the user a chance to cancel the operation.

WHAT'S NEW IN Global Mapper v7.03

- **New Import Formats**
  - Added support for loading DGN v8 and later format files.
  - Added support for loading MapTech format files, including encrypted BSB files and other MapTech topo maps and aerial navigation maps.
  - Added support for loading Idrisi format raster and elevation files.
- **New Export Formats**
  - Added support for exporting loaded vector data to DGN format files.
  - Added support for exporting loaded data to Erdas Imagine IMG format files.
  - Added support for exporting loaded data Idrisi format files.
  - Added support for exporting 8-bit and RGB GeoTIFF files with LZW compression. LZW compression typically results in much better compression that the default methods, but may not be supported by all software applications.
- **Drawing Changes**
  - Significantly improved the display of raster and gridded elevation data at intermediate zoom levels by always anti-aliasing the display when not zoomed

into the pixel level of the data and not zoomed out so far that it doesn't matter much. There will be a slight performance hit for this, but the improvement in display quality seems worth it.
    - Made pressing the ESC key during a draw abort the draw as soon as possible.
- **Projection/Datum Changes**
    - Improved accuracy of the NAD27 (Canada), AGD66, AGD84, and NZGD49 datums by using the NTv2 grid shift method for sub-meter datum transformation accuracy.
    - Added generic NAD27 datum that will automatically use the most accurate local datum conversion based on the location being converted.
    - Added support for the Miller Oblated Stereographic projection.
    - Allowed use of the NZGD2000 datum with the New Zealand Map Grid projection.
    - Made additional datum codes, like those for the NTF datums, be recognized for GeoTIFF files.
    - Made ETRS89 datum be recognized in additional spellings from PRJ files.
    - Corrected small error when transforming the Rome 1940 datum to other datums.
    - Added Clarke 1880 (Benoit) as an available ellipsoid for adding custom datums.
- **View Shed Changes**
    - Added option to the view shed tool to find a view shed of just where a beam will hit the terrain. A start and end transmission angle are specified in addition to the transmitter height in order to find the beam intersection points.
    - Added option to the view shed tool to specify a minimum distance from the transmitter to perform the view shed analysis.
- Improved loading of DXF files that have features in the BLOCKS section of the file.
- Prompt users to unload all loaded data when loading workspace files rather than automatically unloading all loaded data.
- Added option to batch geocode addresses from a file from the Search->Find Address menu command.
- Added support for gridding the export of Simple ASCII Text, VRML, and Zmap Plus Grid files.
- Added support for reversing the order in which rows and columns are named when gridding files on export.
- Made the path profile/line of sight dialog maintain its size between showings, preventing the user from having to continually resize it to get the size they want for different path profiles.
- Added option to the Vector Display tab of the Configuration dialog to allow an arrow to be drawn along line features in the direction that they travel.
- Fixed scaling problem when exporting vector data to a raster file using the EXPORT_RASTER command from a script file.
- Made custom symbols from .ico files draw in their actual size instead of always using the default system size of 32x32.
- Added new built-in point symbol, "Dot – Yellow".
- Fixed problems loading some GPS TrackMaker files that have no waypoints in them.
- Made degree symbols display correctly on Asian versions of Windows that weren't fixed

in the earlier update.

- Fixed problems with render progress on status bar not working properly with map catalog files.
- Fixed problems with some maps that result in multiple layers, like ADRG files, in map catalogs.
- Allowed custom per-layer shaders to work properly with map catalogs containing elevation data.
- Fixed problems with some iso-height area contours not being generated in some rare cases when generating contours.
- Fixed loading of package files containing elevation data from workspaces.
- Fixed occasional problems with missing outer row and/or column of data when exporting a raster or elevation file and cropping to a selected, rectangular area feature.
- Fixed problems with elevation shading and display of the elevation legend when negative scaling factors are used on the Alter Elevations dialog.
- Made up to 3 decimal digits of precision be used when saving elevation values to many ASCII formats.
- Added option to remove archive files (like .zip and .tar.gz) from the list of files to batch convert/reproject by right-clicking on the batch convert file list and selecting the appropriate option.
- Added option to add files to the list of files to batch convert/reproject from a text file containing a list of full paths to files. To access this option, simply right click on the file list in the Batch Convert/Reproject dialog and select the appropriate option.
- Added option to add files to a map catalog from a text file containing a list of full paths to files. To access this option, simply right click on the map list in the Map Catalog dialog and select the appropriate option.
- Corrected half-pixel offset in placement of MrSID files with embedded coordinate information.
- When exporting Shapefiles, do not export line features that are at a point (all vertices coincident) or area features that are a point or a 2-vertex line.
- When exporting Shapefiles, make sure that lines that get cropped to the export bounds maintain their original direction.
- Made attributes for which none of the features being exported have a non-empty value still be exported to DBF files that are created with Shapefiles.
- Allowed confirmation prompt when closing loaded overlays from the Overlay Control Center to be disabled so that it won't be shown again.
- Fixed out of memory errors when zoomed in really far on some MrSID files.
- Fixed loading of E00 files with empty annotations.
- Made deleted holes in area features not be exported to DLG-O format files.
- Added support for tracking NMEA GPS devices that use $EC* sentences rather than $GP* sentences.
- Fixed determination of State Plane projection from Erdas Imagine .img files that use a negative zone number in the header.
- Fixed problem with STL, 3D DXF mesh, and 3D DXF mesh exports that would cause a one sample gap between gridded files when exported.
- Added right-click option to the Search by Attributes dialog to allow selecting all search

results.

- Made files opened by dragging them onto Global Mapper be added to the list of recently used files under the File menu.
- When dragging multiple files onto Global Mapper to load them, make the "Use Selected Projection for All" checkbox option work if the user is asked for a projection.
- Added a registry key to allow overriding where temporary files, like extracted archive contents and downloaded TerraServer tiles, are stored. If you create a HKEY_CURRENT_USER\Software\GlobalMapper\TempDir string value with the folder that you want the temporary files to be based in, that folder will be used the next time that you run Global Mapper.
- Added option to save the elevation legend in the main view to a BMP file by right-clicking on it and selecting the appropriate option.
- Added option to control whether or not unit labels (e.g. "m" or "ft") are displayed on the elevation legend. This setting can be changed by right-clicking on it and selecting the appropriate option.
- Fixed problem with grid line labels being cropped at the bottom when footer strings were used during printing.
- Made new Explorer-style dialogs be used for all file selection.
- Fixed crash when displaying metadata for map catalogs that contain elevation layers.
- Fixed errors loading some tiled TIFF files with separated color channels.
- Made dot symbols look better when printed.
- Made the filling in of small gaps work when exporting DEM files with arc degrees as the current view/export units on the Projection tab of the Configuration dialog.
- When creating area features from selected line features with the Digitizer Tool, only prompt for name, attribute, and style information once, then use that information for all remaining areas created from the selected lines if no other information is available from the lines making up the area.
- Made the count of selected features appear in the status bar when the Digitizer Tool is active and you are not actively working with the selected features.
- Corrected decoding of New Zealand Map Grid projections from ECW files. They were being decoded as a closely-approximated Transverse Mercator projection.
- Fixed loading of some ASRP-format data files.
- Fixed errors loading DLG-O files with area features and non-contiguous element IDs for lines (these are very rare).
- When exporting DXF format files, made area features be fully cropped to the specified export bounds rather than just exporting in whole any area that intersects the export bounds.
- Fixed ordering of data written to GPX files to make sure that really picky applications, like Garmin's MapSource, can always read them.
- Fixed problem when doing multiple line connection operations from the Search by Attributes dialog that would result in extra long lines (they would loop over themselves) after the first line connection operation.
- Made "Longitude of Pole" attributes for Polar Stereographic projections be saved and read from PRJ files.
- Added support for a BOTTOM_UP parameter in BIL file headers to specify that the data

starts at the lower-left rather than the top-left. Just add a line with the text "BOTTOM_UP Y" to the .hdr file to flip the data vertically.
- Added a LAYER_DESC parameter to the GENERATE_CONTOURS script command to allow the name of the generated contour layer to be changed from the default.
- Fixed problem with point features getting the wrong attributes from some E00 files.
- Made holes in area features maintain the descriptions of their parents when exported to ASCII text files.
- Allowed minus signs, dollar signs, and underscores to be used at the start of labels when exporting to DXF format files. Previously those characters were removed from the start of lines to prevent errors. Now a space is just inserted before those characters to get rid of the errors.
- Added support for a LABEL_ON_LINE parameter in ASCII text files for specifying that labels for a line feature should be centered on the line.

WHAT'S NEW IN Global Mapper v7.02

- Added option on Vector Display tab of the Configuration dialog to allow more control over the order that vector features are drawn in. You can now select to have the layer order in the Overlay Control Center take top priority for vector data, allowing vector layers to be drawn under raster layers and also allowing explicit forcing of vector layer draw order.
- Added support for searching on address in the US under the Search menu.
- Added option to download TerraServer data near an address.
- Made transparency and translucency in PNG files be used.
- Added support for creating transparent PNG files (this is now the default).
- **Digitizer Tool Changes**
    - Improved ease of digitizing lots of area, line, and point features by making the Digitizer Tool stay in the creation mode after creating a feature rather than forcing you to re-select the feature type to create each time. You still just need to right-click to cancel the current operation.
    - Added display of the number of points digitized so far when drawing a new line or area feature with the Digitizer Tool.
    - Added option to reverse the order of the vertices in selected line features using the Digitizer Tool.
    - Added option to find unconnected endpoints in selected lines with the Digitizer Tool. This provides an easy method of identifying connectivity problems in loaded data.
    - Fixed creation of duplicate attributes when editing multiple features at a time with the Digitizer Tool and adding a new attribute which already exists in some of the features being edited.
    - Added option to measure cut-and-fill volumes to the right-click menu when a single line or area feature is selected.
- **New Supported Import/Export Formats**
    - Added support for exporting loaded vector data to Lowrance USR format files for use in Lowrance GPS devices.

    - Added support for loading LIDAR data from TerraScan .bin and .ts format files.
    - Added option to print to (Geo)TIFF format files.
    - Added ability to batch convert to Global Mapper Package files.
    - Added support for exporting loaded elevation data to Optimi Terrain format files.
- **Projection/Datum/Unit Changes**
    - Vastly improved accuracy of RT90 (Sweden) datum transformations.
    - Added Indonesia 1974 and Bukit Rimpah datums.
    - Added support for using the French angular unit "grades" with the Geographic projection.
    - Fixed rare problems projecting between a State Plane projection and a Lambert Conformal Conic projection.
    - Fixed loading of Erdas Imagine .img files with embedded projection information. This was broken in the v7.01 release.
    - Added support for loading and saving Southern Transverse Mercator projections in ECW files.
    - Added support for using projection and positioning information from .TAB files for ECW files.
    - Added support for decoding New Zealand Map Grid projections from .TAB files.
    - Added option to write an invalid datum code to DEM files when exporting with a view/export datum set to one that is not supported by the DEM format.
    - Do not allow modifying the Origin Latitude for Mercator projections since it is not used (the latitude origin is always the equator for Mercator).
    - Fixed saving of some projections to MapInfo TAB files. Some projections either could not be written at all or if they had a central meridian scale factor parameter it would always be set to 1.0.
    - Made projection information from supplemental files (like .prj files) be used if available for GeoTIFF files that do not contain projection information internally rather than always asking the user to select the projection in that case.
    - Added GRS 1967 (Indonesia 1974), Sphere Radius 6378388 Meters , and War Office (McCaw 1924) as available ellipsoids for adding custom datums.
    - Fixed name of the "Everest 1830" ellipsoid in the custom datum dialog. It was being incorrectly listed as "Everest 1930".
- Made Ctrl+Right Click in the Zoom Tool restore the last zoom scale.
- Made the name of the map that a vector feature is in always be displayed in the Feature Info dialog for the feature.
- Added button on the General tab of the Configuration dialog to allow restoring all settings to their default values.
- Added support for tracking GPS devices on COM ports up to COM64 (previously the highest support serial port was COM16).
- Made the COM port and baud rate settings for serial GPS devices be properly remembered between sessions.
- Added shortcut key (Ctrl+T) for starting and stopping the tracking of a connected GPS device.
- Made font information about labeled features be saved in Simple ASCII Text files exported with the "include attributes" option set.

- Added support for using new font attributes when reading generic ASCII text files. See the User's Manual section for that menu command for details on the new supported attributes.
- Added ability to combine line features in the Search by Attributes dialog. Just select the lines to combine, then right click on them in the list and select the combine option that appears.
- Fixed errors loading label points from some .e00 files.
- Added support for rectifying ECW and JPG2000 files.
- Added support for loading TAB-referenced raster files which do not have the same base name as the TAB file. You must select the TAB file to load for this to work.
- If a color palette is specified in a TIFF header for files with a grayscale photometric interpretation, use the color palette rather than creating a grayscale one. Apparently some products, like ArcGIS, will create TIFF files in this way for some reason.
- Made TEXT feature labels from MIF/MID files be read in and used.
- Made saving a path profile to a BMP file save a bottom-up rather than a top-down bitmap since some applications (including Global Mapper) can't read top-down bitmaps.
- Fixed problems batch converting to Shapefile format and exporting to the "source file" folder when the input files are either archives (e.g. .zip or .tar.gz files) or the output is being gridded.
- When using the "Add Loaded Files" or "Add Onscreen Files" buttons in the batch conversion dialog and map catalog files are loaded, made the maps referenced by the map catalog be added to the convert list if they are of the right type.
- Fixed loading of attributes from some DBF files that had padding bytes after the DBF header.
- Added support for decoding DMS lat/lon values which use a hyphen as the separator.
- Sped up the export of raster and elevation files when only a subset of a large number of files is being exported.
- Fixed really slow drawing of some rotated BSB files.
- Fixed vertical flip of NTF-format grid files.
- When exporting MapInfo MIF/MID format files, made area features be fully cropped to the specified export bounds rather than just exporting in whole any area that intersects the export bounds.
- Made line and area border widths be stored correctly in MapInfo MIF/MID files.
- When using area features with elevations as obstructions for view shed calculations, make the tested receiver heights inside area features just be based on the terrain and only use the area heights as obstructions. This makes it easier to simulate things like wooded areas blocking reception within those areas and not just beyond them.
- Added Landsat True Color links from resmap.com to the File->Open ECW File from the Web menu dialog.
- Added support for reading in 3D DXF line features and saving the separate elevations for each vertex rather than using the elevation of the first vertex for the entire line.
- Added ability to create regularly spaced tiles of elevation grids from 3D vector data when right-clicking on vector layers in the Overlay Control Center and selecting the option to create an elevation grid from the data. This makes it easier to deal with very large data sets that cannot be gridded all at once without running out of memory.

- Added support for Global Mapper Package files larger than 2GB in size.

WHAT'S NEW IN Global Mapper v7.01

- Made the middle mouse button drag the map in all of the tools and not just the Zoom tool.
- Added option to use an elevation shader other than the shared elevation shader selected on the toolbar for rendering an elevation layer. This option is available from the Options button in the Overlay Control Center.
- Added option to grid (i.e. tile) data during batch conversion.
- Made decimal digit fields exported to Shapefiles display as decimal numbers by default when loaded into other applications rather than displaying just as whole numbers.
- Added and/or improved metadata display from the Overlay Control Center for most file types. The improved metadata display allows copying the metadata to the clipboard and easy viewing of projection information.
- **Projection/Datum/Unit Changes**
    - Added support for the NAD83 HARN/HPGN datums.
    - Improved accuracy of NAD27 Alaska, Old Hawaiian Mean, and Puerto Rico datums by adding support for using the NADCON datum conversion methods for those datums.
    - Improved accuracy of NTF France datums by adding support for using variable grid shifts depending on the location within France.
    - Added support for creating custom datums that use the 7-parameter Bursa-Wolfe datum transformation method (previously only the 3-parameter Molodensky method was supported).
    - Added built-in support for the Irish Grid projection.
    - Added support for yards as a linear unit.
    - Added support for millimeters as an elevation unit.
    - Corrected detection of UTM zones in the Southern Hemisphere from old-format ESRI PRJ files.
    - Improved decoding of some projections from OziExplorer .map files.
- **New Supported Formats**
    - Added support for loading NTF-format grid files, such as those used for elevation data in Great Britain.
    - Added support for loading some FAST format imagery files, such as those used for L7A Landsat data in some parts of the world.
- **Digitizer Tool Changes**
    - Made holding the X and Y keys when moving vertices or features with the Digitizer Tool, clamp the move horizontally or vertically.
    - When creating new line or area features with the Digitizer Tool, the length and enclosed area (if applicable) will be displayed in the status bar as the new feature is drawn.
    - When moving or joining vertices of line or area features with the Digitizer Tool, the length and enclosed area (if applicable) will be displayed in the status bar as the vertices are moved.

- **Measure Tool Changes**
  - When creating a new line feature from a measurement in the Measure Tool, set the length of the measurement to also be the default display label.
  - When displaying length and other measurement strings, such as with the Measure Tool, remove any trailing zeroes from the length to make it more compact.
- **Image Rectification Changes**
  - Added new hotkeys to the image rectification dialog. Now Alt+R will act like pressing the "Update Selected GCP" button, Alt+Q will move the GCP list selection up, and Alt+Z will move the GCP list selection down.
  - Improved the crosshair cursor used in the Zoomed and Reference views of the Image Rectification dialog.
  - Improved the symbols used in the image rectification dialog for displaying ground control points to make it easier to see the data behind the control point.
- **Map Catalog Changes**
  - Added the ability to display metadata about maps in a map catalog by right-clicking on the map in the map list in the Map Catalog dialog and selecting a popup menu option to display metadata about them.
  - Added the ability to have map catalogs be displayed within a range of map scales.
  - Fixed problems using files with Oblique Mercator projections in map catalogs.
  - Fixed problems with some files, particular packages with multiple data layer, being included in map catalogs.
- Corrected placement of Erdas Imagine .img files with a UTM projection in the Southern Hemisphere.
- Added support for getting projection information for MrSID files from .aux files.
- Added option to generate world files when exporting to BIL/BIP/BSQ format files. While the information in the world files is also in the .HDR file generated, some software only checks for a world file. By default, both will be generated.
- Added support for loading JPG files directly from .zip and .tar.gz archives.
- Fixed loading of some Raster Product Format (RPF) data, like CADRG/CIB data, that had odd security descriptor values in the frame files.
- Display a progress dialog when printing to show the progress of generating the high-resolution image to send to the printer.
- Drastically sped up the export of BMP files when capturing the screen to one or printing to one.
- Made zooming the main map view with the mouse wheel only zoom half as far as the zoom buttons on the toolbar.
- Fixed problems introduced in the v7.00 release with calculating view sheds when the global projection units are either arc seconds or radians.
- Made the feature type lists on the Generic ASCII Import dialog be sorted alphabetically.
- If the datum can not be determined from a GeoTIFF file, ask the user to confirm it if we can't determine the datum from some other source rather than just assuming the datum is WGS84.
- Added ability to generate black-and-white GeoTIFF files that use black for the minimum value rather than white. To do this, select the Grayscale – Min Is Black palette option when exporting a black-and-white GeoTIFF file.

- Made auto-collar cropping work correctly for 1:63K scale Alaska DRGs.
- Improved dialog that appears when TerraServer connections fail.
- Made point features with labels be exported as TEXT entities to DXF files rather than either being split up into separate POINT and TEXT entities or being created as a POINT entity with attributes.
- Improved display of elevation lines in the path profile dialog when the elevation range is small.
- Fixed problems with the wrong font being displayed when editing custom area, line, and point types from the Configuration dialog.
- Corrected datum used for VPF (e.g. VMAP, DNC) data. NAD83 was being used when it should have been WGS84. There was no position error however as those datums are the same positionally.
- Fixed problem with the zoom scale changing after a print preview.
- Fixed problem with grid lines not being saved to raster files or printed if no other vector data is loaded.
- Allowed correct loading of elevation TIFF files that don't correctly specify their min/max elevation range.
- Added option to clamp values outside the valid elevation range to the specified elevation range when modifying the valid elevation range of a layer from the Options button in the Overlay Control Center.
- Added support for loading large TIFF files with YCBCR-encoding (usually JPEG-in-TIFF files).
- When loading ECW and JPEG2000 files with apparently flipped Y coordinates, made it optional to flip the image vertically since it some cases that is not correct.
- Added new red and yellow diagonal crosshair symbols.
- When saving PRJ and world file names (e.g. .tfw, .jgw), use lower case to make it easier to use these files on platforms that are case-sensitive, like Linux.
- Made true 3D DXF polylines be generated when exported 3D line features (such as those from XYZ files) to DXF files.
- Made features from Tiger/Line files include the CFCC (census feature class code) as an attribute of the feature if available.
- Improved generation of range rings to always use a great-circle distance method if possible, even if the current projection is not Geographic.
- Added support for automatically positioning imagery using ASTER browse .meta files.

WHAT'S NEW IN Global Mapper v7.00

- Added support for grouping collections of map files together into a "map catalog". Map catalogs allow you to easily load, view, and manage large collections of data without using too much system memory.
- Added support for tracking real-time GPS locations from Garmin USB GPS devices.
- Added option under the Search menu to allow searching loaded vector data on the name, description, or attribute values. The searching allows both text and numeric comparisons in the search criteria. Features can be edited and deleted directly from the search results.
- Added "Gridding" tab to most exports to allow splitting up the data into regularly spaced

tiles on export if desired rather than just exporting a single file.

- **Measure Tool Changes**
  - Added support for calculating "cut-and-fill" volumes within area measurements and along linear measurements using the Measure Tool (right click to see the Calculate Volumes option).
  - Made the bearing from the start to the end of line features be added when creating new lines using either the Measure tool or the Digitizer tool.
  - Changed the cursor used in the Measure Tool to make it easier to perform precise measurements.
- **Digitizer Tool Changes**
  - Added ability to easily create rectangular, square, circular, elliptical, circular arc, and elliptical arc area and line feature using the Digitizer Tool. There are additional items on the right click popup menu for drawing these shapes.
  - Added option to create concentric range rings (i.e. circles of a given radius) on the right-click menu in the Digitizer Tool.
  - Added an option when editing vector features with the Digitizer Tool to add file link attributes by selecting files rather than manually typing the file names.
  - Made area features selected with the Digitizer Tool be drawn in their normal style during exports cropped to the selected area feature(s).
  - Made point feature labels be displayed even if the points are selected with the Digitizer Tool.
- **3D Path Profile/Line of Sight Tool Changes**
  - Added support for calculating "cut-and-fill" volumes along a path profile using the 3D Path Profile/Line of Sight Tool.
  - Added additional menus to the 3D Path Profile dialog to provide easier access to some of the options. Also made the path details be copied to the clipboard when displayed.
  - Added additional options to the 3D Path Profile dialog for controlling the from/to position display format and the coloring and style of the profile elements.
  - Fixed problems with the path profile tool when the loaded data is not correctly projected (i.e. the lat/lon readout in the status bar reads that the coordinates could not be determined).
  - Made elevation values saved to XYZ files from the path profile dialog have 2 digits after the decimal place rather than 1.
- **3D Viewer Changes**
  - In the 3D viewer, allow the vertical exaggeration to be increased all the way to a factor of 100.0 rather than just 20.0.
  - In the 3D viewer, made the Panorama/Walk mode toolbar button act as a mode just like the Rotate, Move, and Zoom buttons since that is how it behaves.
  - In the 3D viewer, added an option to the Properties dialog to allow the background color to be changed.
  - In the 3D viewer, added an option to the Properties dialog to allow the height used in the Panorama/Walk mode to be manually set and to also specify whether the height should be a constant height relative to the ground or a constant height relative to sea level.

    - In the 3D viewer, made the vertical exaggeration and background color settings be remembered between instances of running the software.
- **Batch Convert/Reproject Changes**
    - Added option to the Batch Convert/Reproject dialog to allow the specification of an additional string to append to the names of the files created during the batch convert process.
    - Added option to the Batch Convert/Reproject dialog to allow some files to only be used as filler for other files. To mark files this way, simply right click on them in the source files list and select the option to just use them as filler files.
    - Added option to create 1-bit black-and-white GeoTIFF files with the Batch Converter.
    - Reduced memory requirements during batch conversion when using all loaded files as filler data and there are lots of files being converted.
- **Image Rectification Changes**
    - When shift-clicking in the Reference pane of the image rectification dialog, made the selected coordinates be rounded to the nearest minute for lat/lon values and the nearest 1000 units for other projections.
    - Made the image rectification dialog start out maximized if the dialog was maximized the last time the user closed the dialog.
    - Made the Latitude and Longitude coordinate values in the ground control point list of the image rectification dialog be displayed using the current Position Display Format selection in the Configuration dialog.
    - When double clicking on a control point in the control point list in the image rectification dialog and the rectify coordinates are lat/lon values, format the projected X and Y coordinate fields using the current Position Display Format from the Configuration dialog.
    - While Shift-clicking in the Zoomed view in the image rectification dialog, automatically add the control point to the control point list use the clicked location.
    - When Ctrl clicking in the Entire Image view in the image rectification dialog, automatically recenter the Reference view if there are enough control points entered to convert the clicked coordinates to a ground coordinate.
    - Make layers that are hidden in the Overlay Control Center still be rendered in the rectify window when re-positioning that layer.
    - Default to use triangulated rectification when rectifying imagery any time that 5 or more control points are entered and the "Automatic" rectification method is selected (previously this happened at 8 control points).
- Added support for using the bounds of a loaded layer when exporting or performing other operations that require bounds in a script file. The LAYER_BOUNDS parameter has been added to several script commands to support this.
- Added ONLY_GENERATE_METADATA parameter to the EXPORT_RASTER script command to allow scripts to just create the metadata files like world files and TAB files when exporting GeoTIFF, JPG, and PNG files rather than doing a full export.
- Made workspace files support relative filenames, allowing data referenced by workspace files to be moved so long as the workspace file is moved as well.

- Added option to Terragen .ter file export to allow the creating of non-square terrain files. This files should work with Terragen 0.9.x and later.
- Added option to create area features from the bounds of the selected layer in the Overlay Control Center by selecting and then right-clicking on the layers that you want to create the bounds from.
- Added support for loading data in the GPS TrackMaker (.gtm) format.
- Added support for the Bonne and Cassini-Soldner projections.
- Added support for non-zero central meridians when using the Gall Stereographic projection.
- Added support for the Hartbeesthoek94 datum.
- Added support for loading DTED files that have HDR and/or VOL records at the beginning.
- Added support for loading ASTER HDF files with .hdf0 and .hdf1 extensions as well as additional variations of ASTER SWIR data.
- Fixed export of high-color (24-bit and above) and 8-bit grayscale TIFF files to image-optimized palette-based TIFF and PNG formats when the TIFF file incorrectly specifies that it is grayscale and not RGB.
- Sped up display of TerraServer data that crosses UTM zone boundaries.
- Added support for finding world files with a .wld extension when loading most imagery formats (i.e. BMP, JPG, TIFF, GIF, and PNG).
- Corrected placement of Hawaiian data loaded from Tiger files (the NAD83 datum was being used rather than Old Hawaiian Mean).
- Made the size of the feature info dialog be saved between sessions.
- Fixed decoding of State Plane projections from new format PRJ files. The problem was introduced in the v6.09 release and made some PRJ files with State Plane projections decode the projection into the core projection rather than keeping it as State Plane. This should not have affected any coordinates.
- Corrected incorrect interpretation of "Foot" string from new format PRJ files. Previously this was interpreted as US Survey Feet when it should have been interpreted as International Feet.
- Fixed application crash loading some slightly odd .zip files.
- Made additional digits of precision be stored for settings like custom grid spacing.
- Manually compute the min/max sample values for USGS DEMs that have a non-unity Z resolution since they are often stored incorrectly, resulting in odd shading in Global Mapper. This will apply to things like decimeter and centimeter DEMs.
- Made full extents of polar data reprojected from a polar stereographic projection to another projection be displayed whenever possible (previously the part nearest the pole and near the anti-meridian could get clipped off).
- Increased the maximum number of grid lines that could be displayed when using the custom grid spacing setting.
- Made TIFF files that use a transformation matrix for position information be automatically positioned rather than requiring rectification.
- Made degree symbols display correctly on Asian versions of Windows.
- Corrected drawing and zooming in on ECW and JPEG2000 files that have flipped Y coordinate values in the header.

- Added option to contour generation to control whether or not small gaps in the data are filled (previously they always were).
- Improved the speed of exporting downloaded TerraServer data to new raster files.
- Corrected display of zone numbers for Gauss Krueger Germany projection.
- Only show the warning message about user-defined datums in GeoTIFF files being interpreted as WGS84 once each session.
- When changing the current view projection, maintain the current view window if possible rather than zooming out to all loaded data.
- Added option to initialize sample spacing values to the current screen sample spacing from the dialog allowing specification of sample spacing in units other than the current projection units when performing raster and elevation exports.
- Added red, blue, green, and white dot symbols.